

B43305B9477M060

B43305B9477M060 Information

Contraction of the second seco	 B43305B9477M060 EPCOS (TDK) Capacitors Aluminum Electrolytic Capacitors CAP ALUM 470UF 20% 400V SNAP Radial, Can - Snap-In For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B43305B9477M060 Specifications

Manufacturer Part NumberB43305B9477M060ManufacturerEPCOS (TDK)CategoryCapacitorsPackageAluninum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43305Capacitance470µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)290 mOhm @ 100HzOperating Temperature2000 Hrs @ 85°COperating Temperature2000 Hrs @ 85°CApplicationsGeneral PurposeApplicationsSal @ 100HzRipple Current - High Frequency-Impedance300 mOhmsLad Spacing0394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43305Capacitance470µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)290 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency2.23A @ 100HzImpedance390 mOhmsLead Spacing0.394" (10.00mm)	
Harian Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43305Capacitance470μFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)200 mOhm @ 100HzESR (Equivalent Series Resistance)2000 Hrs @ 85°COperating Temperature6000 Hrs @ 85°CPolarization90arApplicationsGeneral PurposeRipple Current - Low Frequency-Apple Current - High Frequency300 mOhmsLad Spacing309 mOhms	
PackageRadial, Can - Snap-InSeriesB43305Capacitance470μFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)290 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - High Frequency-Impedance390 mOhmsLead Spacing0.394" (10.00mm)	
SeriesB43305Capacitance470µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)290 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency-Impedance390 mOhmsLead Spacing0.394" (10.00mm)	
Capacitance470μFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)290 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency2.23A @ 100HzImpedance390 mOhmsLead Spacing0.394" (10.00mm)	
Tolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)290 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency-Impedance390 mOhmsLead Spacing0.394" (10.00mm)	
Voltage - Rated400VESR (Equivalent Series Resistance)290 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.23A @ 100HzRipple Current - High Frequency-Impedance390 mOhmsLead Spacing0.394" (10.00mm)	
For the constraint of the constr	
Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.23A @ 100HzRipple Current - High Frequency-Impedance390 mOhmsLead Spacing0.394" (10.00mm)	
Operating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.23A @ 100HzRipple Current - High Frequency-Impedance390 mOhmsLead Spacing0.394" (10.00mm)	
PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.23A @ 100HzRipple Current - High Frequency-Impedance390 mOhmsLead Spacing0.394" (10.00mm)	
ApplicationsGeneral PurposeRipple Current - Low Frequency2.23A @ 100HzRipple Current - High Frequency-Impedance390 mOhmsLead Spacing0.394" (10.00mm)	
Ripple Current - Low Frequency2.23A @ 100HzRipple Current - High Frequency-Impedance390 mOhmsLead Spacing0.394" (10.00mm)	
Ripple Current - High Frequency-Impedance390 mOhmsLead Spacing0.394" (10.00mm)	
Impedance390 mOhmsLead Spacing0.394" (10.00mm)	
Lead Spacing 0.394" (10.00mm)	
Size / Dimension 1 181" Dia (30.00mm)	
Height - Seated (Max) 1.654" (42.00mm)	
Surface Mount Land Size -	
Mounting Type Through Hole	
Package / Case Radial, Can - Snap-In	
Repo	

B43305B9477M060 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B43305B9477M060 Payment Methods





If you have any question about B43305B9477M060, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com