

B43305C9477M82

B43305C9477M82 Information

| Heisener.com | Part Number Manufacturer Category Description Package | B43305C9477M82 EPCOS (TDK) Capacitors Aluminum Electrolytic Capacitors CAP ALUM 470UF 20% 400V SNAP Radial, Can - Snap-In - 3 Lead For the pricing/inventory/lead time, please contact | |
|--------------------|---|--|-----------------|
| For Reference Only | | us Website: https://www.heisener.com E-mail: salesdept@heisener.com | Request a Quote |

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B43305C9477M82 Specifications

| Manufacturer Part NumberB43305C9477M82ManufacturerEPCOS (TDK)CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-In - 3 LeadSeriesB43305Capacitance470µFTolerance2000 VVoltage - Rated400VESR (Equivalent Series Resistance)2000 Mrs @ 85°COperating Temperature40°C ~ 85°CPolarizationGeneral PurposeRipple Current - Low Frequency2.05A @ 100HzRipple Current - High Frequency390 mOhmsLead Spacing390 mOhmsLead Spacing1.378° Dia (35.00mm)Size / Dimension1.260° (32.00mm)Surface Mount Land Size-Mouning TypeThrough HolePours1.700 Mouning TypePours1.7000 Mouning TypePours1.7000 Mouning Type | - | |
|---|------------------------------------|---|
| CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-In - 3 LeadSeriesB43305Capacitance470µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)290 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance390 mOhmsLiad Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeFnrough HolePackage / CaseRatial, Can - Snap-In - 3 Lead | Manufacturer Part Number | B43305C9477M82 |
| Auminum Electrolytic CapacitorsPackageRadial, Can - Snap-In - 3 LeadSeriesB43305Capacitance470µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)290 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeRipple Current - Low Frequency2.05A @ 100HzRipple Current - High Frequency-Impedance390 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeFhrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead | Manufacturer | EPCOS (TDK) |
| PackageRadial, Can - Snap-In - 3 LeadSeriesB43305Capacitance470µFTolerance±20%Voltage - Rated00VESR (Equivalent Series Resistance)290 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature440°C ~ 85°CPolarizationGeneral PurposeRipple Current - Low Frequency2.05A @ 100HzImpedance0.94" (10.00mm)Lied Spacing1.378" Dia (35.00mm)Size / Dimension1.260" (32.00mm)Sirface Mount Land Size-Mounting TypeFhough HolePackage / CaseRatial, Can - Snap-In - 3 Lead | Category | Capacitors |
| SeriesB43305Capacitance470µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)290 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency2.05A @ 100HzInpedance390 mOhmsSize / Dimension1.378" Dia (35.00mm)Size / Dimension1.260" (32.00mm)Surface Mount Land Size-Mounting TypeFhrough HolePackage / CaseKadia, Can - Snap-In - 3 Lead | | Aluminum Electrolytic Capacitors |
| Capacitance470µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)200 mDnm @ 100HzESR (Equivalent Series Resistance)2000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency205 A @ 100HzInpedance300 mOhnsIsze / Dimension1.378° Dia (35.00mm)Size / Dimension1.378° Dia (35.00mm)Size / Dimension1.260° (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKadi, Can - Snap-In - 3 Lead | Package | Radial, Can - Snap-In - 3 Lead |
| Tolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)290 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.05A @ 100HzImpedance390 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeFhrough HolePackage / CaseRatial, Can - Snap-In - 3 Lead | Series | B43305 |
| Voltage - Rated400VESR (Equivalent Series Resistance)290 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.05A @ 100HzImpedance390 mOhmsIcad Spacing0.394" (10.00mm)Size / Dinension1.378" Dia (35.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can - Snap-In - 3 Lead | Capacitance | 470µF |
| ConstraintSectorESR (Equivalent Series Resistance)290 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.05A @ 100HzRipple Current - High Frequency390 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.260" (32.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeFackage / Case | Tolerance | $\pm 20\%$ |
| Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.05A @ 100HzRipple Current - High Frequency-Impedance390 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeRadial, Can - Snap-In - 3 Lead | Voltage - Rated | 400V |
| Operating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.05A @ 100HzRipple Current - High Frequency-Impedance390 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead | ESR (Equivalent Series Resistance) | 290 mOhm @ 100Hz |
| PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.05A @ 100HzRipple Current - High Frequency-Impedance390 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead | Lifetime @ Temp. | 2000 Hrs @ 85°C |
| ApplicationsGeneral PurposeRipple Current - Low Frequency2.05A @ 100HzRipple Current - High Frequency-Impedance390 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead | Operating Temperature | $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ |
| Ripple Current - Low Frequency2.05A @ 100HzRipple Current - High Frequency-Impedance390 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead | Polarization | Polar |
| In a randomRipple Current - High Frequency-Impedance390 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead | Applications | General Purpose |
| Impedance390 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead | Ripple Current - Low Frequency | 2.05A @ 100Hz |
| Lead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead | Ripple Current - High Frequency | - |
| Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead | Impedance | 390 mOhms |
| Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead | Lead Spacing | 0.394" (10.00mm) |
| Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead | Size / Dimension | 1.378" Dia (35.00mm) |
| Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead | Height - Seated (Max) | 1.260" (32.00mm) |
| Package / Case Radial, Can - Snap-In - 3 Lead | Surface Mount Land Size | - |
| | Mounting Type | Through Hole |
| Report error | Package / Case | Radial, Can - Snap-In - 3 Lead |
| Report entri | | Report errors? |

B43305C9477M82 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B43305C9477M82 Payment Methods





If you have any question about B43305C9477M82, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com