



B43305D9337M62 Information

Heisener.com

Part NumberB43305D9337M62ManufacturerEPCOS (TDK)CategoryCapacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 330UF 20% 400V SNAP

Package Radial, Can - Snap-In - 3 Lead

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









B43305D9337M62 Specifications

Manufacturer Part NumberB43305D9337M62ManufacturerEPCOS (TDK)CategoryCapacitorsPackageRadial, Can - Snap-In - 3 LeadSeriesB43305Capacitance330µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)410 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.55A @ 100HzRipple Current - High Frequency-Inmedance560 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	L	
CategoryCapacitorsPackageRadial, Can - Snap-In - 3 LeadSeriesB43305Capacitance330µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)410 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.55A @ 100HzRipple Current - High Frequency-Impedance560 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Manufacturer Part Number	B43305D9337M62
Package Radial, Can - Snap-In - 3 Lead Series B43305 Capacitance 330µF Tolerance ±20% Voltage - Rated 400V ESR (Equivalent Series Resistance) 410 mOhm @ 100Hz Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.55A @ 100Hz Ripple Current - High Frequency - Impedance 560 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 1.063" (27.00mm) Surface Mount Land Size - Mounting Type Through Hole	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-In - 3 LeadSeriesB43305Capacitance330μFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)410 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.55A @ 100HzRipple Current - High Frequency-Impedance560 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Category	Capacitors
Series B43305 Capacitance 330µF Tolerance ±20% Voltage - Rated 400V ESR (Equivalent Series Resistance) 410 mOhm @ 100Hz Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.55A @ 100Hz Ripple Current - High Frequency - Impedance 560 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 1.063" (27.00mm) Surface Mount Land Size - Mounting Type Through Hole		Aluminum Electrolytic Capacitors
Capacitance330μFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)410 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.55A @ 100HzRipple Current - High Frequency-Impedance560 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Package	Radial, Can - Snap-In - 3 Lead
Tolerance ±20% Voltage - Rated 400V ESR (Equivalent Series Resistance) 410 mOhm @ 100Hz Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.55A @ 100Hz Ripple Current - High Frequency - Impedance 560 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 1.063" (27.00mm) Surface Mount Land Size - Mounting Type Through Hole	Series	B43305
Voltage - Rated400VESR (Equivalent Series Resistance)410 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.55A @ 100HzRipple Current - High Frequency-Impedance560 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Capacitance	330μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.55A @ 100Hz Ripple Current - High Frequency - Impedance 560 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type 410 mOhm @ 100Hz 2000 Hrs @ 85°C - 40°C ~ 85°C Polar - 40°C ~ 85°C Folar - 40°C ~ 85°C Folar - 40°C ~ 85°C - 40°C ~ 85	Tolerance	±20%
Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.55A @ 100Hz Ripple Current - High Frequency - Impedance 560 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 1.063" (27.00mm) Surface Mount Land Size - Mounting Type Through Hole	Voltage - Rated	400V
Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency 1.55A @ 100Hz Ripple Current - High Frequency - Impedance 560 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 1.063" (27.00mm) Surface Mount Land Size Mounting Type Through Hole	ESR (Equivalent Series Resistance)	410 mOhm @ 100Hz
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.55A @ 100Hz Ripple Current - High Frequency - Impedance 560 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 1.063" (27.00mm) Surface Mount Land Size - Mounting Type Through Hole	Lifetime @ Temp.	2000 Hrs @ 85°C
Applications Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing Current - Dimension 1.378" Dia (35.00mm) Height - Seated (Max) Surface Mount Land Size Mounting Type General Purpose 1.55A @ 100Hz - 1.063" (27.00mm) 1.063" (27.00mm) Through Hole	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency Ripple Current - High Frequency Impedance S60 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 1.063" (27.00mm) Surface Mount Land Size Mounting Type Through Hole	Polarization	Polar
Ripple Current - High Frequency Impedance 560 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 1.063" (27.00mm) Surface Mount Land Size - Mounting Type Through Hole	Applications	General Purpose
Impedance560 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Ripple Current - Low Frequency	1.55A @ 100Hz
Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 1.063" (27.00mm) Surface Mount Land Size - Mounting Type Through Hole	Ripple Current - High Frequency	-
Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Impedance	560 mOhms
Height - Seated (Max) Surface Mount Land Size Mounting Type 1.063" (27.00mm) - Through Hole	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size - Mounting Type Through Hole	Size / Dimension	1.378" Dia (35.00mm)
Mounting Type Through Hole	Height - Seated (Max)	1.063" (27.00mm)
	Surface Mount Land Size	-
Package / Case Radial, Can - Snap-In - 3 Lead	Mounting Type	Through Hole
	Package / Case	Radial, Can - Snap-In - 3 Lead
Report errors?		Report errors?

B43305D9337M62 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

B43305D9337M62 Payment Methods



















B43305D9337M62 Shipping Methods













If you have any question about B43305D9337M62, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com