

# B43305E2108M000

Request a Quote

#### B43305E2108M000 Information

Heisener.com	Part Number	B43305E2108M000
	Manufacturer	EPCOS (TDK)
	Category	Capacitors Aluminum Electrolytic Capacitors
	Description	CAP ALUM 1000UF 20% 250V SNAP
	Package	Radial, Can - Snap-In
		For the pricing/inventory/lead time, please contact
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



### B43305E2108M000 Specifications

Manufacturer Part NumberB43305E2108M000ManufacturerEPCOS (TDK)CategoryCapacitorsPackageAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43305Capacitance1000µFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)130 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationGeneral PurposeRipple Current - High Frequency3.08A @ 100HzLiedapscing3.08A @ 100HzLiedapscing0.304" (10.00mm)Size / Dimension0.394" (10.00mm)Size / Dimension2.047" (52.00mm)Surface Mourt Land Size-Mounting TypeThrough HolePackage / CaseKadia, Can - Snap-In	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43305Capacitance1000µFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)130 mOnm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency3.08A @ 100HzRipple Current - High Frequency1.0Liad Spacing0.394" (10.0mm)Size / Dimension0.984" Dia (25.00mm)Kirder (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Manufacturer Part Number	B43305E2108M000
IdentifyAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43305Capacitance1000µFTolerance20%Voltage - Rated50VESR (Equivalent Series Resistance)30 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarization6neral PurposeApplications6neral PurposeRipple Current - Low Frequency3.08A @ 100HzImpedance180 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.948" Dia (25.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-InSeriesB43305Capacitance1000μFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)130 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency3.08A @ 100HzImpedance180 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Category	Capacitors
SeriesB43305Capacitance1000µFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)130 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency3.08A @ 100HzImpedance180 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough Hole		Aluminum Electrolytic Capacitors
Capacitance1000µFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)130 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency3.08A @ 100HzInpedance180 mOhmsLead Spacing0.934" (10.00mm)Size / Dimension0.948" Dia (25.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Package	Radial, Can - Snap-In
Totance±2%Voltage - Rated250VESR (Equivalent Series Resistance)130 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.08A @ 100HzImpedance180 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Series	B43305
Voltage - Rated250VESR (Equivalent Series Resistance)130 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.08A @ 100HzRipple Current - High Frequency-Impedance180 mOhmsLead Spacing0.934" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Capacitance	1000µF
ESR (Equivalent Series Resistance)130 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.08A @ 100HzRipple Current - High Frequency-Impedance180 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Tolerance	$\pm 20\%$
Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.08A @ 100HzRipple Current - High Frequency-Impedance180 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Voltage - Rated	250V
Operating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.08A @ 100HzRipple Current - High Frequency-Impedance180 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	ESR (Equivalent Series Resistance)	130 mOhm @ 100Hz
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.08A @ 100HzRipple Current - High Frequency-Impedance180 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Lifetime @ Temp.	2000 Hrs @ 85°C
ApplicationsGeneral PurposeRipple Current - Low Frequency3.08A @ 100HzRipple Current - High Frequency-Impedance180 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Operating Temperature	$-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$
Ripple Current - Low Frequency3.08A @ 100HzRipple Current - High Frequency-Impedance180 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Polarization	Polar
In a constructionIn a constructionRipple Current - High Frequency-Impedance180 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Applications	General Purpose
Impedance180 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Ripple Current - Low Frequency	3.08A @ 100Hz
Lead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Ripple Current - High Frequency	-
Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Impedance	180 mOhms
Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size-Mounting TypeThrough Hole	Size / Dimension	0.984" Dia (25.00mm)
Mounting Type Through Hole	Height - Seated (Max)	2.047" (52.00mm)
	Surface Mount Land Size	-
Package / Case Radial, Can - Snap-In	Mounting Type	Through Hole
	Package / Case	Radial, Can - Snap-In
Report erro		Report errors?

#### B43305E2108M000 Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE BUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### B43305E2108M000 Payment Methods



If you have any question about B43305E2108M000, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com