

# B43305E2158M60

Request a Quote

### B43305E2158M60 Information

Heisener.com	Part Number	B43305E2158M60
	Manufacturer	EPCOS (TDK)
	Category	Capacitors Aluminum Electrolytic Capacitors
	Description	CAP ALUM 1500UF 20% 250V SNAP
	Package	Radial, Can - Snap-In
		For the pricing/inventory/lead time, please contact
For Reference Only		us
		Website: https://www.heisener.com
		E-mail: salesdept@heisener.com



Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



# B43305E2158M60 Specifications

CategoryCapacitorsPackageRadial, Can - Snap-InPackageB43305SeriesB43305Capacitance1500µFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)85 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency3.78A @ 100HzRipple Current - High Frequency-Impedance120 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Package / CaseRatial, Can - Snap-In	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43305Capacitance1500µFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)85 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - High Frequency-Impedance120 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Manufacturer Part Number	B43305E2158M60
Aluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43305Capacitance1500μFTolerance-20%Voltage - Rated250VESR (Equivalent Series Resistance)S5 mOhm @ 100HzOperating Temperature2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeRipple Current - Low Frequency3.78A @ 100HzRipple Current - High Frequency-Impedance1.00mminLided Spacing3.394" (10.00mmin)Siz / Dimension1.181" Dia (30.00mmin)Siz / Dimension2.047" (52.00mmin)Sirface Mount Land Size-Mounting TypeFrequencyPackage / CaseKadial, Can - Snap-In	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-InSeriesB43305Capacitance1500μFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)85 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationGeneral PurposeRiple Current - Low Frequency3.78A @ 100HzRiple Current - High Frequency-Impedance120 mOhmsLiad Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Size / Dimension2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Category	Capacitors
SeriesB43305Capacitance1500µFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)85 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.78A @ 100HzLiad Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKadial, Can - Snap-In		Aluminum Electrolytic Capacitors
Capacitance1500µFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)85 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.78A @ 100HzImpedance120 mOhmsLiad Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can - Snap-In	Package	Radial, Can - Snap-In
Tolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)85 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.78A @ 100HzImpedance120 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can - Snap-In	Series	B43305
Voltage - Rated250VESR (Equivalent Series Resistance)85 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.78A @ 100HzLiad Spacing120 mOhmsImpedance0.394" (10.00mm)Lead Spacing1.181" Dia (30.00mm)Size / Dimension2.047" (52.00mm)Height - Seated (Max)-Nurting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Capacitance	1500µF
ESR ESR Esr Polarization 85 mOhm @ 100Hz   Diferiam @ Tempe. 2000 Hrs @ 85°C 2000 Hrs @ 85°C   Operating Temperature -40°C ~ 85°C 2000 Hrs @ 85°C   Polarization Polar 2000 Hrs @ 85°C   Applications General Purpose 2000 Hrs @ 85°C   Ripple Current - Low Frequency S78A @ 100Hz 2000 Hrs @ 85°C   Impedance 120 mOhms 2000 Hrs @ 85°C   Lead Spacing 0.394" (10.00mm) 2000 Hrs @ 85°C   Size / Dimension 1.181" Dia (30.00mm) 2000 Hrs @ 85°C   Surface Mount Land Size - -   Mounting Type - -   Package / Case Radial, Can - Snap-In	Tolerance	±20%
Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.78A @ 100HzRipple Current - High Frequency-Impedance120 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeFackage / CaseRadial, Can - Snap-InRadial, Can - Snap-In	Voltage - Rated	250V
Operating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.78A @ 100HzRipple Current - High Frequency-Impedance120 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	ESR (Equivalent Series Resistance)	85 mOhm @ 100Hz
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.78A @ 100HzRipple Current - High Frequency-Impedance120 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lifetime @ Temp.	2000 Hrs @ 85°C
ApplicationsGeneral PurposeRipple Current - Low Frequency3.78A @ 100HzRipple Current - High Frequency-Impedance120 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency3.78A @ 100HzRipple Current - High Frequency-Impedance120 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Polarization	Polar
In a constraint of a constrain	Applications	General Purpose
Impedance120 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - Low Frequency	3.78A @ 100Hz
IILead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - High Frequency	-
Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Impedance	120 mOhms
Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Size / Dimension	1.181" Dia (30.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Height - Seated (Max)	2.047" (52.00mm)
Package / Case Radial, Can - Snap-In	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can - Snap-In
		Report errors?

#### B43305E2158M60 Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

# B43305E2158M60 Payment Methods



If you have any question about B43305E2158M60, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com