



B43305F2188M62 Information

Heisener.com

Part Number B43305F2188M62 Manufacturer EPCOS (TDK) Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 1800UF 20% 250V SNAP

Radial, Can - Snap-In - 3 Lead **Package**

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









B43305F2188M62 Specifications

Manufacturer Part Number B43305F2188M62 Manufacturer EPCOS (TDK) Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Snap-In - 3 Lead Series B43305 Capacitance 1800μF Tolerance ±20% Voltage - Rated 250V ESR (Equivalent Series Resistance) 70 mOhm @ 100Hz Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 3.52A @ 100Hz Ripple Current - High Frequency - Impedance 100 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 1.850" (47.00mm)	4	
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Snap-In - 3 Lead Series B43305 Capacitance 1800μF Tolerance ±20% Voltage - Rated 250V ESR (Equivalent Series Resistance) 70 mOhm @ 100Hz Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 3.52A @ 100Hz Ripple Current - High Frequency - Impedance 100 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 1.850" (47.00mm)	Manufacturer Part Number	B43305F2188M62
Aluminum Electrolytic Capacitors Package Radial, Can - Snap-In - 3 Lead Series B43305 Capacitance 1800µF Tolerance ±20% Voltage - Rated 250V ESR (Equivalent Series Resistance) 70 mOhm @ 100Hz Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance 100 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max)	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-In - 3 LeadSeriesB43305Capacitance1800μFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)70 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.52A @ 100HzRipple Current - High Frequency-Impedance100 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.850" (47.00mm)	Category	Capacitors
Series B43305 Capacitance 1800μF Tolerance ±20% Voltage - Rated 250V ESR (Equivalent Series Resistance) 70 mOhm @ 100Hz Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 3.52A @ 100Hz Ripple Current - High Frequency - Impedance 100 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 1.850" (47.00mm)		Aluminum Electrolytic Capacitors
Capacitance 1800µF Tolerance ±20% Voltage - Rated 250V ESR (Equivalent Series Resistance) 70 mOhm @ 100Hz Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 3.52A @ 100Hz Ripple Current - High Frequency - Impedance 100 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 1.850" (47.00mm)	Package	Radial, Can - Snap-In - 3 Lead
Tolerance ±20% Voltage - Rated 250V ESR (Equivalent Series Resistance) 70 mOhm @ 100Hz Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 3.52A @ 100Hz Ripple Current - High Frequency - Impedance 100 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 1.850" (47.00mm)	Series	B43305
Voltage - Rated ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing 0.394" (10.00mm) Size / Dimension Height - Seated (Max) 250V 250V 250V 250V 2600 70 mOhm @ 100Hz 40°C ~ 85°C 6eneral Purpose 3.52A @ 100Hz - 100 mOhms 1.378" Dia (35.00mm)	Capacitance	1800μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance 100 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension Height - Seated (Max) 70 mOhm @ 100Hz 2000 Hrs @ 85°C -40°C ~ 85°C Polar -40°C ~ 85°C Polar -40°C ~ 85°C Polar -40°C ~ 85°C -40°C	Tolerance	±20%
Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing 100 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 1.850" (47.00mm)	Voltage - Rated	250V
Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance 100 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 1.850" (47.00mm)	ESR (Equivalent Series Resistance)	70 mOhm @ 100Hz
Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing Dimension 1.378" Dia (35.00mm) Height - Seated (Max) Polar Polar Polar Polar Polar Oceneral Purpose 3.52A @ 100Hz - 100 mOhms 0.394" (10.00mm) 1.378" Dia (35.00mm)	Lifetime @ Temp.	2000 Hrs @ 85°C
Applications Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing Lead Spacing Size / Dimension Height - Seated (Max) General Purpose 3.52A @ 100Hz - 100 mOhms 0.394" (10.00mm) 1.378" Dia (35.00mm) 1.850" (47.00mm)	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency Ripple Current - High Frequency Impedance 100 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 1.850" (47.00mm)	Polarization	Polar
Ripple Current - High Frequency - Impedance 100 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 1.850" (47.00mm)	Applications	General Purpose
Impedance 100 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 1.850" (47.00mm)	Ripple Current - Low Frequency	3.52A @ 100Hz
Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 1.850" (47.00mm)	Ripple Current - High Frequency	-
Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 1.850" (47.00mm)	Impedance	100 mOhms
Height - Seated (Max) 1.850" (47.00mm)	Lead Spacing	0.394" (10.00mm)
-	Size / Dimension	1.378" Dia (35.00mm)
	Height - Seated (Max)	1.850" (47.00mm)
Surface Mount Land Size -	Surface Mount Land Size	-
Mounting Type Through Hole	Mounting Type	Through Hole
Package / Case Radial, Can - Snap-In - 3 Lead	Package / Case	Radial, Can - Snap-In - 3 Lead
Report errors?		Report errors?

B43305F2188M62 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

B43305F2188M62 Payment Methods



















B43305F2188M62 Shipping Methods













If you have any question about B43305F2188M62, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com