

# B43305G2567M87

#### B43305G2567M87 Information

Heisener.com	 B43305G2567M87 EPCOS (TDK) Capacitors Aluminum Electrolytic Capacitors CAP ALUM 560UF 20% 250V SNAP Radial, Can - Snap-In For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



### B43305G2567M87 Specifications

Manufacturer Part NumberB43305G2567M87ManufacturerEPCOS (TDK)CategoryCapacitorsCategoryAluninum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43305Capacitance560µFTolerance±20%Voltage - Rated250VESK Equivalent Series Resistance)230 mOhm @100HzDifferime @ Temp.2000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationPolarApplicationsGenera PurposeRipple Current - Low Frequency1.84A @ 100HzRipple Current - High Frequency0.391" (10.00mm)Lied Spacing0.394" (10.00mm)Size / Dimension1.81" Dia (30.00mm)Munting Type-Mounting TypeFrequencyRice / Case2.000 Hrs @ 8.000 HrsRice / Case3.000 HrsSize / Dimension1.81" Dia (30.000 HrsSi	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43305Capacitance560µFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)230 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeRipple Current - Low Frequency1.84A @ 100HzRipple Current - High Frequency-Imedance0.394" (10.00mm)Lied Spacing1.181" Dia (30.00mm)Size / Dimension1.181" Dia (30.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Manufacturer Part Number	B43305G2567M87
IdentifyAluminum Electrolytic CapacitonsPackageRadial, Can - Snap-InSeriesB43305Capacitance560µFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)300 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationFolareApplicationsGeneral PurposeRipple Current - High Frequency1.84A @ 100HzLinedance310 mOhmsLead Spacing0.394' (1.00mm)Size / Dimension1.81" Dia (30.00ml)Size / Dimension1.063' (27.00ml)Hight - Seated (Max)-Mounting TypeForough HolePackage / CaseKadia, Can - Snap-In	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-InSeriesB43305Capacitance560µFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)230 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency1.84A @ 100HzImpedance0394" (10.00mm)Lied Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Size / Dimension-Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Pounting TypeFhrough HolePackage / CaseKadia, Can - Snap-In	Category	Capacitors
SeriesB43305Capacitance560µFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)230 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency1.84A @ 100HzIded Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Size / Dimension1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKadial, Can - Snap-In		Aluminum Electrolytic Capacitors
Capacitance560µFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)200 mm of 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationFolarApplicationsGeneral PurposeRipple Current - High Frequency.Inpedance310 mOhmsSize / Dimension.181° Dia (30.00mm)Size / Dimension.181° Dia (30.00mm)Surface Mount Land Size.Mounting TypeThrough HolePackage / CaseMail, Can - Snap-In	Package	Radial, Can - Snap-In
Tolerance±0%Yoltage - Rated250VESR (Equivalent Series Resistance)230 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency1.84A @ 100HzImpedance310 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeFurough Lande StatePackage / CaseRadial, Can - Snap-In	Series	B43305
Voltage - Rated250VESR (Equivalent Series Resistance)230 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.84A @ 100HzHippedance310 mOhmsIstad Spacing0.394" (10.00mm)Size / Dimension1.083" (27.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Hounting TypeFrequencyPackage / CaseRadial, Can - Snap-In	Capacitance	560µF
FSR (Equivalent Series Resistance)230 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.84A @ 100HzRipple Current - High Frequency-Impedance310 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.063" (27.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeRadial, Can - Snap-In	Tolerance	±20%
Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.84A @ 100HzRipple Current - High Frequency-Impedance310 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Voltage - Rated	250V
Operating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.84A @ 100HzRipple Current - High Frequency-Impedance310 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max).Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	ESR (Equivalent Series Resistance)	230 mOhm @ 100Hz
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.84A @ 100HzRipple Current - High Frequency-Impedance310 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lifetime @ Temp.	2000 Hrs @ 85°C
ApplicationsGeneral PurposeRipple Current - Low Frequency1.84A @ 100HzRipple Current - High Frequency-Impedance310 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency1.84A @ 100HzRipple Current - High Frequency-Impedance310 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.081" Dia (30.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Polarization	Polar
In Provide ArrorRipple Current - High Frequency-Impedance310 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Applications	General Purpose
Impedance310 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - Low Frequency	1.84A @ 100Hz
Lead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - High Frequency	-
Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Impedance	310 mOhms
Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Size / Dimension	1.181" Dia (30.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Height - Seated (Max)	1.063" (27.00mm)
Package / Case Radial, Can - Snap-In	Surface Mount Land Size	-
	Mounting Type	Through Hole
	Package / Case	Radial, Can - Snap-In
Report erro		Report errors?

#### B43305G2567M87 Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE BUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### B43305G2567M87 Payment Methods





If you have any question about B43305G2567M87, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com