



B43310A5568M000 Information



For Reference Only

Part Number B43310A5568M000
Manufacturer EPCOS (TDK)
Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 5600UF 20% 450V SCREW

Package Radial, Can - Screw Terminals

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









B43310A5568M000 Specifications

Manufacturer Part Number B43310A5568M000 Manufacturer EPCOS (TDK) Category Capacitors Package Radial, Can - Screw Terminals Series B43310 Capacitance 5600µF Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) 34 mOhm @ 120Hz Lifetine @ Temp. 2000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 13.3A @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing 1.248" (31.70mm) Size / Dimension 3.028" Dia (76.90mm) Height - Seated (Max) 6.102" (155.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals		
Category Capacitors Package Radial, Can - Screw Terminals Series B43310 Capacitance 5600μF Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) 34 mOhm @ 120Hz Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 13.3A @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing 1.248" (31.70mm) Size / Dimension 3.028" Dia (76.90mm) Height - Seated (Max) 6.102" (155.00mm) Surface Mount Land Size - Mounting Type Chassis Mount	Manufacturer Part Number	B43310A5568M000
PackageAluminum Electrolytic CapacitorsPackageRadial, Can - Screw TerminalsSeriesB43310Capacitance5600μFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)34 mOhm @ 120HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-25°C ~ 85°CPolarApplicationsRipple Current - Low Frequency13.3A @ 120HzRipple Current - High Frequency-Impedance-Lead Spacing1.248" (31.70mm)Size / Dimension3.028" Dia (76.90mm)Height - Seated (Max)6.102" (155.00mm)Surface Mount Land Size-Mounting TypeChassis Mount	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Screw TerminalsSeriesB43310Capacitance5600µFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)34 mOhm @ 120HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-25°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency13.3A @ 120HzRipple Current - High Frequency-Impedance-Lead Spacing1.248" (31.70mm)Size / Dimension3.028" Dia (76.90mm)Height - Seated (Max)6.102" (155.00mm)Surface Mount Land Size-Mounting TypeChassis Mount	Category	Capacitors
Series B43310 Capacitance 5600μF Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) 34 mOhm @ 120Hz Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 13.3A @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing 1.248" (31.70mm) Size / Dimension 3.028" Dia (76.90mm) Height - Seated (Max) 6.102" (155.00mm) Surface Mount Land Size - Mounting Type Chassis Mount		Aluminum Electrolytic Capacitors
Capacitance 5600µF Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) 34 mOhm @ 120Hz Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 13.3A @ 120Hz Ripple Current - High Frequency - Lead Spacing 1.248" (31.70mm) Size / Dimension 3.028" Dia (76.90mm) Height - Seated (Max) 6.102" (155.00mm) Surface Mount Land Size - Mounting Type Chassis Mount	Package	Radial, Can - Screw Terminals
Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) 34 mOhm @ 120Hz Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 13.3A @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing 1.248" (31.70mm) Size / Dimension 3.028" Dia (76.90mm) Height - Seated (Max) 6.102" (155.00mm) Surface Mount Land Size - Mounting Type Chassis Mount	Series	B43310
Voltage - Rated450VESR (Equivalent Series Resistance)34 mOhm @ 120HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-25°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency13.3A @ 120HzRipple Current - High Frequency-Lead Spacing1.248" (31.70mm)Size / Dimension3.028" Dia (76.90mm)Height - Seated (Max)6.102" (155.00mm)Surface Mount Land Size-Mounting TypeChassis Mount	Capacitance	5600μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing 1.248" (31.70mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type 34 mOhm @ 120Hz 34 mOhm @ 120Hz 34 mOhm @ 120Hz 36 mS°C -25°C ~ 85°C Polar -25°C ~ 85°C General Purpose 1.3.3 A @ 120Hz -21.3 A @ 120Hz -22.3 A @ 120Hz -23.4 B @ 1.2	Tolerance	±20%
Lifetime @ Temp. Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 13.3A @ 120Hz Ripple Current - High Frequency Impedance - Lead Spacing 1.248" (31.70mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type 2000 Hrs @ 85°C -25°C ~ 85°C General Purpose General Purpose 1.3.3A @ 120Hz 1.3.3A @ 120Hz 1.3.3A @ 120Hz 1.3.3A @ 120Hz Chassis Mount	Voltage - Rated	450V
Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency	ESR (Equivalent Series Resistance)	34 mOhm @ 120Hz
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 13.3A @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing 1.248" (31.70mm) Size / Dimension 3.028" Dia (76.90mm) Height - Seated (Max) 6.102" (155.00mm) Surface Mount Land Size - Mounting Type Chassis Mount	Lifetime @ Temp.	2000 Hrs @ 85°C
Applications Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing 1.248" (31.70mm) Size / Dimension 3.028" Dia (76.90mm) Height - Seated (Max) Surface Mount Land Size Mounting Type General Purpose 13.3A @ 120Hz - Chassis Mount Chassis Mount	Operating Temperature	-25°C ~ 85°C
Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing Lead Spacing Size / Dimension Leight - Seated (Max) Surface Mount Land Size Mounting Type 13.3A @ 120Hz - 13.3A @ 120Hz 1248" (31.70mm) - 1.248" (31.70mm) 6.102" (155.00mm) Chassis Mount	Polarization	Polar
Ripple Current - High Frequency Impedance Lead Spacing 1.248" (31.70mm) Size / Dimension 3.028" Dia (76.90mm) Height - Seated (Max) 6.102" (155.00mm) Surface Mount Land Size Mounting Type Chassis Mount	Applications	General Purpose
Impedance-Lead Spacing1.248" (31.70mm)Size / Dimension3.028" Dia (76.90mm)Height - Seated (Max)6.102" (155.00mm)Surface Mount Land Size-Mounting TypeChassis Mount	Ripple Current - Low Frequency	13.3A @ 120Hz
Lead Spacing1.248" (31.70mm)Size / Dimension3.028" Dia (76.90mm)Height - Seated (Max)6.102" (155.00mm)Surface Mount Land Size-Mounting TypeChassis Mount	Ripple Current - High Frequency	-
Size / Dimension3.028" Dia (76.90mm)Height - Seated (Max)6.102" (155.00mm)Surface Mount Land Size-Mounting TypeChassis Mount	Impedance	-
Height - Seated (Max) Surface Mount Land Size Mounting Type 6.102" (155.00mm) - Chassis Mount	Lead Spacing	1.248" (31.70mm)
Surface Mount Land Size - Mounting Type Chassis Mount	Size / Dimension	3.028" Dia (76.90mm)
Mounting Type Chassis Mount	Height - Seated (Max)	6.102" (155.00mm)
C 71	Surface Mount Land Size	-
Package / Case Radial, Can - Screw Terminals	Mounting Type	Chassis Mount
,	Package / Case	Radial, Can - Screw Terminals
Report errors?		Report errors?

B43310A5568M000 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

B43310A5568M000 Payment Methods



















B43310A5568M000 Shipping Methods













If you have any question about B43310A5568M000, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com