

B43455A4828M003

B43455A4828M003 Information

Container.com	 B43455A4828M003 EPCOS (TDK) Capacitors Aluminum Electrolytic Capacitors CAP ALUM 8200UF 20% 350V SCREW Radial, Can - Screw Terminals For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B43455A4828M003 Specifications

Manufacturer Part Number B43455A4828M003 Manufacturer EPCOS (TDK) Category Capacitors Aluminum Electrolytic Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Screw Terminals Series B43455 Capacitance 8200µF Tolerance ±20% Voltage - Rated 350V ESR (Equivalent Series Resistance) 23 mOhm © 100Hz Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization General Purpose Applications General Purpose Ripple Current - Low Frequency - Impedance - Lead Spacing 1.248° (31.70mm) Size / Dimension 3.583° Dia (91.00mm) Height - Seated (Max) 5.728° (145.50mm) Surface Mount Land Size - Mounting Type Chasis Mount Package Case Kadial, Can - Screw Terminals	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Screw TerminalsSeriesB43455Capacitance8200µFTolerance±20%Voltage - Rated350VESR (Equivalent Series Resistance)23 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - High Frequency-Impedance-Lead Spacing3.583° Dia (91.00mm)Size / Dimension5.728° (145.50mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Manufacturer Part Number	B43455A4828M003
Auminum Electrolytic CapacitorsPackageRadial, Can - Screw TerminalsSeriesB43455Capacitance\$200µFtolerance±20%Voltage - Rated350VESR (Equivalent Series Resistance)23 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance-Lead Spacing1.248" (31.70mm)Size / Dimension3.583" Dia (91.00mm)Height - Seated (Max)5.728" (145.50mm)Surface Mount Land Size-Mounting TypeChasis MountPackage / CaseRadial, Can - Screw Terminals	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Screw TerminalsSeriesB43455Capacitance\$200µFTolerance±20%Voltage - Rated350VESR (Equivalent Series Resistance)23 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationGeneral PurposeRipple Current - Low Frequency15A @ 100HzRipple Current - High Frequency-Impedance1.248" (31.70mm)Size / Dimension3.583" Dia (91.00mm)Height - Seated (Max)5.728" (145.50mm)Surface Mount Land Size-Mounting TypeChasis MountPackage / CaseRadial, Can - Screw Terminals	Category	Capacitors
SeriesB43455Capacitance8200µFTolerance±20%Voltage - Rated350VESR (Equivalent Series Resistance)23 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance-Lead Spacing1.248" (31.70mm)Size / Dimension3.583" Dia (91.00mm)Height - Seated (Max)5.728" (145.50mm)Surface Mount Land Size-Mounting TypeChasis MountPackage / CaseRadial, Can - Screw Terminals		Aluminum Electrolytic Capacitors
Capacitance8200µFTolerance±20%Voltage Rated350VESR (Equivalent Series Resistance)23 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency15A @ 100HzImpedance.Lead Spacing3.583° Dia (91.00mm)Size / Dimension5.728° (145.50mm)Surface Mount Land Size.Mounting TypeChasis MountPackage / CaseRatial, Can - Screw Terminals	Package	Radial, Can - Screw Terminals
Tolerance±20%Voltage - Rated350VESR (Equivalent Series Resistance)23 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarzationPolarApplicationsGeneral PurposeRipple Current - High Frequency15A @ 100HzImpedance-Lead Spacing3.583" Dia (91.00mm)Size / Dimension5.728" (145.50mm)Burface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Series	B43455
Voltage - Rated350VESR (Equivalent Series Resistance)23 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency15A @ 100HzRipple Current - High Frequency-Lead Spacing1.248" (31.70mm)Size / Dimension5.728" (145.50mm)Height - Seated (Max)5.728" (145.50mm)Surface Mount Land Size-Pokage / CaseRatial, Can - Screw Terminals	Capacitance	8200µF
ESR (Equivalent Series Resistance)23 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarPolarApplicationsGeneral PurposeRipple Current - Low Frequency15A @ 100HzRipple Current - High Frequency-Impedance-Lead Spacing1.248" (31.70mm)Size / Dimension5.728" (145.50mm)Height - Seated (Max)-Surface Mount Land Size-Hounting TypeChasis MountPackage / CaseRadial, Can - Screw Terminals	Tolerance	±20%
Lifetime @ Temp.10000 Hrs @ 85°CDeperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency15A @ 100HzRipple Current - High Frequency-Impedance-Lead Spacing3.583" Dia (91.00mm)Size / Dimension5.728" (145.50mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Voltage - Rated	350V
Operating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency15A @ 100HzRipple Current - High Frequency-Impedance-Lead Spacing1.248" (31.70mm)Size / Dimension5.728" (145.50mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	ESR (Equivalent Series Resistance)	23 mOhm @ 100Hz
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency15A @ 100HzRipple Current - High Frequency-Impedance-Lead Spacing1.248" (31.70mm)Size / Dimension3.583" Dia (91.00mm)Height - Seated (Max)5.728" (145.50mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Lifetime @ Temp.	10000 Hrs @ 85°C
ApplicationsGeneral PurposeRipple Current - Low Frequency15A @ 100HzRipple Current - High Frequency-Impedance-Lead Spacing1.248" (31.70mm)Size / Dimension3.583" Dia (91.00mm)Height - Seated (Max)5.728" (145.50mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency15A @ 100HzRipple Current - High Frequency-Impedance-Lead Spacing1.248" (31.70mm)Size / Dimension3.583" Dia (91.00mm)Height - Seated (Max)5.728" (145.50mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Polarization	Polar
In a constraint of a constrain	Applications	General Purpose
Impedance-Lead Spacing1.248" (31.70mm)Size / Dimension3.583" Dia (91.00mm)Height - Seated (Max)5.728" (145.50mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Ripple Current - Low Frequency	15A @ 100Hz
Lead Spacing1.248" (31.70mm)Size / Dimension3.583" Dia (91.00mm)Height - Seated (Max)5.728" (145.50mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Ripple Current - High Frequency	-
Size / Dimension3.583" Dia (91.00mm)Height - Seated (Max)5.728" (145.50mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Impedance	-
Height - Seated (Max)5.728" (145.50mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Lead Spacing	1.248" (31.70mm)
Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Size / Dimension	3.583" Dia (91.00mm)
Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Height - Seated (Max)	5.728" (145.50mm)
Package / Case Radial, Can - Screw Terminals	Surface Mount Land Size	-
• • • • • • • • • • • • • • • • • • •	Mounting Type	Chassis Mount
Report errors	Package / Case	Radial, Can - Screw Terminals
		Report errors?

B43455A4828M003 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B43455A4828M003 Payment Methods



If you have any question about B43455A4828M003, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com