



#### B43455C4338M7 Information

Heisener.com

Part Number B43455C4338M7 Manufacturer EPCOS (TDK) Category

Capacitors

**Aluminum Electrolytic Capacitors** 

**Description** CAP ALUM 3300UF 20% 350V SCREW

Radial, Can - Screw Terminals **Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **B43455C4338M7 Specifications**

Manufacturer Part Number         B43455C4338M7           Manufacturer         EPCOS (TDK)           Category         Capacitors           Aluminum Electrolytic Capacitors           Package         Radial, Can - Screw Terminals           Series         B43455           Capacitance         330µF           Tolerance         ±20%           Voltage - Rated         350V           ESR (Equivalent Series Resistance)         32 mOhm @ 100Hz           Lifetime @ Temp.         10000 Hrs @ 85°C           Operating Temperature         -40°C ~ 85°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         8.1A @ 100Hz           Ripple Current - High Frequency         -           Impedance         38 mOhms           Lead Spacing         1.122" (28.50mm)           Size / Dimension         2.532" Dia (64.30mm)           Height - Seated (Max)         4.201" (106.70mm)           Surface Mount Land Size         -           Mounting Type         Chassis Mount           Package / Case         Radial, Can - Screw Terminals		
Category         Capacitors           Aluminum Electrolytic Capacitors           Package         Radial, Can - Screw Terminals           Series         B43455           Capacitance         3300µF           Tolerance         ±20%           Voltage - Rated         350V           ESR (Equivalent Series Resistance)         32 mOhm @ 100Hz           Lifetime @ Temp.         10000 Hrs @ 85°C           Operating Temperature         -40°C ~ 85°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         8.1A @ 100Hz           Ripple Current - High Frequency         -           Impedance         38 mOhms           Lead Spacing         1.122" (28.50mm)           Size / Dimension         2.532" Dia (64.30mm)           Height - Seated (Max)         4.201" (106.70mm)           Surface Mount Land Size         -           Mounting Type         Chassis Mount           Package / Case         Radial, Can - Screw Terminals	Manufacturer Part Number	B43455C4338M7
Package         Radial, Can - Screw Terminals           Series         B43455           Capacitance         3300μF           Tolerance         ±20%           Voltage - Rated         350V           ESR (Equivalent Series Resistance)         32 mOhm @ 100Hz           Lifetime @ Temp.         10000 Hrs @ 85°C           Operating Temperature         -40°C ~ 85°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         8.1A @ 100Hz           Ripple Current - High Frequency         -           Impedance         38 mOhms           Lead Spacing         1.122" (28.50mm)           Size / Dimension         2.532" Dia (64.30mm)           Height - Seated (Max)         4.201" (106.70mm)           Surface Mount Land Size         -           Mounting Type         Chassis Mount           Package / Case         Radial, Can - Screw Terminals	Manufacturer	EPCOS (TDK)
Package         Radial, Can - Screw Terminals           Series         B43455           Capacitance         3300µF           Tolerance         ±20%           Voltage - Rated         350V           ESR (Equivalent Series Resistance)         32 mOhm @ 100Hz           Lifetime @ Temp.         10000 Hrs @ 85°C           Operating Temperature         -40°C ~ 85°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         8.1A @ 100Hz           Ripple Current - High Frequency         -           Impedance         38 mOhms           Lead Spacing         1.122" (28.50mm)           Size / Dimension         2.532" Dia (64.30mm)           Height - Seated (Max)         4.201" (106.70mm)           Surface Mount Land Size         -           Mounting Type         Chassis Mount           Package / Case         Radial, Can - Screw Terminals	Category	Capacitors
Series         B43455           Capacitance         3300µF           Tolerance         ±20%           Voltage - Rated         350V           ESR (Equivalent Series Resistance)         32 mOhm @ 100Hz           Lifetime @ Temp.         10000 Hrs @ 85°C           Operating Temperature         -40°C ~ 85°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         8.1A @ 100Hz           Ripple Current - High Frequency         -           Impedance         38 mOhms           Lead Spacing         1.122" (28.50mm)           Size / Dimension         2.532" Dia (64.30mm)           Height - Seated (Max)         4.201" (106.70mm)           Surface Mount Land Size         -           Mounting Type         Chassis Mount           Package / Case         Radial, Can - Screw Terminals		Aluminum Electrolytic Capacitors
Capacitance       3300μF         Tolerance       ±20%         Voltage - Rated       350V         ESR (Equivalent Series Resistance)       32 mOhm @ 100Hz         Lifetime @ Temp.       10000 Hrs @ 85°C         Operating Temperature       -40°C ~ 85°C         Polarization       Polar         Applications       General Purpose         Ripple Current - Low Frequency       8.1A @ 100Hz         Ripple Current - High Frequency       -         Impedance       38 mOhms         Lead Spacing       1.122" (28.50mm)         Size / Dimension       2.532" Dia (64.30mm)         Height - Seated (Max)       4.201" (106.70mm)         Surface Mount Land Size       -         Mounting Type       Chassis Mount         Package / Case       Radial, Can - Screw Terminals	Package	Radial, Can - Screw Terminals
Tolerance ±20%  Voltage - Rated 350V  ESR (Equivalent Series Resistance) 32 mOhm @ 100Hz  Lifetime @ Temp. 10000 Hrs @ 85°C  Operating Temperature -40°C ~ 85°C  Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 8.1A @ 100Hz  Ripple Current - High Frequency -  Impedance 38 mOhms  Lead Spacing 1.122" (28.50mm)  Size / Dimension 2.532" Dia (64.30mm)  Height - Seated (Max) 4.201" (106.70mm)  Surface Mount Land Size -  Mounting Type Chassis Mount  Package / Case Radial, Can - Screw Terminals	Series	B43455
Voltage - Rated  ESR (Equivalent Series Resistance)  Lifetime @ Temp.  10000 Hrs @ 85°C  Operating Temperature  -40°C ~ 85°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  Ripple Current - High Frequency  Impedance  1.122" (28.50mm)  Size / Dimension  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Chassis Mount  Package / Case  Riowood House  32 mOhm @ 100Hz  -40°C ~ 85°C  General Purpose  8.1A @ 100Hz  -100Hz	Capacitance	3300μF
ESR (Equivalent Series Resistance)  Lifetime @ Temp.  Operating Temperature  -40°C ~ 85°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  Ripple Current - High Frequency  Impedance  Lead Spacing  1.122" (28.50mm)  Size / Dimension  4.201" (106.70mm)  Surface Mount Land Size  Mounting Type  Chassis Mount  Package / Case  Riovo A85°C  -0000 Hrs @ 85°C  -0000 Hrs @ 85°C  -40°C ~	Tolerance	±20%
Lifetime @ Temp.  Operating Temperature  -40°C ~ 85°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  Ripple Current - High Frequency  Impedance  Lead Spacing  Size / Dimension  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Package / Case  10000 Hrs @ 85°C  -40°C ~ 85°C  Polar  -40°C ~ 85°C  -40°C ~ 85°C  -40°C ~ 85°C  -40°C ~ 85°C  Seneral Purpose  8.1A @ 100Hz  -  1.122" (28.50mm)  2.532" Dia (64.30mm)  4.201" (106.70mm)  Chassis Mount  Radial, Can - Screw Terminals	Voltage - Rated	350V
Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency - Impedance 38 mOhms Lead Spacing 1.122" (28.50mm) Size / Dimension Leight - Seated (Max) 4.201" (106.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	ESR (Equivalent Series Resistance)	32 mOhm @ 100Hz
Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 8.1A @ 100Hz  Ripple Current - High Frequency -  Impedance 38 mOhms  Lead Spacing 1.122" (28.50mm)  Size / Dimension 2.532" Dia (64.30mm)  Height - Seated (Max) 4.201" (106.70mm)  Surface Mount Land Size -  Mounting Type Chassis Mount  Package / Case Radial, Can - Screw Terminals	Lifetime @ Temp.	10000 Hrs @ 85°C
Applications  Ripple Current - Low Frequency  Ripple Current - High Frequency  Impedance  Sa mOhms  Lead Spacing  1.122" (28.50mm)  Size / Dimension  2.532" Dia (64.30mm)  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Chassis Mount  Package / Case  Radial, Can - Screw Terminals	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency Ripple Current - High Frequency Impedance 38 mOhms Lead Spacing 1.122" (28.50mm) Size / Dimension 2.532" Dia (64.30mm) Height - Seated (Max) 4.201" (106.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Polarization	Polar
Ripple Current - High Frequency Impedance 38 mOhms Lead Spacing 1.122" (28.50mm) Size / Dimension 2.532" Dia (64.30mm) Height - Seated (Max) 4.201" (106.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Applications	General Purpose
Impedance38 mOhmsLead Spacing1.122" (28.50mm)Size / Dimension2.532" Dia (64.30mm)Height - Seated (Max)4.201" (106.70mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Ripple Current - Low Frequency	8.1A @ 100Hz
Lead Spacing 1.122" (28.50mm)  Size / Dimension 2.532" Dia (64.30mm)  Height - Seated (Max) 4.201" (106.70mm)  Surface Mount Land Size -  Mounting Type Chassis Mount  Package / Case Radial, Can - Screw Terminals	Ripple Current - High Frequency	-
Size / Dimension 2.532" Dia (64.30mm)  Height - Seated (Max) 4.201" (106.70mm)  Surface Mount Land Size -  Mounting Type Chassis Mount  Package / Case Radial, Can - Screw Terminals	Impedance	38 mOhms
Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Chassis Mount  Package / Case  Radial, Can - Screw Terminals	Lead Spacing	1.122" (28.50mm)
Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Size / Dimension	2.532" Dia (64.30mm)
Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Height - Seated (Max)	4.201" (106.70mm)
Package / Case Radial, Can - Screw Terminals	Surface Mount Land Size	-
-	Mounting Type	Chassis Mount
	Package / Case	Radial, Can - Screw Terminals
Report errors?		Report errors?

#### B43455C4338M7 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

#### **B43455C4338M7 Payment Methods**



















### **B43455C4338M7 Shipping Methods**













If you have any question about B43455C4338M7, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com