



B43455C5338M3 Information

Heisener.com

Part Number B43455C5338M3 Manufacturer EPCOS (TDK) Category

Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 3300UF 20% 450V SCREW

Package Radial, Can - Screw Terminals

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









B43455C5338M3 Specifications

Manufacturer Part Number B43455C5338M3 Manufacturer EPCOS (TDK) Category Capacitors Package Radial, Can - Screw Terminals Series B43455 Capacitance 3300µF Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) 30 mOhm @ 100Hz Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 9.4A @ 100Hz Ripple Current - High Frequency - Impedance 36 mOhms Lead Spacing 1.248" (31.70mm) Size / Dimension 3.028" Dia (76.90mm) Height - Seated (Max) 4.201" (106.70mm) Surface Mount Land Size - Mounting Type Chassis Mount		
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Screw Terminals Series B43455 Capacitance 3300µF Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) 30 mOhm @ 100Hz Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polar Applications General Purpose Ripple Current - Low Frequency 9.4A @ 100Hz Ripple Current - High Frequency - Impedance 36 mOhms Lead Spacing 1.248" (31.70mm) Size / Dimension 3.028" Dia (76.90mm) Height - Seated (Max) 4.201" (106.70mm) Surface Mount Land Size -	Manufacturer Part Number	B43455C5338M3
PackageRadial, Can - Screw TerminalsSeriesB43455Capacitance3300µFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)30 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency9.4A @ 100HzRipple Current - High Frequency-Impedance36 mOhmsLead Spacing1.248" (31.70mm)Size / Dimension3.028" Dia (76.90mm)Height - Seated (Max)4.201" (106.70mm)Surface Mount Land Size-	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Screw TerminalsSeriesB43455Capacitance3300µFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)30 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency9.4A @ 100HzRipple Current - High Frequency-Impedance36 mOhmsLead Spacing1.248" (31.70mm)Size / Dimension3.028" Dia (76.90mm)Height - Seated (Max)4.201" (106.70mm)Surface Mount Land Size-	Category	Capacitors
Series B43455 Capacitance 3300µF Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) 30 mOhm @ 100Hz Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 9.4A @ 100Hz Ripple Current - High Frequency - Impedance 36 mOhms Lead Spacing 1.248" (31.70mm) Size / Dimension 3.028" Dia (76.90mm) Height - Seated (Max) 4.201" (106.70mm) Surface Mount Land Size -		Aluminum Electrolytic Capacitors
Capacitance 3300μF Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) 30 mOhm @ 100Hz Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 9.4A @ 100Hz Ripple Current - High Frequency - Impedance 36 mOhms Lead Spacing 1.248" (31.70mm) Size / Dimension 3.028" Dia (76.90mm) Height - Seated (Max) 4.201" (106.70mm) Surface Mount Land Size -	Package	Radial, Can - Screw Terminals
Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) 30 mOhm @ 100Hz Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 9.4A @ 100Hz Ripple Current - High Frequency - Impedance 36 mOhms Lead Spacing 1.248" (31.70mm) Size / Dimension 3.028" Dia (76.90mm) Height - Seated (Max) 4.201" (106.70mm) Surface Mount Land Size -	Series	B43455
Voltage - Rated 450V ESR (Equivalent Series Resistance) 30 mOhm @ 100Hz Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 9.4A @ 100Hz Ripple Current - High Frequency - Impedance 36 mOhms Lead Spacing 1.248" (31.70mm) Size / Dimension 3.028" Dia (76.90mm) Height - Seated (Max) 4.201" (106.70mm) Surface Mount Land Size -	Capacitance	3300μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing 1.248" (31.70mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size 30 mOhm @ 100Hz 10000 Hrs @ 85°C -40°C ~ 85°C Polar -40°C ~ 85°C -40°C ~ 85	Tolerance	±20%
Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 9.4A @ 100Hz Ripple Current - High Frequency - Impedance 36 mOhms Lead Spacing 1.248" (31.70mm) Size / Dimension 3.028" Dia (76.90mm) Height - Seated (Max) 4.201" (106.70mm) Surface Mount Land Size -	Voltage - Rated	450V
Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance 36 mOhms Lead Spacing 1.248" (31.70mm) Size / Dimension 3.028" Dia (76.90mm) Height - Seated (Max) Surface Mount Land Size -40°C ~ 85°C Polar Apolication Polar Application 9.4A @ 100Hz - 1.248" (31.70mm) 3.028" Dia (76.90mm) 4.201" (106.70mm)	ESR (Equivalent Series Resistance)	30 mOhm @ 100Hz
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 9.4A @ 100Hz Ripple Current - High Frequency - Impedance 36 mOhms Lead Spacing 1.248" (31.70mm) Size / Dimension 3.028" Dia (76.90mm) Height - Seated (Max) 4.201" (106.70mm) Surface Mount Land Size -	Lifetime @ Temp.	10000 Hrs @ 85°C
Applications Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing 1.248" (31.70mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size General Purpose 9.4A @ 100Hz - 1.248" (31.70mm) 3.028" Dia (76.90mm) 4.201" (106.70mm) -	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency 9.4A @ 100Hz Ripple Current - High Frequency - Impedance 36 mOhms Lead Spacing 1.248" (31.70mm) Size / Dimension 3.028" Dia (76.90mm) Height - Seated (Max) 4.201" (106.70mm) Surface Mount Land Size -	Polarization	Polar
Ripple Current - High Frequency - Impedance 36 mOhms Lead Spacing 1.248" (31.70mm) Size / Dimension 3.028" Dia (76.90mm) Height - Seated (Max) 4.201" (106.70mm) Surface Mount Land Size -	Applications	General Purpose
Impedance 36 mOhms Lead Spacing 1.248" (31.70mm) Size / Dimension 3.028" Dia (76.90mm) Height - Seated (Max) 4.201" (106.70mm) Surface Mount Land Size -	Ripple Current - Low Frequency	9.4A @ 100Hz
Lead Spacing 1.248" (31.70mm) Size / Dimension 3.028" Dia (76.90mm) Height - Seated (Max) 4.201" (106.70mm) Surface Mount Land Size -	Ripple Current - High Frequency	-
Size / Dimension3.028" Dia (76.90mm)Height - Seated (Max)4.201" (106.70mm)Surface Mount Land Size-	Impedance	36 mOhms
Height - Seated (Max) Surface Mount Land Size 4.201" (106.70mm) -	Lead Spacing	1.248" (31.70mm)
Surface Mount Land Size -	Size / Dimension	3.028" Dia (76.90mm)
	Height - Seated (Max)	4.201" (106.70mm)
Mounting Type Chassis Mount	Surface Mount Land Size	-
	Mounting Type	Chassis Mount
Package / Case Radial, Can - Screw Terminals	Package / Case	Radial, Can - Screw Terminals
Report errors?		Report errors?

B43455C5338M3 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

B43455C5338M3 Payment Methods





















B43455C5338M3 Shipping Methods













If you have any question about B43455C5338M3, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com