



B43457A4129M003 Information

Heisener.com

Part Number B43457A4129M003 Manufacturer EPCOS (TDK)

Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 12000UF 20% 350V SCREW

Radial, Can - Screw Terminals **Package** For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









B43457A4129M003 Specifications

Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Screw Terminals Series B43457 Capacitance 12000µF Tolerance ±20% Voltage - Rated 350V ESR (Equivalent Series Resistance) 17 mOhm @ 100Hz Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 20A @ 100Hz Ripple Current - High Frequency - Impedance - Lead Spacing 1.248" (31.70mm) Size / Dimension 3.583" Dia (91.00mm) Height - Seated (Max) 7.559" (192.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals		
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Screw Terminals Series B43457 Capacitance 12000µF Tolerance ±20% Voltage - Rated 350V ESR (Equivalent Series Resistance) 17 mOhm @ 100Hz Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 20A @ 100Hz Ripple Current - High Frequency - Lead Spacing 1.248" (31.70mm) Size / Dimension 3.583" Dia (91.00mm) Height - Seated (Max) 7.559" (192.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Manufacturer Part Number	B43457A4129M003
Package Radial, Can - Screw Terminals Series B43457 Capacitance 12000µF Tolerance ±20% Voltage - Rated 350V ESR (Equivalent Series Resistance) 17 mOhm @ 100Hz Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 20A @ 100Hz Ripple Current - High Frequency - Lead Spacing 1.248" (31.70mm) Size / Dimension 3.583" Dia (91.00mm) Height - Seated (Max) 7.559" (192.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Manufacturer	EPCOS (TDK)
Package Radial, Can - Screw Terminals Series B43457 Capacitance 12000μF Tolerance ±20% Voltage - Rated 350V ESR (Equivalent Series Resistance) 17 mOhm @ 100Hz Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 20A @ 100Hz Ripple Current - High Frequency - Impedance - Lead Spacing 1.248" (31.70mm) Size / Dimension 3.583" Dia (91.00mm) Height - Seated (Max) 7.559" (192.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Category	Capacitors
Series B43457 Capacitance 12000μF Tolerance ±20% Voltage - Rated 350V ESR (Equivalent Series Resistance) 17 mOhm @ 100Hz Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 20A @ 100Hz Ripple Current - High Frequency - Impedance - Lead Spacing 1.248" (31.70mm) Size / Dimension 3.583" Dia (91.00mm) Height - Seated (Max) 7.559" (192.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals		Aluminum Electrolytic Capacitors
Capacitance 12000µF Tolerance ±20% Voltage - Rated 350V ESR (Equivalent Series Resistance) 17 mOhm @ 100Hz Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 20A @ 100Hz Ripple Current - High Frequency - Impedance - Lead Spacing 1.248" (31.70mm) Size / Dimension 3.583" Dia (91.00mm) Height - Seated (Max) 7.559" (192.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Package	Radial, Can - Screw Terminals
Tolerance ±20% Voltage - Rated 350V ESR (Equivalent Series Resistance) 17 mOhm @ 100Hz Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 20A @ 100Hz Ripple Current - High Frequency - Impedance - Lead Spacing 1.248" (31.70mm) Size / Dimension 3.583" Dia (91.00mm) Height - Seated (Max) 7.559" (192.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Rated (Max) Radial, Can - Screw Terminals	Series	B43457
Voltage - Rated ESR (Equivalent Series Resistance) Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency - Impedance Lead Spacing 1.248" (31.70mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Radial, Can - Screw Terminals	Capacitance	12000μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing 1.248" (31.70mm) Size / Dimension 3.583" Dia (91.00mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Tolerance	±20%
Lifetime @ Temp. Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case 10000 Hrs @ 85°C -40°C ~ 85°C Polar -40°C ~ 85°C Polar -40°C ~ 85°C -40°C	Voltage - Rated	350V
Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 20A @ 100Hz Ripple Current - High Frequency Impedance Lead Spacing 1.248" (31.70mm) Size / Dimension 3.583" Dia (91.00mm) Height - Seated (Max) 7.559" (192.00mm) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	ESR (Equivalent Series Resistance)	17 mOhm @ 100Hz
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 20A @ 100Hz Ripple Current - High Frequency - Impedance - Lead Spacing 1.248" (31.70mm) Size / Dimension 3.583" Dia (91.00mm) Height - Seated (Max) 7.559" (192.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Lifetime @ Temp.	10000 Hrs @ 85°C
Applications General Purpose Ripple Current - Low Frequency 20A @ 100Hz Ripple Current - High Frequency Impedance - Lead Spacing 1.248" (31.70mm) Size / Dimension 3.583" Dia (91.00mm) Height - Seated (Max) 7.559" (192.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing 1.248" (31.70mm) Size / Dimension Size / Dimension 3.583" Dia (91.00mm) Height - Seated (Max) 7.559" (192.00mm) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Polarization	Polar
Ripple Current - High Frequency - Impedance - Lead Spacing 1.248" (31.70mm) Size / Dimension 3.583" Dia (91.00mm) Height - Seated (Max) 7.559" (192.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Applications	General Purpose
Impedance - Lead Spacing 1.248" (31.70mm) Size / Dimension 3.583" Dia (91.00mm) Height - Seated (Max) 7.559" (192.00mm) Surface Mount Land Size - Chassis Mount Package / Case Radial, Can - Screw Terminals	Ripple Current - Low Frequency	20A @ 100Hz
Lead Spacing 1.248" (31.70mm) Size / Dimension 3.583" Dia (91.00mm) Height - Seated (Max) 7.559" (192.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Ripple Current - High Frequency	-
Size / Dimension 3.583" Dia (91.00mm) Height - Seated (Max) 7.559" (192.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Impedance	-
Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Lead Spacing	1.248" (31.70mm)
Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Size / Dimension	3.583" Dia (91.00mm)
Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Height - Seated (Max)	7.559" (192.00mm)
Package / Case Radial, Can - Screw Terminals	Surface Mount Land Size	-
-	Mounting Type	Chassis Mount
Report errors?	Package / Case	Radial, Can - Screw Terminals
		Report errors?

B43457A4129M003 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

B43457A4129M003 Payment Methods





















B43457A4129M003 Shipping Methods













If you have any question about B43457A4129M003, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com