



B43457C5228M3 Information

Heisener.com

Part Number B43457C5228M3
Manufacturer EPCOS (TDK)
Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 2200UF 20% 450V SCREW

Package Radial, Can - Screw Terminals

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









B43457C5228M3 Specifications

Manufacturer Part Number B43457C5228M3 Manufacturer EPCOS (TDK) Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Screw Terminals Series B43457 Capacitance 2200µF Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) 50 mOhm @ 100Hz Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 7.5A @ 100Hz Ripple Current - High Frequency - Impedance 60 mOhms Lead Spacing 1.122" (28.50mm) Size / Dimension 2.532" Dia (64.30mm) Height - Seated (Max) 4.201" (106.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals		
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Screw Terminals Series B43457 Capacitance 2200µF Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) 50 mOhm @ 100Hz Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance 60 mOhms Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Manufacturer Part Number	B43457C5228M3
Package Radial, Can - Screw Terminals Series B43457 Capacitance 2200μF Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) 50 mOhm @ 100Hz Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 7.5A @ 100Hz Ripple Current - High Frequency - Impedance 60 mOhms Lead Spacing 1.122" (28.50mm) Size / Dimension 2.532" Dia (64.30mm) Height - Seated (Max) 4.201" (106.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Manufacturer	EPCOS (TDK)
Package Radial, Can - Screw Terminals Series B43457 Capacitance 2200µF Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) 50 mOhm @ 100Hz Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 7.5A @ 100Hz Ripple Current - High Frequency - Impedance 60 mOhms Lead Spacing 1.122" (28.50mm) Size / Dimension 2.532" Dia (64.30mm) Height - Seated (Max) 4.201" (106.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Category	Capacitors
Series B43457 Capacitance 2200µF Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) 50 mOhm @ 100Hz Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 7.5A @ 100Hz Ripple Current - High Frequency - Impedance 60 mOhms Lead Spacing 1.122" (28.50mm) Size / Dimension 2.532" Dia (64.30mm) Height - Seated (Max) 4.201" (106.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals		Aluminum Electrolytic Capacitors
Capacitance 2200μF Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) 50 mOhm @ 100Hz Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - 5A @ 100Hz Ripple Current - High Frequency - Impedance 60 mOhms Lead Spacing 1.122" (28.50mm) Size / Dimension 2.532" Dia (64.30mm) Height - Seated (Max) 4.201" (106.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Package	Radial, Can - Screw Terminals
Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) 50 mOhm @ 100Hz Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 7.5A @ 100Hz Ripple Current - High Frequency - Impedance 60 mOhms Lead Spacing 1.122" (28.50mm) Size / Dimension 2.532" Dia (64.30mm) Height - Seated (Max) 4.201" (106.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Series	B43457
Voltage - Rated ESR (Equivalent Series Resistance) Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency - Impedance 60 mOhms Lead Spacing 1.122" (28.50mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Rio000 Hrs @ 85°C -40°C ~ 85°C	Capacitance	2200μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency 7.5A @ 100Hz Ripple Current - High Frequency Impedance 60 mOhms Lead Spacing 1.122" (28.50mm) Size / Dimension 4.201" (106.70mm) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Riono Minima 100Hz 100Hz 100HC 4.00 TOH 60 mOhms 1.122" (28.50mm) 2.532" Dia (64.30mm) 4.201" (106.70mm) Chassis Mount	Tolerance	±20%
Lifetime @ Temp. Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance 60 mOhms Lead Spacing 1.122" (28.50mm) Size / Dimension 4.201" (106.70mm) Surface Mount Land Size Mounting Type Chassis Mount Package / Case 1.0000 Hrs @ 85°C -40°C ~ 85°C -40°C ~ 85°C 6eneral Purpose 7.5A @ 100Hz 6eneral Purpose 7.5A @ 100Hz 1.122" (28.50mm) 2.532" Dia (64.30mm) 4.201" (106.70mm) Chassis Mount Radial, Can - Screw Terminals	Voltage - Rated	450V
Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 7.5A @ 100Hz Ripple Current - High Frequency - Impedance 60 mOhms Lead Spacing 1.122" (28.50mm) Size / Dimension 2.532" Dia (64.30mm) Height - Seated (Max) 4.201" (106.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	ESR (Equivalent Series Resistance)	50 mOhm @ 100Hz
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 7.5A @ 100Hz Ripple Current - High Frequency - Impedance 60 mOhms Lead Spacing 1.122" (28.50mm) Size / Dimension 2.532" Dia (64.30mm) Height - Seated (Max) 4.201" (106.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Lifetime @ Temp.	10000 Hrs @ 85°C
Applications General Purpose 7.5A @ 100Hz 7.5A @ 100Hz Ripple Current - High Frequency Impedance 60 mOhms Lead Spacing 1.122" (28.50mm) Size / Dimension 2.532" Dia (64.30mm) Height - Seated (Max) 4.201" (106.70mm) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency Ripple Current - High Frequency Impedance 60 mOhms Lead Spacing 1.122" (28.50mm) Size / Dimension 2.532" Dia (64.30mm) Height - Seated (Max) 4.201" (106.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Polarization	Polar
Ripple Current - High Frequency - Impedance 60 mOhms Lead Spacing 1.122" (28.50mm) Size / Dimension 2.532" Dia (64.30mm) Height - Seated (Max) 4.201" (106.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Applications	General Purpose
Impedance60 mOhmsLead Spacing1.122" (28.50mm)Size / Dimension2.532" Dia (64.30mm)Height - Seated (Max)4.201" (106.70mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Ripple Current - Low Frequency	7.5A @ 100Hz
Lead Spacing 1.122" (28.50mm) Size / Dimension 2.532" Dia (64.30mm) Height - Seated (Max) 4.201" (106.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Ripple Current - High Frequency	-
Size / Dimension 2.532" Dia (64.30mm) Height - Seated (Max) 4.201" (106.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Impedance	60 mOhms
Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Lead Spacing	1.122" (28.50mm)
Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Size / Dimension	2.532" Dia (64.30mm)
Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Height - Seated (Max)	4.201" (106.70mm)
Package / Case Radial, Can - Screw Terminals	Surface Mount Land Size	-
-	Mounting Type	Chassis Mount
Report errors?	Package / Case	Radial, Can - Screw Terminals
		Report errors?

B43457C5228M3 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

B43457C5228M3 Payment Methods



















B43457C5228M3 Shipping Methods













If you have any question about B43457C5228M3, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com