

B43501A1227M87

lest a Quote

B43501A1227M87 Information

Part Number	B43501A1227M87	
Manufacturer	EPCOS (TDK)	
Category Description	Capacitors Aluminum Electrolytic Capacitors	
	CAP ALUM 220UF 20% 160V SNAP	- 262
Package	Radial, Can - Snap-In	
	For the pricing/inventory/lead time, please contact	
	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Requ
	Manufacturer Category Description	Aluminum Electrolytic Capacitors Description CAP ALUM 220UF 20% 160V SNAP Package Radial, Can - Snap-In For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B43501A1227M87 Specifications

Manufacturer Part Number B43501A1227M87 Manufacturer EPCOS (TDK) Category Capacitors Aluminum Electrolytic Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Snap-In Series B43501 Capacitance 220µF Tolerance 220µF Voltage - Rated 160V ESR (Equivalent Series Resistance) 530 mOhm @ 100Hz Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature 40°C ~ 85°C Polarization General Purpose Ripple Current - Low Frequency I.11 A @ 100Hz Ripple Current - High Frequency - Impedance 730 mOhms Lead Spacing 0.394° (10.00mm) Size / Dimension 0.630° (22.00mm) Height - Seated (Max) 1.63° (27.00mm) Size / Dimension - Mounting Type - Mounting Type -		
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43501Capacitance220µFTolerance±20%Voltage - Rated160VESR (Equivalent Series Resistance)530 mOhm @ 100HzESR (Equivalent Series Resistance)530 mOhm @ 100HzDerating Temperature-40°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency-11.1A @ 100HzRipple Current - High Frequency-30 mOhmsLead Spacing0.394" (10.00mm)Size / Dinension0.866" Dia (22.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can - Snap-In	Manufacturer Part Number	B43501A1227M87
IdentifyAluminum Electrolytic CapacitonsPackageRadial, Can - Snap-InSeriesB43501Capacitance20µFTolerance±20%Voltage - Rated160VESR (Equivalent Series Resistance)530 mOhm @ 100HzLifetime @ Temp.00000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - High Frequency-Impedance730 mOhmsLided Spacing0.394" (10.00mm)Size / Dimension0.666" Dia (22.00mm)Size / Dimension1.663" (27.00mm)Surface Mount Land Size-Mounting TypeFurough HolePackage / CaseRadia, Can - Snap-In	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-InSeriesB43501Capacitance220μFTolerance±20%Voltage - Rated60VESR (Equivalent Series Resistance)530 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationGeneral PurposeRipple Current - Low Frequency.11A @ 100HzRipple Current - High Frequency.30 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension.0866" Dia (22.00mm)Height - Seated (Max).1063" (27.00mm)Surface Mount Land Size.Pockage / CaseRadial, Can - Snap-In	Category	Capacitors
SeriesB43501Capacitance220µFTolerance±20%Voltage - Rated160VESR (Equivalent Series Resistance)530 mOhm @ 100HzESR (Equivalent Series Resistance)0000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency1.1A @ 100HzInpedance730 mOhmsSize / Dimension0.866° Dia (22.00mm)Size / Dimension.666° Dia (22.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKaila, Can - Snap-In		Aluminum Electrolytic Capacitors
Capacitance20µFTolerance±0%Voltage - Rated160VESR (Equivalent Series Resistance)530 mOhm @ 100HzESR (Equivalent Series Resistance)10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.1A @ 100HzInpedance730 mOhmsIngedance0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Size / Dimension1.603" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKail, Can - Snap-In	Package	Radial, Can - Snap-In
Yolrance±0%Voltage - Rated160VESR (Equivalent Series Resistance)530 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.1A @ 100HzRipple Current - High Frequency0394" (10.00mm)Lead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Series	B43501
Voltage - Rated160VESR (Equivalent Series Resistance)530 mOhm @ 100HzESR (Equivalent Series Resistance)10000 Hrs @ 85°CLifetime @ Temp0000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency-11A @ 100HzHippedance-30 mOhmsInpedance0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can - Snap-In	Capacitance	220µF
For a constraint of a constrai	Tolerance	±20%
Lifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.1A @ 100HzRipple Current - High Frequency-Impedance730 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeRadial, Can - Snap-In	Voltage - Rated	160V
Operating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.1A @ 100HzRipple Current - High Frequency-Impedance730 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	ESR (Equivalent Series Resistance)	530 mOhm @ 100Hz
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.1A @ 100HzRipple Current - High Frequency-Impedance730 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lifetime @ Temp.	10000 Hrs @ 85°C
ApplicationsGeneral PurposeRipple Current - Low Frequency1.1A @ 100HzRipple Current - High Frequency-Impedance730 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency1.1A @ 100HzRipple Current - High Frequency-Impedance730 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Polarization	Polar
In a constraint of a constrain	Applications	General Purpose
Impedance730 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - Low Frequency	1.1A @ 100Hz
Lead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - High Frequency	-
Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Impedance	730 mOhms
Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Size / Dimension	0.866" Dia (22.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Height - Seated (Max)	1.063" (27.00mm)
Package / Case Radial, Can - Snap-In	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors	Package / Case	Radial, Can - Snap-In
		Report errors?

B43501A1227M87 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B43501A1227M87 Payment Methods





If you have any question about B43501A1227M87, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com