

B43501A2188M62

B43501A2188M62 Information

Containance contract	 B43501A2188M62 EPCOS (TDK) Capacitors Aluminum Electrolytic Capacitors CAP ALUM 1800UF 20% 250V SNAP Radial, Can - Snap-In - 3 Lead For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B43501A2188M62 Specifications

Manufacturer Part Number B43501A2188M62 Manufacturer EPCOS (TDK) Category Capacitors Aluminum Electrolytic Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Snap-In - 3 Lead Series B43501 Capacitance B800µF Tolerance ±20% Voltage - Rated 250V ESR (Equivalent Series Resistance) 55 mOhm @ 100Hz Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization General Purpose Applications General Purpose Ripple Current - Low Frequency - 128 @ 100Hz Impedance 5 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 2.244" (57.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Kadial, Can - Snap-In - 3 Lead	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-In - 3 LeadSeriesB43501Capacitance1800µFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)55 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationGeneral PurposeApplications5.12A @ 100HzRipple Current - Low Frequency5.12A @ 100HzImpedance0.394" (10.00mm)Lied Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.244" (57.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Manufacturer Part Number	B43501A2188M62
Aluminum Electrolytic CapacitorsPackageRadial, Can - Snap-In - 3 LeadSeriesB43501Capacitance1800µFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)55 mOhm @ 100HzLifetime @ Temp.00000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationGeneral PurposeApplications5.12A @ 100HzRipple Current - Low Frequency-Impedance75 mOhmsLidetjime Spacing0.394" (10.00mm)Siz / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.44" (57.00mm)Surface Mount Land Size-Mounting TypeRadial, Can - Snap-In - 3 Lead	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-In - 3 LeadSeriesB43501Capacitance1800µFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)55 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationGeneral PurposeRipple Current - Low Frequency5.12A @ 100HzRipple Current - High Frequency.Impedance75 mOhmsLiad Spacing0.394" (10.00mm)Siz / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.244" (57.00mm)Surface Mount Land Size-Mounting TypeFackage / Case	Category	Capacitors
SeriesB43501Capacitance1800µFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)55 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationGeneral PurposeApplications512A @ 100HzRipple Current - Low Frequency5.12A @ 100HzLingedance75 mOhmsLad Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.244" (57.00mm)Surface Mount Land Size-Mounting TypeFurough HolePackage / CaseKadial, Can - Snap-In - 3 Lead		Aluminum Electrolytic Capacitors
Capacitance1800µFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)55 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency5.12A @ 100HzImpedance75 mOhmsSize / Dimension0.394" (10.00mm)Size / Dimension2.244" (57.00mm)Surface Mount Land Size-Mounting TypeFurous HalePackage / CaseRatial, Can - Snap-In - 3 Lead	Package	Radial, Can - Snap-In - 3 Lead
Tolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)55 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarzationPolarApplicationsGeneral PurposeRipple Current - High Frequency5.12A @ 100HzImpedance75 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.244" (57.00mm)Surface Mount Land Size-Mounting TypeRadial, Can - Snap-In - 3 Lead	Series	B43501
Voltage - Rated250VESR (Equivalent Series Resistance)55 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency5.12A @ 100HzRipple Current - High Frequency-Impedance75 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.244" (57.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can - Snap-In - 3 Lead	Capacitance	1800µF
ESR (Equivalent Series Resistance) 55 mOhm @ 100Hz Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polar Polar Applications General Purpose Ripple Current - Low Frequency 5.12A @ 100Hz Impedance - Impedance 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 2.244" (57.00mm) Surface Mount Land Size - Mounting Type Through Hole Rackage / Case Radial, Can - Snap-In - 3 Lead	Tolerance	$\pm 20\%$
Lifetime @ Temp.10000 Hrs @ 85°CDeperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency5.12A @ 100HzRipple Current - High Frequency-Impedance75 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.244" (57.00mm)Surface Mount Land Size-Mounting TypeRadial, Can - Snap-In - 3 Lead	Voltage - Rated	250V
Operating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency5.12A @ 100HzRipple Current - High Frequency-Impedance75 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.244" (57.00mm)Surface Mount Land Size-Mounting TypeFnough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	ESR (Equivalent Series Resistance)	55 mOhm @ 100Hz
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency5.12A @ 100HzRipple Current - High Frequency-Impedance75 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.244" (57.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Lifetime @ Temp.	10000 Hrs @ 85°C
ApplicationsGeneral PurposeRipple Current - Low Frequency5.12A @ 100HzRipple Current - High Frequency-Impedance75 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.244" (57.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency5.12A @ 100HzRipple Current - High Frequency-Impedance75 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.244" (57.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Polarization	Polar
In a constraint of a constrain	Applications	General Purpose
Impedance75 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.244" (57.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Ripple Current - Low Frequency	5.12A @ 100Hz
Lead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.244" (57.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Ripple Current - High Frequency	-
Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.244" (57.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Impedance	75 mOhms
Height - Seated (Max)2.244" (57.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Size / Dimension	1.378" Dia (35.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Height - Seated (Max)	2.244" (57.00mm)
Package / Case Radial, Can - Snap-In - 3 Lead	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors	Package / Case	Radial, Can - Snap-In - 3 Lead
		Report errors?

B43501A2188M62 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B43501A2188M62 Payment Methods





If you have any question about B43501A2188M62, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com