

# B43501A3227M80

#### B43501A3227M80 Information

Heisener.com	Part Number Manufacturer Category Description Package	B43501A3227M80 EPCOS (TDK) Capacitors Aluminum Electrolytic Capacitors CAP ALUM 220UF 20% 385V SNAP Radial, Can - Snap-In For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



### B43501A3227M80 Specifications

Manufacturer Part NumberB43501A3227M80ManufacturerEPCOS (TDK)CategoryCapacitorsAckageAluninum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43501Capacitance20µFTolerance±20%Voltage - Rated85VESR (Equivalent Series Resistance)0000 Mrm @ 100HzLifetime @ Temp.00000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationGeneral PurposeRipple Current - High Frequency-Inpedance490 mOhmsLide Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Hight - Seated (Max).Surface Mount Land Size-Mounting Type-Mounting Type-Pance Meter-Mounting Type-Pance Meter-Mounting Type-Pance Meter-Pance Meter-Pance Meter-Mounting Type-Pance Meter-Pance Meter- <th></th> <th></th>		
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43501Capacitance20µFTolerance±20%Voltage - Rated385VESR (Equivalent Series Resistance)300 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - High Frequency-Impedance409 mOhmsLiad Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Manufacturer Part Number	B43501A3227M80
IdentifyAluminum Electrolytic CapacitonsPackageRadial, Can - Snap-InSeriesB43501Capacitance20\u03c6Tolerance20\u03c6Voltage - Rated855VESR (Equivalent Series Resistance)000 mOhm @ 100HzLifetime @ Temp.00000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Hogh Frequency.414A @ 100HzRipple Current - High Frequency0304° (1.00mm)Lead Spacing0.394° (1.00mm)Size / Dimension.694° Dia (2.00mm)Hight - Seated (Max).6154° (4.200mm)Surface Mount Land Size.Hounting TypeMounting TypePackage / CaseMail Can - Snap-In	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-InSeriesB43501Capacitance220µFTolerance±20%Voltage - Rated385VESR (Equivalent Series Resistance)300 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeRipple Current - Low Frequency-141A @ 100HzKipple Current - High Frequency-394" (10.00mm)Lied Spacing0.994" bia (25.00mm)Size / Dimension1.654" (42.00mm)Surface Mount Land Size-Mounting TypeFirough HolePackage / CaseRadial, Can - Snap-In	Category	Capacitors
SeriesB43501Capacitance220µFTolerance±20%Voltage - Rated385VESR (Equivalent Series Resistance)300 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - High Frequency1.41A @ 100HzInpedance490 mOhmsSize / Dimension0.984" Dia (25.00mm)Size / Dimension1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In		Aluminum Electrolytic Capacitors
Capacitance220µFTolerance±20%Voltage - Rated385VESR (Equivalent Series Resistance)300 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency-Inpedance490 mOhmsLad Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Size / Dimension-Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKadia (Can - Snap-In	Package	Radial, Can - Snap-In
Tolerance±0%Yoltage - Rated385VESR (Equivalent Series Resistance)300 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency1.41A @ 100HzImpedance490 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can - Snap-In	Series	B43501
Voltage - Rated385VESR (Equivalent Series Resistance)300 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency1.41A @ 100HzRipple Current - High Frequency-Impedance490 mOhmsIcad Spacing0.394" (10.00mm)Size / Dimension1.654" (42.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Capacitance	220µF
ESR (Equivalent Series Resistance)300 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.41A @ 100HzRipple Current - High Frequency-Impedance490 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeFuncePackage / CaseRadial, Can - Snap-In	Tolerance	±20%
Lifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.41A @ 100HzRipple Current - High Frequency-Impedance490 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Voltage - Rated	385V
Operating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.41A @ 100HzRipple Current - High Frequency-Impedance490 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeFnough HolePackage / CaseRadia, Can - Snap-In	ESR (Equivalent Series Resistance)	300 mOhm @ 100Hz
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.41A @ 100HzRipple Current - High Frequency-Impedance490 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lifetime @ Temp.	10000 Hrs @ 85°C
ApplicationsGeneral PurposeRipple Current - Low Frequency1.41A @ 100HzRipple Current - High Frequency-Impedance490 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Operating Temperature	$-40^{\circ}$ C ~ $85^{\circ}$ C
Ripple Current - Low Frequency1.41A @ 100HzRipple Current - High Frequency-Impedance490 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Polarization	Polar
In a constraint of a constrain	Applications	General Purpose
Impedance490 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - Low Frequency	1.41A @ 100Hz
Lead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - High Frequency	-
Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Impedance	490 mOhms
Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Size / Dimension	0.984" Dia (25.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Height - Seated (Max)	1.654" (42.00mm)
Package / Case Radial, Can - Snap-In	Surface Mount Land Size	-
	Mounting Type	Through Hole
Paport area	Package / Case	Radial, Can - Snap-In
<b>Report</b> end		Report errors?

#### B43501A3227M80 Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE BUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### B43501A3227M80 Payment Methods





If you have any question about B43501A3227M80, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com