

# B43501A3477M60

#### B43501A3477M60 Information

Contraction of the second seco		B43501A3477M60 EPCOS (TDK) Capacitors Aluminum Electrolytic Capacitors CAP ALUM 470UF 20% 385V SNAP Radial, Can - Snap-In For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



### B43501A3477M60 Specifications

ManufacturerEPCOS (TDK)CapacitorsCapacitorsAtuminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43501Capacitance470µFTolerance±20%Voltage - Rated385VESR (Equivalent Series Resistance)140 mOhm @ 100HzDerating Temperature40°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRiple Current - High Frequency-Lifed Spacing30 mOhmsSiz / Dimension1.378° Dia (35.00mm)Siz / Dimension1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough Hole		
CapacitorsCapacitorsAckageRadial, Can - Snap-InPackageRadial, Can - Snap-InSeriesB43501Capacitance470µFTolerance±20%Voltage - Rated385VESR (Equivalent Series Resistance)140 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeRiple Current - Low Frequency2.5A @ 100HzRiple Current - High Frequency-Impedance230 mOhmsSize / Dimension1.378° Dia (35.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Manufacturer Part Number	B43501A3477M60
Aluminum Electrolytic CapacitonsPackageRadial, Can - Snap-InSeriesB43501Capacitance470µFColerance±20%Voltage - Rated385VESR (Equivalent Series Resistance)140 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationGeneral PurposeRipple Current - Low Frequency2.5A @ 100HzRipple Current - High Frequency-Size / Dimension3.30" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max).Surface Mount Land Size-Package / CaseRadia, Can - Snap-In	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-InSeriesB43501Capacitance470µFColorance±20%Voltage - Rated385VESR (Equivalent Series Resistance)140 mOhm @ 100HzLifetime @ Temp.0000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolariCapacitanceApplicationsGeneral PurposeRipple Current - Low Frequency2.5 A @ 100HzRipple Current - High Frequency30 mOhmsSize / Dimension1.378" Dia (35.00mm)Size / Dimension1.654" (42.00mm)Height - Seated (Max)-Kurface Mount Land Size-Package / CaseRadia, Can - Snap-In	Category	Capacitors
SeriesB43501Capacitance470µFTolerance±20%Voltage - Rated385VESR (Equivalent Series Resistance)140 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.5A @ 100HzLifetime G30 mOhmsSize / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Package / CaseRadial, Can - Snap-In		Aluminum Electrolytic Capacitors
Capacitance470µFTolerance±20%Voltage - Rated385VESR (Equivalent Series Resistance)140 mOhm @ 100HzESR (Equivalent Series Resistance)10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.5A @ 100HzBisple Current - High Frequency-Size / Dimension1.378" Dia (35.00mm)Bise / Dimension1.654" (42.00mm)Surface Mount Land Size-Pounting TypeRial, Can - Snap-In	Package	Radial, Can - Snap-In
Polerance±0%Voltage - Rated385VESR (Equivalent Series Resistance)140 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.5A @ 100HzRipple Current - High Frequency-Impedance230 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.654" (42.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Package / CaseRatial, Can - Snap-In	Series	B43501
Voltage - Rated385VESR (Equivalent Series Resistance)140 mOhm @ 100HzESR (Equivalent Series Resistance)10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarPolarizationsGeneral PurposeApplicationsScA @ 100HzRipple Current - Low Frequency2.5A @ 100HzImpedance230 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.654" (42.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Package / CaseRadial, Can - Snap-In	Capacitance	470µF
Constraint140 mOhm @ 100HzESR (Equivalent Series Resistance)10000 Hrs @ 85°CDerating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.5A @ 100HzRipple Current - High Frequency-Impedance230 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.654" (42.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Package / CaseRadial, Can - Snap-In	Tolerance	$\pm 20\%$
Lifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeApple Current - Low Frequency2.5A @ 100HzRipple Current - High Frequency-Impedance230 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Voltage - Rated	385V
Operating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.5A @ 100HzRipple Current - High Frequency-Impedance230 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)-Surface Mount Land Size-Package / CaseRatial, Can - Snap-In	ESR (Equivalent Series Resistance)	140 mOhm @ 100Hz
PolarizationPolarPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance230 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lifetime @ Temp.	10000 Hrs @ 85°C
ApplicationsGeneral PurposeRipple Current - Low Frequency2.5A @ 100HzRipple Current - High Frequency-Impedance230 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency2.5A @ 100HzRipple Current - High Frequency-Impedance230 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Polarization	Polar
Ripple Current - High Frequency-Impedance230 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Applications	General Purpose
Impedance230 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - Low Frequency	2.5A @ 100Hz
IOutputLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - High Frequency	-
Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Impedance	230 mOhms
Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Size / Dimension	1.378" Dia (35.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Height - Seated (Max)	1.654" (42.00mm)
Package / Case Radial, Can - Snap-In	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can - Snap-In
		Report errors?

#### B43501A3477M60 Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE BUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### B43501A3477M60 Payment Methods





If you have any question about B43501A3477M60, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com