

B43501A5567M67

B43501A5567M67 Information

Contraction Com	 B43501A5567M67 EPCOS (TDK) Capacitors Aluminum Electrolytic Capacitors CAP ALUM 560UF 20% 450V SNAP Radial, Can - Snap-In For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B43501A5567M67 Specifications

SeriesB43501Capacitance560µFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)240 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.91A @ 100HzLiad Spacing.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.244" (57.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKadial, Can - Snap-In		
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43501Capacitance560µFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)240 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeRipple Current - Low Frequency2.91A @ 100HzRipple Current - High Frequency-Impedance0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Size / Dimension1.378" Dia (35.00mm)Size / Dimension2.244" (57.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Manufacturer Part Number	B43501A5567M67
Aluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43501Capacitance560µFTolerance±20%Voltage - Rated450 VESR (Equivalent Series Resistance)240 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeRipple Current - Low Frequency291A @ 100HzRipple Current - High Frequency-Impedance290 mOhmsLiad Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.244" (57.00mm)Surface Mount Land Size-Package / CaseKadial, Can - Snap-In	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-InSeriesB43501Capacitance560µFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)240 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeRiple Current - Low Frequency-Impedance290 mOhmsLiad Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Size / Dimension2.244" (57.00mm)Surface Mount Land Size-Mounting TypeFhrough HolePackage / CaseKadial, Can - Snap-In	Category	Capacitors
SeriesB43501Capacitance560µFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)240 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.91A @ 100HzLiad Spacing.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.244" (57.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKadial, Can - Snap-In		Aluminum Electrolytic Capacitors
Capacitance560µFColarance±20%Voltage - Rated450VESR (Equivalent Series Resistance)240 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance290 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.244" (57.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Package	Radial, Can - Snap-In
Tolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)240 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.91A @ 100HzImpedance290 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.244" (57.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can - Snap-In	Series	B43501
Voltage - Rated450VESR (Equivalent Series Resistance)240 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.91A @ 100HzImpedance90 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.244" (57.00mm)Surface Mount Land Size-Mounting TypeRadial, Can - Snap-In	Capacitance	560µF
ESR240 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.91A @ 100HzBipple Current - High Frequency-Impedance290 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.244" (57.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Tolerance	$\pm 20\%$
Lifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.91A @ 100HzRipple Current - High Frequency-Impedance290 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.244" (57.00mm)Surface Mount Land Size-Mounting TypeFurough HolePackage / CaseRadial, Can - Snap-In	Voltage - Rated	450V
Operating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.91A @ 100HzRipple Current - High Frequency-Impedance290 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.244" (57.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	ESR (Equivalent Series Resistance)	240 mOhm @ 100Hz
PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.91A @ 100HzRipple Current - High Frequency-Impedance290 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.244" (57.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lifetime @ Temp.	10000 Hrs @ 85°C
ApplicationsGeneral PurposeRipple Current - Low Frequency2.91A @ 100HzRipple Current - High Frequency-Impedance290 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.244" (57.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency2.91A @ 100HzRipple Current - High Frequency-Impedance290 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.244" (57.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Polarization	Polar
Ripple Current - High Frequency-Impedance290 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.244" (57.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Applications	General Purpose
Impedance290 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.244" (57.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - Low Frequency	2.91A @ 100Hz
IILead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.244" (57.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - High Frequency	-
Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.244" (57.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Impedance	290 mOhms
Height - Seated (Max)2.244" (57.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Size / Dimension	1.378" Dia (35.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Height - Seated (Max)	2.244" (57.00mm)
Package / Case Radial, Can - Snap-In	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can - Snap-In
		Report errors?

B43501A5567M67 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B43501A5567M67 Payment Methods





If you have any question about B43501A5567M67, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com