

### B43501A9686M60

#### B43501A9686M60 Information

Heisener.com	 B43501A9686M60 EPCOS (TDK) Capacitors Aluminum Electrolytic Capacitors CAP ALUM 68UF 20% 400V SNAP Radial, Can - Snap-In For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

#### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



#### B43501A9686M60 Specifications

Anufacturer EPCOS (TDK)   Category Capacitors   Aluminum Electrolytic Capacitors Aluminum Electrolytic Capacitors   Package Radial, Can - Snap-In   Series B43501   Capacitance 68µF   Tolerance ±20%   Voltage - Rated 400V   ESR (Equivalent Series Resistance) 980 mOhm @ 100Hz   Lifetime @ Temp. 10000 Hrs @ 85°C   Operating Temperature -40°C ~ 85°C   Polarization General Purpose   Applications General Purpose   Ripple Current - Low Frequency -   Impedance 1.56 Ohms   Lead Spacing 0.394" (10.00mm)   Size / Dimension 0.866" Dia (22.00mm)   Height - Seated (Max) 1.063" (27.00mm)   Surface Mount Land Size -   Mounting Type Through Hole	_	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43501Capacitance68µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)980 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency610mA @ 100HzRipple Current - High Frequency-Impedance1.56 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can - Snap-In	Manufacturer Part Number	B43501A9686M60
Aluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43501Capacitance68µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)980 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeRipple Current - Low Frequency610mA @ 100HzRipple Current - High Frequency-Ingedance1.56 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Package / CaseRadial, Can - Snap-In	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-InSeriesB43501Capacitance68µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)980 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeRiple Current - Low Frequency610mA @ 100HzRiple Current - High Frequency.56 OhmsLad Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Package / CaseRadial, Can - Snap-In	Category	Capacitors
SeriesB43501Capacitance68µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)980 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency610mA @ 100HzLied Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max).Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In		Aluminum Electrolytic Capacitors
Capacitance 68μF   Tolerance ±20%   Voltage - Rated 400V   ESR (Equivalent Series Resistance) 980 mOhm @ 100Hz   Lifetime @ Temp. 10000 Hrs @ 85°C   Operating Temperature -40°C ~ 85°C   Polarization Polar   Applications General Purpose   Ripple Current - Low Frequency 610mA @ 100Hz   Impedance 1.56 Ohms   Lead Spacing 0.394" (10.00mm)   Size / Dimension 0.866" Dia (22.00mm)   Surface Mount Land Size -   Mounting Type Through Hole   Package / Case Radial, Can - Snap-In	Package	Radial, Can - Snap-In
Tolerance±0%Voltage - Rated400VESR (Equivalent Series Resistance)980 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency610mA @ 100HzRipple Current - High Frequency-Impedance1.56 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can - Snap-In	Series	B43501
Voltage - Rated400VESR (Equivalent Series Resistance)980 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency610mA @ 100HzImpedance.56 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Package / CaseRadial, Can - Snap-In	Capacitance	68µF
ESR (Equivalent Series Resistance)980 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency610mA @ 100HzBipple Current - High Frequency-Impedance1.56 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeRadial, Can - Snap-In	Tolerance	±20%
Lifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency610mA @ 100HzRipple Current - High Frequency-Impedance1.56 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Voltage - Rated	400V
Operating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency610mA @ 100HzRipple Current - High Frequency-Impedance1.56 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	ESR (Equivalent Series Resistance)	980 mOhm @ 100Hz
PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency610mA @ 100HzRipple Current - High Frequency-Impedance1.56 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lifetime @ Temp.	10000 Hrs @ 85°C
ApplicationsGeneral PurposeRipple Current - Low Frequency610mA @ 100HzRipple Current - High Frequency-Impedance1.56 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency610mA @ 100HzRipple Current - High Frequency-Impedance1.56 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Polarization	Polar
Ripple Current - High Frequency-Impedance1.56 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Applications	General Purpose
Impedance1.56 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - Low Frequency	610mA @ 100Hz
IILead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - High Frequency	-
Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Impedance	1.56 Ohms
Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Size / Dimension	0.866" Dia (22.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Height - Seated (Max)	1.063" (27.00mm)
Package / Case Radial, Can - Snap-In	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can - Snap-In
		Report errors?

#### B43501A9686M60 Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

## SERVICE EUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

DISCOVER

# B43501A9686M60 Payment Methods

#### B43501A9686M60 Shipping Methods



If you have any question about B43501A9686M60, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com