

# B43501B3337M60

#### B43501B3337M60 Information

Contraction of the second		B43501B3337M60 EPCOS (TDK) Capacitors Aluminum Electrolytic Capacitors CAP ALUM 330UF 20% 385V SNAP Radial, Can - Snap-In For the pricing/inventory/lead time, please contact	
For Reference	Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



### B43501B3337M60 Specifications

Manufacturer Part Number B43501B3337M60   Manufacturer EPCOS (TDK)   Category Capacitors   Aluminum Electrolytic Capacitors Aluminum Electrolytic Capacitors   Package Radial, Can - Snap-In   Series B43501   Capacitance 330µF   Tolerance 2000 mOhm @ 100Hz   Voltage - Rated 385V   ESR (Equivalent Series Resistance) 2000 mOhm @ 100Hz   Lifetime @ Temp. 10000 Mrs @ 85°C   Operating Temperature 40°C ~ 85°C   Polarization General Purpose   Ripple Current - Low Frequency 1.88A @ 100Hz   Impedance 330 mOhms   Lead Spacing 0.394" (10.00mm)   Size / Dimension 0.984" Dia (25.00mm)   Size / Dimension 0.944" Dia (25.00mm)   Size / Dimension 2.047" (52.00mm)   Height - Seated (Max) 2.047" (52.00mm)   Size / Dimension -   Mounting Type -   Mounting Type -	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43501Capacitance330µFTolerance±20%Voltage - Rated385VESR (Equivalent Series Resistance)200 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency.Impedance330 mOhmsLied Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Sirface Mount Land Size.Mounting TypeFnough HolePackage / CaseRadial, Can - Snap-In	Manufacturer Part Number	B43501B3337M60
IdentifyAluminum Electrolytic CapacitonsPackageRadial, Can - Snap-InSeriesB43501Capacitance30µFTolerance±20%Voltage - Rated885VESR (Equivalent Series Resistance)000 mOhm @ 100HzLifetime @ Temp.00000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationGeneral PurposeRipple Current - Low Frequency.Ripple Current - High Frequency.30 mOhmsLided Spacing.30 mOhmsLided Spacing.30 mOhmsLead Spacing.30 mOhmsSize / Dimension.984" Dia (25.00mm)Size / Dimension.040" (52.00mm)Surface Mount Land Size.Mounting TypeThrough HolePackage / CaseRatia, Can - Snap-In	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-InSeriesB43501Capacitance30µFTolerance±20%Voltage - Rated385VESR (Equivalent Series Resistance)000 mOhm @ 100HzLifetime @ Temp.0000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency1.88A @ 100HzImpedance0.304" (10.00mm)Lead Spacing0.944" Dia (25.00mm)Size / Dimension2.047" (52.00mm)Size / Dimension-Mounting TypeFnough HolePackage / CaseKail, Can - Snap-In	Category	Capacitors
SeriesB43501Capacitance330µFTolerance±20%Voltage - Rated385VESR (Equivalent Series Resistance)200 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency1.88A @ 100HzInpedance330 mOhnsSize / Dimension0.984" 10.00mm)Size / Dimension0.984" 10.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKadia, Can - Snap-In		Aluminum Electrolytic Capacitors
Capacitance330µFTolerance±20%Voltage - Rated385VESR (Equivalent Series Resistance)200 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.88A @ 100HzInpedance30 mOhmsLad Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-<	Package	Radial, Can - Snap-In
Tolerance±20%Yoltage - Rated385VESR (Equivalent Series Resistance)200 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.88A @ 100HzRipple Current - High Frequency-Impedance330 mOhmsSize / Dimension0.984" Dia (25.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can - Snap-In	Series	B43501
Voltage - Rated385VESR (Equivalent Series Resistance)200 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.88A @ 100HzImpedance-Impedance330 mOhmsIstay Seried (Max)0.984" Dia (25.00mm)Size / Dinension2.047" (52.00mm)Height - Seated (Max)-Surface Mount Land Size-Pounting TypeThrough HolePackage / CaseRatial, Can - Snap-In	Capacitance	330µF
FSR (Equivalent Series Resistance)200 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.88A @ 100HzRipple Current - High Frequency-Impedance330 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeFackage / Case	Tolerance	$\pm 20\%$
Lifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.88A @ 100HzRipple Current - High Frequency-Impedance330 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Voltage - Rated	385V
Operating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.88A @ 100HzRipple Current - High Frequency-Impedance330 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	ESR (Equivalent Series Resistance)	200 mOhm @ 100Hz
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.88A @ 100HzRipple Current - High Frequency-Impedance330 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lifetime @ Temp.	10000 Hrs @ 85°C
ApplicationsGeneral PurposeRipple Current - Low Frequency1.88A @ 100HzRipple Current - High Frequency-Impedance330 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency1.88A @ 100HzRipple Current - High Frequency-Impedance330 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Polarization	Polar
In a randomRipple Current - High Frequency-Impedance330 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Applications	General Purpose
Impedance330 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - Low Frequency	1.88A @ 100Hz
IILead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - High Frequency	-
Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Impedance	330 mOhms
Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Size / Dimension	0.984" Dia (25.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Height - Seated (Max)	2.047" (52.00mm)
Package / Case Radial, Can - Snap-In	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report error	Package / Case	Radial, Can - Snap-In
		Report errors?

#### B43501B3337M60 Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE BUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### B43501B3337M60 Payment Methods





If you have any question about B43501B3337M60, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com