

B43501B3567M60

equest a Quote

B43501B3567M60 Information

57M60 K)
lectrolytic Capacitors
560UF 20% 385V SNAP
- Snap-In
ng/inventory/lead time, please contact
os://www.heisener.com
1

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B43501B3567M60 Specifications

Manufacturer Part Number B43501B3567M60 Manufacturer EPCOS (TDK) Category Capacitors Aluminum Electrolytic Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Snap-In Series B43501 Capacitance SofoµF Tolerance ±20% Voltage - Rated 385 V ESR (Equivalent Series Resistance) 10000 Mrs @ 85°C Operating Temperature 40°C ~ 85°C Polarization General Purpose Applications General Purpose Rippe Current - Low Frequency 2.76A @ 100Hz Ippedance 190 mOhms Lead Spacing 0.394° (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Size / Dimension 2.244" (57.00mm) Size / Dimension 2.244" (57.00mm) Size / Dimension Force Hale Mounting Type Action Canacitane	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43501Capacitance560µFTolerance±20%Voltage - Rated385VESR (Equivalent Series Resistance)120 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeRipple Current - Low Frequency2.76A @ 100HzRipple Current - High Frequency-Impedance190 mOhmsLied Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Surface Mount Land Size-Mounting TypeFhrough HolePackage / CaseRadial, Can - Snap-In	Manufacturer Part Number	B43501B3567M60
IdentifyAluminum Electrolytic CapacitonsPackageRadial, Can - Snap-InSeriesB43501Capacitance560µFTolerance±20%Voltage - Rated385VESR (Equivalent Series Resistance)120 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationGeneral PurposeApplicationsS76A @ 100HzRipple Current - High Frequency-Impedance100 mOhmsLided Spacing0.394" (10.00mm)Size / Dimension1.81" Dia (30.00mm)Size / Dimension2.244" (57.00mm)Hight - Seated (Max)-Mounting TypeFurough HolePackage / CaseMail, Can - Snap-In	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-InSeriesB43501Capacitance560μFTolerance±20%Voltage - Rated385VESR (Equivalent Series Resistance)120 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationGeneral PurposeRipple Current - Low Frequency2.76A @ 100HzImpedance109 mOhmsLiad Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Size / Dimension2.244" (57.00mm)Surface Mount Land Size-Mounting TypeRatial, Can - Snap-In	Category	Capacitors
SeriesB43501Capacitance560µFTolerance±20%Voltage - Rated385VESR (Equivalent Series Resistance)120 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.76A @ 100HzImpedance109 mOhmsLiad Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Size / Dimension2.244" (57.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In		Aluminum Electrolytic Capacitors
Capacitance560µFTolerance±20%Voltage - Rated385VESR (Equivalent Series Resistance)100 mm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - High Frequency-Impedance190 mOhmsLad Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Size / Dimension-Height - Seated (Max)-Surface Mount Land Size-Hounting TypeThrough HolePackage / CaseStail, Can - Snap-In	Package	Radial, Can - Snap-In
Toleance±0%Voltage - Rated385VESR (Equivalent Series Resistance)120 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.76A @ 100HzBipple Current - High Frequency0394" (10.00mm)Lead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)2.244" (57.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can - Snap-In	Series	B43501
Voltage - Rated385VESR (Equivalent Series Resistance)120 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.76A @ 100HzImpedance190 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)2.244" (57.00mm)Surface Mount Land Size-Hounting TypeThrough HolePackage / CaseRatia, Can - Snap-In	Capacitance	560µF
ESR (Equivalent Series Resistance)120 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.76A @ 100HzRipple Current - High Frequency-Impedance190 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeFurogan CarlencePackage / CaseRadial, Can - Snap-In	Tolerance	±20%
Lifetime @ Temp.10000 Hrs @ 85°CDperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.76A @ 100HzRipple Current - High Frequency-Impedance190 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)2.244" (57.00mm)Surface Mount Land Size-Mounting TypeRadial, Can - Snap-In	Voltage - Rated	385V
Operating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.76A @ 100HzRipple Current - High Frequency-Impedance190 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	ESR (Equivalent Series Resistance)	120 mOhm @ 100Hz
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.76A @ 100HzRipple Current - High Frequency-Impedance190 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)2.244" (57.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lifetime @ Temp.	10000 Hrs @ 85°C
ApplicationsGeneral PurposeRipple Current - Low Frequency2.76A @ 100HzRipple Current - High Frequency-Impedance190 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)2.244" (57.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency2.76A @ 100HzRipple Current - High Frequency-Impedance190 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)2.244" (57.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Polarization	Polar
In a constraint of the product of t	Applications	General Purpose
Impedance190 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)2.244" (57.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - Low Frequency	2.76A @ 100Hz
Lead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)2.244" (57.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - High Frequency	-
Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)2.244" (57.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Impedance	190 mOhms
Height - Seated (Max)2.244" (57.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Size / Dimension	1.181" Dia (30.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Height - Seated (Max)	2.244" (57.00mm)
Package / Case Radial, Can - Snap-In	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors	Package / Case	Radial, Can - Snap-In
1		Report errors?

B43501B3567M60 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B43501B3567M60 Payment Methods





If you have any question about B43501B3567M60, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com