



### **B43501B3567M62 Information**

Heisener.com

For Reference Only

**Part Number** B43501B3567M62 Manufacturer EPCOS (TDK) Category

Capacitors

**Aluminum Electrolytic Capacitors Description** CAP ALUM 560UF 20% 385V SNAP

Radial, Can - Snap-In - 3 Lead **Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# B43501B3567M62 Specifications

Manufacturer Part Number         B43501B3567M62           Manufacturer         EPCOS (TDK)           Category         Capacitors           Package         Radial, Can - Snap-In - 3 Lead           Series         B43501           Capacitance         560μF           Tolerance         ±20%           Voltage - Rated         385V           ESR (Equivalent Series Resistance)         120 mOhm @ 100Hz           Lifetime @ Temp.         10000 Hrs @ 85°C           Operating Temperature         -40°C ~ 85°C           Polarization         General Purpose           Ripple Current - Low Frequency         2,76A @ 100Hz           Ripple Current - High Frequency         -           Lead Spacing         0,394" (10.00mm)           Size / Dimension         1,181" Dia (30.00mm)           Leight - Seated (Max)         2,244" (57.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can - Snap-In - 3 Lead	*	
Category         Capacitors           Package         Radial, Can - Snap-In - 3 Lead           Series         B43501           Capacitance         560µF           Tolerance         ±20%           Voltage - Rated         385V           ESR (Equivalent Series Resistance)         120 mOhm @ 100Hz           Lifetime @ Temp.         10000 Hrs @ 85°C           Operating Temperature         -40°C ~ 85°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         2.76A @ 100Hz           Ripple Current - High Frequency         -           Impedance         190 mOhms           Lead Spacing         0.394" (10.00mm)           Size / Dimension         1.181" Dia (30.00mm)           Height - Seated (Max)         2.244" (57.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can - Snap-In - 3 Lead	Manufacturer Part Number	B43501B3567M62
Package         Radial, Can - Snap-In - 3 Lead           Series         B43501           Capacitance         560μF           Tolerance         ±20%           Voltage - Rated         385V           ESR (Equivalent Series Resistance)         120 mOhm @ 100Hz           Lifetime @ Temp.         10000 Hrs @ 85°C           Operating Temperature         -40°C ~ 85°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         2.76A @ 100Hz           Ripple Current - High Frequency         -           Impedance         190 mOhms           Lead Spacing         0.394" (10.00mm)           Size / Dimension         1.181" Dia (30.00mm)           Height - Seated (Max)         2.244" (57.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can - Snap-In - 3 Lead	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-In - 3 LeadSeriesB43501Capacitance560μFTolerance±20%Voltage - Rated385VESR (Equivalent Series Resistance)120 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.76A @ 100HzRipple Current - High Frequency-Impedance190 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)2.244" (57.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Category	Capacitors
Series         B43501           Capacitance         560μF           Tolerance         ±20%           Voltage - Rated         385V           ESR (Equivalent Series Resistance)         120 mOhm @ 100Hz           Lifetime @ Temp.         10000 Hrs @ 85°C           Operating Temperature         -40°C ~ 85°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         2.76A @ 100Hz           Ripple Current - High Frequency         -           Impedance         190 mOhms           Lead Spacing         0.394" (10.00mm)           Size / Dimension         1.181" Dia (30.00mm)           Height - Seated (Max)         2.244" (57.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can - Snap-In - 3 Lead		Aluminum Electrolytic Capacitors
Capacitance         560μF           Tolerance         ±20%           Voltage - Rated         385V           ESR (Equivalent Series Resistance)         120 mOhm @ 100Hz           Lifetime @ Temp.         10000 Hrs @ 85°C           Operating Temperature         -40°C ~ 85°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         2.76A @ 100Hz           Ripple Current - High Frequency         -           Impedance         190 mOhms           Lead Spacing         0.394" (10.00mm)           Size / Dimension         1.181" Dia (30.00mm)           Height - Seated (Max)         2.244" (57.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can - Snap-In - 3 Lead	Package	Radial, Can - Snap-In - 3 Lead
Tolerance ±20%  Voltage - Rated 385V  ESR (Equivalent Series Resistance) 120 mOhm @ 100Hz  Lifetime @ Temp. 10000 Hrs @ 85°C  Operating Temperature -40°C ~ 85°C  Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 2.76A @ 100Hz  Ripple Current - High Frequency -  Impedance 190 mOhms  Lead Spacing 0.394" (10.00mm)  Size / Dimension 1.181" Dia (30.00mm)  Height - Seated (Max) 2.244" (57.00mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can - Snap-In - 3 Lead	Series	B43501
Voltage - Rated385 VESR (Equivalent Series Resistance)120 mOhm @ 100 HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.76A @ 100 HzRipple Current - High Frequency-Impedance190 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)2.244" (57.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Capacitance	560μF
ESR (Equivalent Series Resistance)  Lifetime @ Temp.  Operating Temperature  -40°C ~ 85°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  2.76A @ 100Hz  Ripple Current - High Frequency  Impedance  190 mOhms  Lead Spacing  0.394" (10.00mm)  Size / Dimension  1.181" Dia (30.00mm)  Height - Seated (Max)  2.244" (57.00mm)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can - Snap-In - 3 Lead	Tolerance	±20%
Lifetime @ Temp.  10000 Hrs @ 85°C  Operating Temperature  -40°C ~ 85°C  Polarization  Applications  Ripple Current - Low Frequency  Ripple Current - High Frequency  Impedance  Lead Spacing  Size / Dimension  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Package / Case  10000 Hrs @ 85°C  -40°C ~ 85°C  General Purpose  2.76A @ 100Hz  -100Hz  -100Hz  -100Hs  -110High - Can - Snap-In - 3 Lead	Voltage - Rated	385V
Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency - Impedance 190 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 2.244" (57.00mm) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead	ESR (Equivalent Series Resistance)	120 mOhm @ 100Hz
Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 2.76A @ 100Hz  Ripple Current - High Frequency -  Impedance 190 mOhms  Lead Spacing 0.394" (10.00mm)  Size / Dimension 1.181" Dia (30.00mm)  Height - Seated (Max) 2.244" (57.00mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can - Snap-In - 3 Lead	Lifetime @ Temp.	10000 Hrs @ 85°C
Applications General Purpose  Ripple Current - Low Frequency 2.76A @ 100Hz  Ripple Current - High Frequency - Impedance 190 mOhms  Lead Spacing 0.394" (10.00mm)  Size / Dimension 1.181" Dia (30.00mm)  Height - Seated (Max) 2.244" (57.00mm)  Surface Mount Land Size - Mounting Type Through Hole  Package / Case Radial, Can - Snap-In - 3 Lead	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency  Ripple Current - High Frequency  Impedance  190 mOhms  Lead Spacing  0.394" (10.00mm)  Size / Dimension  1.181" Dia (30.00mm)  Height - Seated (Max)  2.244" (57.00mm)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can - Snap-In - 3 Lead	Polarization	Polar
Ripple Current - High Frequency Impedance 190 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 2.244" (57.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead	Applications	General Purpose
Impedance190 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)2.244" (57.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Ripple Current - Low Frequency	2.76A @ 100Hz
Lead Spacing 0.394" (10.00mm)  Size / Dimension 1.181" Dia (30.00mm)  Height - Seated (Max) 2.244" (57.00mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can - Snap-In - 3 Lead	Ripple Current - High Frequency	-
Size / Dimension 1.181" Dia (30.00mm)  Height - Seated (Max) 2.244" (57.00mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can - Snap-In - 3 Lead	Impedance	190 mOhms
Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can - Snap-In - 3 Lead	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size -  Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead	Size / Dimension	1.181" Dia (30.00mm)
Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead	Height - Seated (Max)	2.244" (57.00mm)
Package / Case Radial, Can - Snap-In - 3 Lead	Surface Mount Land Size	-
-	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can - Snap-In - 3 Lead
		Report errors?

#### **B43501B3567M62 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### B43501B3567M62 Payment Methods



















# B43501B3567M62 Shipping Methods













If you have any question about B43501B3567M62, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com