



B43501B5107M60 Information

(Heisener.com

For Reference Only

Part NumberB43501B5107M60ManufacturerEPCOS (TDK)CategoryCapacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 100UF 20% 450V SNAP

Package Radial, Can - Snap-In

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









B43501B5107M60 Specifications

Manufacturer Part Number Manufacturer EPCOS (TDK) Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Snap-In Series B43501 Capacitance 100µF Tolerance ±20% Voltage - Rated ESR (Equivalent Series Resistance) Lifetime @ Temp. Operating Temperature Polarization Applications Rightle Current - Low Frequency B43501 Capacitors Radial, Can - Snap-In B43501 Capacitors B43501 Capacitors B43501 LiOuµF 100µF 100µF 100µF 1.33 Ohm @ 100Hz 1.33 Ohm @ 100Hz Capacitors Capacitors B43501 Lifetime @ Temp. D1000 Hrs @ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency
$\begin{tabular}{lllllllllllllllllllllllllllllllllll$
Aluminum Electrolytic Capacitors Package Radial, Can - Snap-In Series B43501 Capacitance 100μF Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) 1.33 Ohm @ 100Hz Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 860mA @ 100Hz
PackageRadial, Can - Snap-InSeriesB43501Capacitance $100\mu F$ Tolerance $\pm 20\%$ Voltage - Rated $450V$ ESR (Equivalent Series Resistance) $1.33 \text{ Ohm @ } 100\text{Hz}$ Lifetime @ Temp. $10000 \text{ Hrs @ } 85^{\circ}\text{C}$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency $860\text{mA @ } 100\text{Hz}$
SeriesB43501Capacitance $100\mu F$ Tolerance $\pm 20\%$ Voltage - Rated $450V$ ESR (Equivalent Series Resistance) $1.33 \text{ Ohm } @ 100\text{Hz}$ Lifetime @ Temp. $10000 \text{ Hrs } @ 85^{\circ}\text{C}$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency $860\text{mA} @ 100\text{Hz}$
Capacitance $100\mu F$ Tolerance $\pm 20\%$ Voltage - Rated $450V$ ESR (Equivalent Series Resistance) $1.33 \text{ Ohm @ }100\text{Hz}$ Lifetime @ Temp. $10000 \text{ Hrs @ }85^{\circ}\text{C}$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency $860\text{mA @ }100\text{Hz}$
Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) 1.33 Ohm @ 100Hz Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 860mA @ 100Hz
Voltage - Rated 450V ESR (Equivalent Series Resistance) 1.33 Ohm @ 100Hz Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 860mA @ 100Hz
ESR (Equivalent Series Resistance) Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency 1.33 Ohm @ 100Hz 10000 Hrs @ 85°C -40°C ~ 85°C Polar Polar Applications General Purpose
Lifetime @ Temp. $10000 \text{Hrs} \@ 85^{\circ}\text{C}$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency $860\text{mA} \@ 100\text{Hz}$
Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 860mA @ 100Hz
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 860mA @ 100Hz
Applications General Purpose Ripple Current - Low Frequency 860mA @ 100Hz
Ripple Current - Low Frequency 860mA @ 100Hz
Ripple Current - High Frequency -
Impedance 1.6 Ohms
Lead Spacing 0.394" (10.00mm)
Size / Dimension 0.984" Dia (25.00mm)
Height - Seated (Max) 1.260" (32.00mm)
Surface Mount Land Size -
Mounting Type Through Hole
Package / Case Radial, Can - Snap-In
Report errors?

B43501B5107M60 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

B43501B5107M60 Payment Methods



















B43501B5107M60 Shipping Methods













If you have any question about B43501B5107M60, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com