

B43501B5107M82

Request a Quote

B43501B5107M82 Information

Heisener.com	Part Number	B43501B5107M82	
	Manufacturer	EPCOS (TDK)	
	Category	Capacitors Aluminum Electrolytic Capacitors	
	Description	CAP ALUM 100UF 20% 450V SNAP	
	Package	Radial, Can - Snap-In - 3 Lead	
		For the pricing/inventory/lead time, please contact	
For Reference Only		us	
		Website: https://www.heisener.com	
T of Reference only		E-mail: salesdept@heisener.com	

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B43501B5107M82 Specifications

Manufacturer Part Number B43501B5107M82 Manufacturer EPCOS (TDK) Category Capacitors Aluminum Electrolytic Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Snap-In - 3 Lead Series B43501 Capacitance 100µF Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) 1.33 Ohm @ 100Hz Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization General Purpose Applications General Purpose Ripple Current - Low Frequency - Impedance 1.6 Ohms Lead Spacing 0.394" (10.00mm) Size / Dimension 0.984" Dia (20.00mm) Size / Dimension - Mounting Type - Mounting Type Through Hole	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-In - 3 LeadSeriesB43501Capacitance100µFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)1.33 Ohm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeRipple Current - Low Frequency860mA @ 100HzRipple Current - High Frequency-Impedance1.6 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Manufacturer Part Number	B43501B5107M82
Auminum Electrolytic CapacitorsPackageRadial, Can - Snap-In - 3 LeadSeriesB43501Capacitance100µFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)1.33 Ohm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeRipple Current - Low Frequency660mA @ 100HzRipple Current - High Frequency-Impedance1.6 OhmsLead Spacing0.394" (10.00mm)Size / Dimension1.260" (32.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeFurough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-In - 3 LeadSeriesB43501Capacitance100µFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)1.33 Ohm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationGeneral PurposeRipple Current - Low Frequency60mA @ 100HzRipple Current - High Frequency-Impedance1.6 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Category	Capacitors
SeriesB43501Capacitance100µFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)1.33 Ohm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency860mA @ 100HzLied Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeFurough HolePackage / CaseKadial, Can - Snap-In - 3 Lead		Aluminum Electrolytic Capacitors
Capacitance100μFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)1.33 Ohm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency-Impedance1.6 OhmsLead Spacing0.984" Dia (25.00mm)Size / Dimension1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can - Snap-In - 3 Lead	Package	Radial, Can - Snap-In - 3 Lead
Tolerance±2%Voltage - Rated450VESR (Equivalent Series Resistance)1.33 Ohm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency860mA @ 100HzImpedance1.6 OhmsLead Spacing0.394" (10.00mn)Size / Dimension1.260" (32.00mn)Height - Seated (Max)1.260" (32.00mn)Surface Mount Land Size-Hounting TypeRadial, Can - Snap-In - 3 Lead	Series	B43501
Voltage - Rated450VESR (Equivalent Series Resistance)1.33 Ohm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency860mA @ 100HzRipple Current - High Frequency1.6 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Hounting TypeThrough HolePackage / CaseRatial, Can - Snap-In - 3 Lead	Capacitance	100µF
Lease1.33 Ohm @ 100HzESR (Equivalent Series Resistance)1.0000 Hrs @ 85°CLifetime @ Temp.0000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency860mA @ 100HzRipple Current - High Frequency-Impedance1.6 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeFurquencePackage / CaseRadial, Can - Snap-In - 3 Lead	Tolerance	±20%
Lifetime @ Temp.10000 Hrs @ 85°CDeperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency860mA @ 100HzRipple Current - High Frequency-Impedance1.6 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeRadial, Can - Snap-In - 3 Lead	Voltage - Rated	450V
Operating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency860mA @ 100HzRipple Current - High Frequency-Impedance1.6 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Hight - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeFrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	ESR (Equivalent Series Resistance)	1.33 Ohm @ 100Hz
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency860mA @ 100HzRipple Current - High Frequency-Impedance1.6 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Lifetime @ Temp.	10000 Hrs @ 85°C
ApplicationsGeneral PurposeRipple Current - Low Frequency860mA @ 100HzRipple Current - High Frequency-Impedance1.6 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency860mA @ 100HzRipple Current - High Frequency-Impedance1.6 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Polarization	Polar
In a constraint of a constrain	Applications	General Purpose
Impedance1.6 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Ripple Current - Low Frequency	860mA @ 100Hz
Lead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Ripple Current - High Frequency	-
Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Impedance	1.6 Ohms
Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Size / Dimension	0.984" Dia (25.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Height - Seated (Max)	1.260" (32.00mm)
Package / Case Radial, Can - Snap-In - 3 Lead	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors	Package / Case	Radial, Can - Snap-In - 3 Lead
		Report errors?

B43501B5107M82 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B43501B5107M82 Payment Methods





If you have any question about B43501B5107M82, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com