

B43501B5397M60

B43501B5397M60 Information

() H		Aluminum Electrolytic Capacitors ption CAP ALUM 390UF 20% 450V SNAP	
For Re	ference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B43501B5397M60 Specifications

Series B4351 Capacitance 390µF Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) 340 mOhm @ 100Hz Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature 40°C ~ 85°C Polar General Purpose Applications General Purpose Ripple Current - Low Frequency - Impedance 410 mOhms Liag Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Surface Mount Land Size - Mounting Type - Package / Case Kadial, Can - Snap-In		
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43501Capacitance390µFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)340 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeRipple Current - Low Frequency2.31A @ 100HzRipple Current - High Frequency-Impedance1.378° Dia (35.00mm)Lied Spacing3.590° (47.00mm)Size / Dimension1.850° (47.00mm)Height - Seated (Max)1.850° (47.00mm)Surface Mount Land Size-Mounting TypeFinrough HolePackage / CaseRadial, Can - Snap-In	Manufacturer Part Number	B43501B5397M60
Indext PackageAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43501Capacitance390µFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)340 mOhm @ 100HzDieraing Temperature10000 Hrs @ 85°COperating Temperatureeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency2.31A @ 100HzRipple Current - High Frequency.31A @ 100HzSiz / Dimension1.378° Dia (3.500mm)Siz / Dimension1.378° Dia (3.500mm)Height - Seated (Max).850° (4.700mm)Surface Mount Land Size-Mounting TypeFacuage / EasePackage / CaseRadial, Can - Snap-In	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-InSeriesB43501Capacitance390µFTolerance20%Voltage - Rated450VESR (Equivalent Series Resistance)340 mOhm @ 100HzDierang Temperature40°C ~ 85°COperating TemperaturePolarApplicationsGeneral PurposeRipple Current - Low Frequency2.31A @ 100HzRipple Current - High Frequency0.394" (10.0mm)Siz / Dimension1.378" Dia (35.00mm)Siz / Dimension1.378" Dia (35.00mm)Sirdare Mount Land Size-Mounting TypeForugh HolePackage / CaseKaial, Can - Snap-In	Category	Capacitors
Series B4351 Capacitance 390µF Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) 340 mOhm @ 100Hz Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature 40°C ~ 85°C Polar General Purpose Applications General Purpose Ripple Current - Low Frequency - Impedance 410 mOhms Liag Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Surface Mount Land Size - Mounting Type - Package / Case Kadial, Can - Snap-In		Aluminum Electrolytic Capacitors
Capacitance390μFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)340 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance410 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Package	Radial, Can - Snap-In
Tolerance±2%Voltage - Rated450VESR (Equivalent Series Resistance)340 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.31A @ 100HzImpedance410 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Series	B43501
Voltage - Rated450VESR (Equivalent Series Resistance)340 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.31A @ 100HzImpedance410 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeFuncy HolePackage / CaseRatial, Can - Snap-In	Capacitance	390µF
Constraint340 mOhm @ 100HzESR (Equivalent Series Resistance)340 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.31A @ 100HzRipple Current - High Frequency-Impedance410 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeFackage / CaseRestRadial, Can - Snap-In	Tolerance	±20%
Lifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeApple Current - Low Frequency2.31A @ 100HzRipple Current - High Frequency-Impedance410 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeFurough HolePackage / CaseRadial, Can - Snap-In	Voltage - Rated	450V
Operating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.31A @ 100HzRipple Current - High Frequency-Impedance410 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeForugationPackage / CaseRadial, Can - Snap-In	ESR (Equivalent Series Resistance)	340 mOhm @ 100Hz
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.31A @ 100HzRipple Current - High Frequency-Impedance410 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lifetime @ Temp.	10000 Hrs @ 85°C
ApplicationsGeneral PurposeRipple Current - Low Frequency2.31A @ 100HzRipple Current - High Frequency-Impedance410 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency2.31A @ 100HzRipple Current - High Frequency-Impedance410 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Polarization	Polar
In our and programRipple Current - High Frequency-Impedance410 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Applications	General Purpose
Impedance410 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - Low Frequency	2.31A @ 100Hz
IILead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - High Frequency	-
Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Impedance	410 mOhms
Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Size / Dimension	1.378" Dia (35.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Height - Seated (Max)	1.850" (47.00mm)
Package / Case Radial, Can - Snap-In	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors	Package / Case	Radial, Can - Snap-In
		Report errors?

B43501B5397M60 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B43501B5397M60 Payment Methods



If you have any question about B43501B5397M60, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com