

B43501B9107M62

Request a Quote

B43501B9107M62 Information

Heisener.com		B43501B9107M62 EPCOS (TDK) Capacitors Aluminum Electrolytic Capacitors CAP ALUM 100UF 20% 400V SNAP	
	Package	Radial, Can - Snap-In - 3 Lead For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B43501B9107M62 Specifications

ManufacturerEPCOS (TDK)CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-In - 3 LeadSeriesB43501Capacitance100µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)660 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency800mA @ 100HzImpedance1.06 OhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-In - 3 LeadPackageB43501Capacitance100µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)660 mOhm @ 100HzDieraing Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency.Impedance1.06 OhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Manufacturer Part Number	B43501B9107M62
Auminum Electrolytic CapacitorsPackageRadial, Can - Snap-In - 3 LeadSeriesB43501Capacitance100µFtolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)660 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeRipple Current - Low Frequency800mA @ 100HzRipple Current - High Frequency-Impedance0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Package / CaseRadial, Can - Snap-In - 3 Lead	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-In - 3 LeadSeriesB43501Capacitance100µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)660 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency800mA @ 100HzImpedance1.06 OhmsLad Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Category	Capacitors
SeriesB43501Capacitance100µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)660 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency800mA @ 100HzLiad Spacing.0394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max).1850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead		Aluminum Electrolytic Capacitors
Capacitance100µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)660 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency600 Mns @ 100HzImpedance1.06 OhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Package	Radial, Can - Snap-In - 3 Lead
Tolerance ±20% Voltage - Rated 400V ESR (Equivalent Series Resistance) 660 mOhm @ 100Hz Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polar Folar Applications General Purpose Ripple Current - Low Frequency 600 mOhm @ 100Hz Impedance 1.06 Ohms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Surface Mount Land Size - Mounting Type - Package / Case Rial, Can - Snap-In - 3 Lead	Series	B43501
Voltage - Rated400VESR (Equivalent Series Resistance)660 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency800mA @ 100HzLead Spacing1.06 OhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Capacitance	100µF
CGESR (Equivalent Series Resistance)660 mOhm @ 100HzESR (Equivalent Series Resistance)10000 Hrs @ 85°CLifetime @ Temp40°C ~ 85°COperating TemperaturePolarPolarizationGeneral PurposeApplications800mA @ 100HzRipple Current - Low Frequency800mA @ 100HzImpedance1.06 OhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Tolerance	±20%
Lifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency800mA @ 100HzRipple Current - High Frequency-Impedance1.06 OhmsLead Spacing0.394" (10.00mm)Size / Dimension1.850" (47.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeFurough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Voltage - Rated	400V
Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 800mA @ 100Hz Ripple Current - High Frequency - Impedance 1.06 Ohms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 1.850" (47.00mm) Surface Mount Land Size - Mounting Type Fhough Hole Package / Case Radial, Can - Snap-In - 3 Lead	ESR (Equivalent Series Resistance)	660 mOhm @ 100Hz
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency800mA @ 100HzRipple Current - High Frequency-Impedance1.06 OhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Lifetime @ Temp.	10000 Hrs @ 85°C
ApplicationsGeneral PurposeRipple Current - Low Frequency800mA @ 100HzRipple Current - High Frequency-Impedance1.06 OhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency800mA @ 100HzRipple Current - High Frequency-Impedance1.06 OhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Polarization	Polar
In a constraint of the product of t	Applications	General Purpose
Impedance1.06 OhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Ripple Current - Low Frequency	800mA @ 100Hz
Lead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Ripple Current - High Frequency	-
Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Impedance	1.06 Ohms
Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Size / Dimension	1.378" Dia (35.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Height - Seated (Max)	1.850" (47.00mm)
Package / Case Radial, Can - Snap-In - 3 Lead	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors'	Package / Case	Radial, Can - Snap-In - 3 Lead
		Report errors?

B43501B9107M62 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B43501B9107M62 Payment Methods





If you have any question about B43501B9107M62, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com