

# B43501B9277M80

### B43501B9277M80 Information

Heisener.com	 B43501B9277M80 EPCOS (TDK) Capacitors Aluminum Electrolytic Capacitors CAP ALUM 270UF 20% 400V SNAP Radial, Can - Snap-In For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



### B43501B9277M80 Specifications

Manufacturer Part Number B43501B9277M80   Manufacturer EPCOS (TDK)   Category Capacitors   Aluminum Electrolytic Capacitors Aluminum Electrolytic Capacitors   Package Radial, Can - Snap-In   Series B43501   Capacitance 270µF   Tolerance 220%   Voltage - Rated 400V   ESR (Equivalent Series Resistance) 250 mOhm @ 100Hz   Lifetime @ Temp. 10000 Hrs @ 85°C   Operating Temperature 40°C ~ 85°C   Polarization General Purpose   Ripple Current - Low Frequency 1.63A @ 100Hz   Impedance 400 mOhms   Lead Spacing 0.394° (10.00mm)   Size / Dimension 0.948° Dia (25.00mm)   Size / Dimension 1.850° (47.00mm)   Size / Dimension 1.850° (47.00mm)	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43501Capacitance270µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)250 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeRipple Current - Low Frequency1.63A @ 100HzRipple Current - High Frequency-Impedance0.984" Dia (25.00mm)Lied Spacing0.984" Dia (25.00mm)Size / Dinension0.984" Anio (25.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Manufacturer Part Number	B43501B9277M80
IdentifyAluminum Electrolytic CapacitonsPackageRadial, Can - Snap-InSeriesB43501Capacitance270μFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)250 mOhm @100HzOperating Temperature10000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationFolarApplicationsGenera PurposeRipple Current - Low Frequency1.63A @ 100HzRipple Current - High Frequency0.94" (10.00mm)Lead Spacing0.94" (10.00mm)Size / Dimension1.850" (47.00mm)Hight - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Hounting TypeFolapeLane SnapeLanePockage / CaseRatia, Can - SnapeLane	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-InSeriesB43501Capacitance270μFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)250 mOhm @ 100HzOperating Temperature10000 Hrs @ 85°COperating Temperaturee40°C ~ 85°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency1.63A @ 100HzImpedance0.94" (10.0mm)Lead Spacing0.94" (10.0mm)Size / Dimension1.850" (47.0mm)Height - Seated (Max)1.850" (47.0mm)Surface Mount Land Size-Hounting TypeFolapeLane Snap-In	Category	Capacitors
SeriesB43501Capacitance270µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)250 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationFolarApplicationsGeneral PurposeRipple Current - High Frequency-Inpedance400 mOhmsSize / Dimension0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKalial, Can - Snap-In		Aluminum Electrolytic Capacitors
Capacitance270µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)250 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency1.63A @ 100HzInpedance400 mOhnsLad Spacing0.394" (10.00mm)Size / Dimension1.850" (47.00mm)Bright - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeFnough HolePackage / CaseKail, Can - Snap-In	Package	Radial, Can - Snap-In
Tolerance±20%Yoltage - Rated400VESR (Equivalent Series Resistance)250 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.63A @ 100HzImpedance400 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Hounting TypeFnrough HolePackage / CaseRatial, Can - Snap-In	Series	B43501
Voltage - Rated400VESR (Equivalent Series Resistance)250 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency1.63A @ 100HzHippedance400 mOhmsIcad Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Hounting TypeFolaresPackage / CaseRatial, Can - Snap-In	Capacitance	270µF
For ESR (Equivalent Series Resistance)250 mOhm @ 100HzESR (Equivalent Series Resistance)250 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.63A @ 100HzRipple Current - High Frequency-Impedance400 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeFurquencyPackage / CaseRadial, Can - Snap-In	Tolerance	$\pm 20\%$
Lifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.63A @ 100HzRipple Current - High Frequency-Impedance400 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeFackage / CaseRadial, Can - Snap-InRadial, Can - Snap-In	Voltage - Rated	400V
Operating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.63A @ 100HzRipple Current - High Frequency-Impedance400 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	ESR (Equivalent Series Resistance)	250 mOhm @ 100Hz
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.63A @ 100HzRipple Current - High Frequency-Impedance400 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lifetime @ Temp.	10000 Hrs @ 85°C
ApplicationsGeneral PurposeRipple Current - Low Frequency1.63A @ 100HzRipple Current - High Frequency-Impedance400 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Operating Temperature	$-40^{\circ}$ C ~ $85^{\circ}$ C
Ripple Current - Low Frequency1.63A @ 100HzRipple Current - High Frequency-Impedance400 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Polarization	Polar
In a rangeRipple Current - High Frequency-Impedance400 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Applications	General Purpose
Impedance400 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - Low Frequency	1.63A @ 100Hz
IILead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - High Frequency	-
Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Impedance	400 mOhms
Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Size / Dimension	0.984" Dia (25.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Height - Seated (Max)	1.850" (47.00mm)
Package / Case Radial, Can - Snap-In	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors	Package / Case	Radial, Can - Snap-In
		Report errors?

#### B43501B9277M80 Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

### B43501B9277M80 Payment Methods





If you have any question about B43501B9277M80, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com