

# B43501B9397M67

#### B43501B9397M67 Information

Contract terrice contention	 B43501B9397M67 EPCOS (TDK) Capacitors Aluminum Electrolytic Capacitors CAP ALUM 390UF 20% 400V SNAP Radial, Can - Snap-In For the pricing/inventory/lead time, please contact		
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	R	lequest a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



### B43501B9397M67 Specifications

Manufacturer EPCOS (TDK)   Category Capacitors   Aluminum Electrolytic Capacitors Aluminum Electrolytic Capacitors   Package Radial, Can - Snap-In   Series B43501   Capacitance 390µF   Tolerance ±20%   Voltage - Rated 400V   ESR (Equivalent Series Resistance) 170 mOhm @ 100Hz   Lifetime @ Temp. 10000 Hrs @ 85°C   Operating Temperature -40°C ~ 85°C   Polarization General Purpose   Applications General Purpose   Ripple Current - Low Frequency -   Impedance 280 mOhms   Lead Spacing 0.394" (10.00mm)   Size / Dimension 1.181" Dia (30.00mm)   Height - Seated (Max) 1.850" (47.00mm)   Surface Mount Land Size -   Mounting Type Through Hole   Package / Case Radial, Can - Snap-In	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43501Capacitance390µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)170 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance280 mOhmsLied Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Manufacturer Part Number	B43501B9397M67
Aluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43501Capacitance390µFTolerance-20%Voltage - Rated400VESR (Equivalent Series Resistance)170 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeApplications2.13A @ 100HzRipple Current - High Frequency-Linded Spacing380 mOhmsLiad Spacing0.394" (10.00mm)Size / Dimension1.81" Dia (30.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Package / CaseFaculta Case - Inorge HolePackage / CaseRadial, Can - Snap-In	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-InSeriesB43501Capacitance390µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)170 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeRiple Current - Low Frequency-Riple Current - High Frequency-Size / Dimension1.181" Dia (30.00mm)Size / Dimension1.850" (47.00mm)Height - Seated (Max).850" (47.00mm)Surface Mount Land Size-Package / CaseRadial, Can - Snap-In	Category	Capacitors
SeriesB43501Capacitance390µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)170 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency2.13A @ 100HzLied Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKadial, Can - Snap-In		Aluminum Electrolytic Capacitors
Capacitance390µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)170 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.13A @ 100HzLingedance280 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Package	Radial, Can - Snap-In
±2%   Yoltage - Rated 400V   ESR (Equivalent Series Resistance) 170 mOhm @ 100Hz   Lifetime @ Temp. 10000 Hrs @ 85°C   Operating Temperature -40°C ~ 85°C   Polar Folar   Applications General Purpose   Ripple Current - Low Frequency 2.13A @ 100Hz   Impedance 280 mOhms   Lead Spacing 0.394" (10.00mm)   Size / Dimension 1.181" Dia (30.00mm)   Height - Seated (Max) 1.850" (47.00mm)   Surface Mount Land Size -   Mounting Type Through Hole   Package / Case Radial, Can - Snap-In	Series	B43501
Voltage - Rated400VESR (Equivalent Series Resistance)170 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.13A @ 100HzImpedance280 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeFacial Can - Snap-In	Capacitance	390µF
ESR 170 mOhm @ 100Hz   ESR (Equivalent Series Resistance) 10000 Hrs @ 85°C   Lifetime @ Temp. 40°C ~ 85°C   Operating Temperature Polar   Polarization General Purpose   Applications General Purpose   Ripple Current - Low Frequency 2.13A @ 100Hz   Impedance 280 mOhms   Lead Spacing 0.394" (10.00mm)   Size / Dimension 1.181" Dia (30.00mm)   Height - Seated (Max) 1.850" (47.00mm)   Surface Mount Land Size -   Mounting Type Through Hole   Package / Case Raial, Can - Snap-In	Tolerance	±20%
Lifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.13A @ 100HzRipple Current - High Frequency-Impedance280 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeFurough HolePackage / CaseRadial, Can - Snap-In	Voltage - Rated	400V
Operating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.13A @ 100HzRipple Current - High Frequency-Impedance280 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	ESR (Equivalent Series Resistance)	170 mOhm @ 100Hz
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.13A @ 100HzRipple Current - High Frequency-Impedance280 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lifetime @ Temp.	10000 Hrs @ 85°C
ApplicationsGeneral PurposeRipple Current - Low Frequency2.13A @ 100HzRipple Current - High Frequency-Impedance280 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency2.13A @ 100HzRipple Current - High Frequency-Impedance280 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Polarization	Polar
In a constraint of the product of t	Applications	General Purpose
Impedance280 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - Low Frequency	2.13A @ 100Hz
IILead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - High Frequency	-
Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Impedance	280 mOhms
Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Size / Dimension	1.181" Dia (30.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Height - Seated (Max)	1.850" (47.00mm)
Package / Case Radial, Can - Snap-In	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors <sup>4</sup>	Package / Case	Radial, Can - Snap-In
		Report errors?

#### B43501B9397M67 Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE ELARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

# B43501B9397M67 Payment Methods





If you have any question about B43501B9397M67, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com