

B43501B9477M87

B43501B9477M87 Information

	Heisener.com	Part Number Manufacturer Category Description Package	B43501B9477M87 EPCOS (TDK) Capacitors Aluminum Electrolytic Capacitors CAP ALUM 470UF 20% 400V SNAP Radial, Can - Snap-In For the pricing/inventory/lead time, please contact	
	For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B43501B9477M87 Specifications

Anufacturer EPCOS (TDK) Category Capacitors Atuminum Electrolytic Capacitors Atuminum Electrolytic Capacitors Package Radial, Can - Snap-In Series B43501 Capacitance 470µF Tolerance ±20% Voltage - Rated 400V ESR (Equivalent Series Resistance) 140 mOhm @ 100Hz Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization General Purpose Riple Current - Low Frequency 244A @ 100Hz Rippe Current - High Frequency - Impedance 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Size / Dimension 2.047" (52.00mm) Size / Dimension - Mounting Type Through Hole		
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43501Capacitance470µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)140 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.44A @ 100HzLifetime @ Japacitance30 mOhmsImpedance230 mOhmsSize / Dimension1.378" Dia (35.00mm)Size / Dimension1.378" Dia (35.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Manufacturer Part Number	B43501B9477M87
Aluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43501Capacitance470µF±20%400VVoltage - Rated400 vESR (Equivalent Series Resistance)140 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeRipple Current - Low Frequency2.44A @ 100HzRipple Current - High Frequency-Size / Dimension1.378" Dia (35.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Package / CaseRadial, Can - Snap-In	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-InSeriesB43501Capacitance470µFTolerance±20%Voltage - Rated00VESR (Equivalent Series Resistance)140 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeRipple Current - Low Frequency2.44A @ 100HzRipple Current - High Frequency-Size / Dimension1.378" Dia (35.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Package / CaseRadial, Can - Snap-In	Category	Capacitors
SeriesB43501Capacitance470µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)140 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.44A @ 100HzLifedance230 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Package / CaseRadial, Can - Snap-In		Aluminum Electrolytic Capacitors
470µF Tolerance 470µF 20% 400V Voltage - Rated 400V ESR (Equivalent Series Resistance) 140 mOhm @ 100Hz Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 2.44A @ 100Hz Lifedance 230 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 2.047" (52.00mm) Surface Mount Land Size - Package / Case Radial, Can - Snap-In	Package	Radial, Can - Snap-In
Polerance±0%Voltage - Rated400VESR (Equivalent Series Resistance)140 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.44A @ 100HzRipple Current - High Frequency-Impedance230 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Size / Dimension2.047" (52.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Package / CaseRatial, Can - Snap-In	Series	B43501
Voltage - Rated400VESR (Equivalent Series Resistance)140 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.44A @ 100HzRipple Current - High Frequency-Impedance230 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Package / CaseRatial, Can - Snap-In	Capacitance	470µF
ESR (Equivalent Series Resistance)140 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.44A @ 100HzRipple Current - High Frequency-Impedance230 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Package / CaseRadial, Can - Snap-In	Tolerance	±20%
Lifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.44A @ 100HzRipple Current - High Frequency-Impedance230 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Voltage - Rated	400V
Operating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.44A @ 100HzRipple Current - High Frequency-Impedance230 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	ESR (Equivalent Series Resistance)	140 mOhm @ 100Hz
PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.44A @ 100HzRipple Current - High Frequency-Impedance230 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lifetime @ Temp.	10000 Hrs @ 85°C
ApplicationsGeneral PurposeRipple Current - Low Frequency2.44A @ 100HzRipple Current - High Frequency-Impedance230 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency2.44A @ 100HzRipple Current - High Frequency-Impedance230 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Polarization	Polar
In Provide ApplyIntervention of the provide ApplyRipple Current - High Frequency-Impedance230 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Applications	General Purpose
Impedance230 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - Low Frequency	2.44A @ 100Hz
IOutputLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - High Frequency	-
Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Impedance	230 mOhms
Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Size / Dimension	1.378" Dia (35.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Height - Seated (Max)	2.047" (52.00mm)
Package / Case Radial, Can - Snap-In	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can - Snap-In
		Report errors?

B43501B9477M87 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B43501B9477M87 Payment Methods



If you have any question about B43501B9477M87, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com