

B43501B9567M60

B43501B9567M60 Information

| Contract service stants terr | B43501B9567M60 EPCOS (TDK) Capacitors Aluminum Electrolytic Capacitors CAP ALUM 560UF 20% 400V SNAP Radial, Can - Snap-In For the pricing/inventory/lead time, please contact | |
|------------------------------|---|-----------------|
| For Reference Only | us Website: https://www.heisener.com E-mail: salesdept@heisener.com | Request a Quote |

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B43501B9567M60 Specifications

| Manufacturer Part Number B43501B9567M60 Manufacturer EPCOS (TDK) Category Capacitors Aluminum Electrolytic Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Snap-In Series B43501 Capacitance 560µF Tolerance 560µF Voltage - Rated 400V SSR (Equivalent Series Resistance) 10000 Hrs @ 85°C Operating Temperature 40°C ~ 85°C Operating Temperature Series 100000 Hrs @ 85°C Applications General Purpose Ripple Current - Low Frequency 282A @ 100Hz Ippedance 190 mOhms Lead Spacing 0.394° (10.00mm) Size / Dimension 1.378° Dia (35.00mm) Size / Dimension 1.378° Dia (35.00mm) Size / Dimension 1.50° (47.00mm) Height - Seated (Max) 5.50° (47.00mm) Size / Dimension 1.50° (47.00mm) Size / Dimension 1.50° (47.00mm) Mounting Type - Mounting Type Radial, Can - Snap-In < | - | |
|--|------------------------------------|----------------------------------|
| CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43501Capacitance560µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)120 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeRipple Current - Low Frequency2.82A @ 100HzRipple Current - High Frequency-Impedance190 mOhmsLiad Spacing0.394" (10.00mm)Size / Dinension1.378" Dia (35.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeFhrough HolePackage / CaseRadial, Can - Snap-In | Manufacturer Part Number | B43501B9567M60 |
| IdentifyAluninum Electrolytic CapacitonsPackageRadial, Can - Snap-InSeriesB43501Capacitance560µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)120 mOhm @ 100HzDieraing Temperature00000 Hrs @ 85°COperating Temperature00000 Hrs @ 85°CPolarizationFolarApplicationsGenera PurposeRipple Current - Low Frequency0.82A @ 100HzRipple Current - High Frequency0.394" (10.00mm)Lead Spacing1.378" bia (35.00mm)Size / Dimension1.850" (47.00mm)Hight - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Hounting TypeFolape Land StatePockage / CaseRadia, Can - Snap-In | Manufacturer | EPCOS (TDK) |
| PackageRadial, Can - Snap-InSeriesB43501Capacitance560μFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)120 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationGeneral PurposeRipple Current - Low Frequency2.82A @ 100HzImpedance1.378" Dia (35.00mm)Lied Spacing1.378" Dia (35.00mm)Size / Dimension1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In | Category | Capacitors |
| SeriesB43501Capacitance560µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)120 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationFolarApplicationsGeneral PurposeRipple Current - High Frequency2.82A @ 100HzInpedance1.90 mOhmsSize / Dimension1.378° Dia (35.00mm)Size / Dimension1.850° (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKaila (Can - Snap-In | | Aluminum Electrolytic Capacitors |
| Capacitance560µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)120 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - High Frequency-Ingedance190 mOhmsLad Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Sirafe Mount Land Size-Mounting Type-Pokage / CaseMoute Asong-In | Package | Radial, Can - Snap-In |
| Yolrance±0%Voltage - Rated400VESR (Equivalent Series Resistance)120 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.82A @ 100HzRipple Current - High Frequency0.394" (10.00mm)Lead Spacing0.394" (10.00mm)Size / Dimension1.850" (47.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeRatial, Can - Snap-In | Series | B43501 |
| Voltage - Rated400VESR (Equivalent Series Resistance)120 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.82A @ 100HzMipedance190 mOhmsInpedance0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeFough HolePackage / CaseRational Can - Snap-In | Capacitance | 560µF |
| For a constraint of a constrai | Tolerance | ±20% |
| Lifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.82A @ 100HzRipple Current - High Frequency-Impedance190 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeRadial, Can - Snap-In | Voltage - Rated | 400V |
| Operating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.82A @ 100HzRipple Current - High Frequency-Impedance190 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In | ESR (Equivalent Series Resistance) | 120 mOhm @ 100Hz |
| PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.82A @ 100HzRipple Current - High Frequency-Impedance190 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In | Lifetime @ Temp. | 10000 Hrs @ 85°C |
| ApplicationsGeneral PurposeRipple Current - Low Frequency2.82A @ 100HzRipple Current - High Frequency-Impedance190 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In | Operating Temperature | -40°C ~ 85°C |
| Ripple Current - Low Frequency2.82A @ 100HzRipple Current - High Frequency-Impedance190 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In | Polarization | Polar |
| In a constraint of a constrain | Applications | General Purpose |
| Impedance190 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In | Ripple Current - Low Frequency | 2.82A @ 100Hz |
| Lead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In | Ripple Current - High Frequency | - |
| Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In | Impedance | 190 mOhms |
| Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In | Lead Spacing | 0.394" (10.00mm) |
| Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In | Size / Dimension | 1.378" Dia (35.00mm) |
| Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In | Height - Seated (Max) | 1.850" (47.00mm) |
| Package / Case Radial, Can - Snap-In | Surface Mount Land Size | - |
| | Mounting Type | Through Hole |
| Report errors | Package / Case | Radial, Can - Snap-In |
| 1 | | Report errors? |

B43501B9567M60 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.


SERVICE ELARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B43501B9567M60 Payment Methods





E-mail: salesdept@heisener.com