



### B43501C2337M62 Information

Heisener.com

Part Number B43501C2337M62
Manufacturer EPCOS (TDK)
Category Capacitors

Aluminum Electrolytic Capacitors

**Description** CAP ALUM 330UF 20% 250V SNAP

Package Radial, Can - Snap-In - 3 Lead

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **B43501C2337M62 Specifications**

Manufacturer Part Number       B43501C2337M62         Manufacturer       EPCOS (TDK)         Category       Capacitors         Aluminum Electrolytic Capacitors         Package       Radial, Can - Snap-In - 3 Lead         Series       B43501         Capacitance       330µF         Tolerance       ±20%         Voltage - Rated       250V         ESR (Equivalent Series Resistance)       300 mOhm @ 100Hz         Lifetime @ Temp.       10000 Hrs @ 85°C         Operating Temperature       -40°C ~ 85°C         Polar       Polar         Applications       General Purpose         Ripple Current - Low Frequency       1.51A @ 100Hz         Ripple Current - High Frequency       -         Impedance       390 mOhms         Lead Spacing       0.394" (10.00mm)         Size / Dimension       0.866" Dia (22.00mm)         Height - Seated (Max)       1.457" (37.00mm)         Surface Mount Land Size       Through Hole         Package (Case       Package (Case	1	
Category         Capacitors           Package         Radial, Can - Snap-In - 3 Lead           Series         B43501           Capacitance         330µF           Tolerance         ±20%           Voltage - Rated         250V           ESR (Equivalent Series Resistance)         300 mOhm @ 100Hz           Lifetime @ Temp.         10000 Hrs @ 85°C           Operating Temperature         -40°C ~ 85°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         1.51A @ 100Hz           Ripple Current - High Frequency         -           Impedance         390 mOhms           Lead Spacing         0.394" (10.00mm)           Size / Dimension         0.866" Dia (22.00mm)           Height - Seated (Max)         1.457" (37.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole	Manufacturer Part Number	B43501C2337M62
PackageAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-In - 3 LeadSeriesB43501Capacitance330µFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)300 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.51A @ 100HzRipple Current - High Frequency-Impedance390 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-In - 3 LeadSeriesB43501Capacitance330µFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)300 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.51A @ 100HzRipple Current - High Frequency-Impedance390 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Category	Capacitors
Series         B43501           Capacitance         330µF           Tolerance         ±20%           Voltage - Rated         250V           ESR (Equivalent Series Resistance)         300 mOhm @ 100Hz           Lifetime @ Temp.         10000 Hrs @ 85°C           Operating Temperature         -40°C ~ 85°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         1.51A @ 100Hz           Ripple Current - High Frequency         -           Impedance         390 mOhms           Lead Spacing         0.394" (10.00mm)           Size / Dimension         0.866" Dia (22.00mm)           Height - Seated (Max)         1.457" (37.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole		Aluminum Electrolytic Capacitors
Capacitance330μFTolerance±20%Voltage - Rated250 VESR (Equivalent Series Resistance)300 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.51A @ 100HzRipple Current - High Frequency-Impedance390 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Package	Radial, Can - Snap-In - 3 Lead
Tolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)300 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.51A @ 100HzRipple Current - High Frequency-Impedance390 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Series	B43501
Voltage - Rated250VESR (Equivalent Series Resistance)300 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.51A @ 100HzRipple Current - High Frequency-Impedance390 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Capacitance	330μF
ESR (Equivalent Series Resistance)  Lifetime @ Temp.  10000 Hrs @ 85°C  Operating Temperature  -40°C ~ 85°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  1.51A @ 100Hz  Ripple Current - High Frequency  - Impedance  390 mOhms  Lead Spacing  0.394" (10.00mm)  Size / Dimension  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  300 mOhm @ 100Hz  -40°C ~ 85°C  -00ar  -40°C ~ 85°C  -00ar  -40°C ~ 85°C  -00ar  -40°C ~ 85°C  -00ar  -40°C ~ 85°C  -40°C	Tolerance	±20%
Lifetime @ Temp.  Operating Temperature  -40°C ~ 85°C  Polarization  Polar  Applications  General Purpose  Ripple Current - Low Frequency  1.51A @ 100Hz  Ripple Current - High Frequency  Impedance  390 mOhms  Lead Spacing  0.394" (10.00mm)  Size / Dimension  Height - Seated (Max)  1.457" (37.00mm)  Surface Mount Land Size  Mounting Type  10000 Hrs @ 85°C  -40°C ~ 80°C  -40°C ~	Voltage - Rated	250V
Operating Temperature  -40°C ~ 85°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  1.51A @ 100Hz  Ripple Current - High Frequency  Impedance  390 mOhms  Lead Spacing  0.394" (10.00mm)  Size / Dimension  0.866" Dia (22.00mm)  Height - Seated (Max)  1.457" (37.00mm)  Surface Mount Land Size  Mounting Type  Through Hole	ESR (Equivalent Series Resistance)	300 mOhm @ 100Hz
Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 1.51A @ 100Hz  Ripple Current - High Frequency -  Impedance 390 mOhms  Lead Spacing 0.394" (10.00mm)  Size / Dimension 0.866" Dia (22.00mm)  Height - Seated (Max) 1.457" (37.00mm)  Surface Mount Land Size -  Mounting Type Through Hole	Lifetime @ Temp.	10000 Hrs @ 85°C
Applications  General Purpose  Ripple Current - Low Frequency  Ripple Current - High Frequency  Impedance  390 mOhms  Lead Spacing  0.394" (10.00mm)  Size / Dimension  0.866" Dia (22.00mm)  Height - Seated (Max)  1.457" (37.00mm)  Surface Mount Land Size  Mounting Type  Through Hole	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency  Ripple Current - High Frequency  Impedance  Size / Dimension  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  1.51A @ 100Hz	Polarization	Polar
Ripple Current - High Frequency Impedance 390 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 0.866" Dia (22.00mm) Height - Seated (Max) 1.457" (37.00mm) Surface Mount Land Size - Mounting Type Through Hole	Applications	General Purpose
Impedance390 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Ripple Current - Low Frequency	1.51A @ 100Hz
Lead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Ripple Current - High Frequency	-
Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Impedance	390 mOhms
Height - Seated (Max)  Surface Mount Land Size  Mounting Type  1.457" (37.00mm)  - Through Hole	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size - Mounting Type Through Hole	Size / Dimension	0.866" Dia (22.00mm)
Mounting Type Through Hole	Height - Seated (Max)	1.457" (37.00mm)
	Surface Mount Land Size	-
Package / Case  Radial Can - Span In - 3 Lead	Mounting Type	Through Hole
rackage / Case Ratial, Call - Shap-in - 3 Leau	Package / Case	Radial, Can - Snap-In - 3 Lead
Report errors?		Report errors?

#### **B43501C2337M62 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **B43501C2337M62 Payment Methods**



















### B43501C2337M62 Shipping Methods













If you have any question about B43501C2337M62, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com