



B43501C5277M62 Information

Heisener.com

Part Number B43501C5277M62
Manufacturer EPCOS (TDK)
Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 270UF 20% 450V SNAP

Package Radial, Can - Snap-In - 3 Lead

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









B43501C5277M62 Specifications

Manufacturer Part Number B43501C5277M62 Manufacturer EPCOS (TDK) Category Capacitors Package Radial, Can - Snap-In - 3 Lead Scries B43501 Capacitance 270µF Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) 490 mOhm @ 100Hz Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.7A @ 100Hz Ripple Current - High Frequency - Impedance 590 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.654" (42.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead	4	
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Snap-In - 3 Lead Series B43501 Capacitance 270µF Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) 490 mOhm @ 100Hz Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications Ripple Current - Low Frequency Ripple Current - High Frequency Impedance 1039 mOhms Lead Spacing 590 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead	Manufacturer Part Number	B43501C5277M62
Package Radial, Can - Snap-In - 3 Lead Series B43501 Capacitance 270µF Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) 490 mOhm @ 100Hz Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.7A @ 100Hz Ripple Current - High Frequency - Impedance 590 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.654" (42.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-In - 3 LeadSeriesB43501Capacitance270μFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)490 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.7A @ 100HzRipple Current - High Frequency-Impedance590 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Category	Capacitors
Series B43501 Capacitance 270μF Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) 490 mOhm @ 100Hz Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.7A @ 100Hz Ripple Current - High Frequency - Impedance 590 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.654" (42.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead		Aluminum Electrolytic Capacitors
Capacitance 270μF Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) 490 mOhm @ 100Hz Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.7A @ 100Hz Ripple Current - High Frequency - Impedance 590 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.654" (42.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead	Package	Radial, Can - Snap-In - 3 Lead
Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) 490 mOhm @ 100Hz Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.7A @ 100Hz Ripple Current - High Frequency - Impedance 590 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.654" (42.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead	Series	B43501
Voltage - Rated450 VESR (Equivalent Series Resistance)490 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.7A @ 100HzRipple Current - High Frequency-Impedance590 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Capacitance	270μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency 1.7A @ 100Hz Ripple Current - High Frequency Impedance 590 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.654" (42.00mm) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead	Tolerance	±20%
Lifetime @ Temp. Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.7A @ 100Hz Ripple Current - High Frequency - Impedance 590 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead	Voltage - Rated	450V
Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency - Impedance S90 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.654" (42.00mm) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead	ESR (Equivalent Series Resistance)	490 mOhm @ 100Hz
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.7A @ 100Hz Ripple Current - High Frequency - Impedance 590 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.654" (42.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead	Lifetime @ Temp.	10000 Hrs @ 85°C
Applications General Purpose Ripple Current - Low Frequency 1.7A @ 100Hz Ripple Current - High Frequency - Impedance 590 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.654" (42.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency Ripple Current - High Frequency Impedance S90 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.654" (42.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead	Polarization	Polar
Ripple Current - High Frequency Impedance 590 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.654" (42.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead	Applications	General Purpose
Impedance590 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Ripple Current - Low Frequency	1.7A @ 100Hz
Lead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Ripple Current - High Frequency	-
Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.654" (42.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead	Impedance	590 mOhms
Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead	Size / Dimension	1.181" Dia (30.00mm)
Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead	Height - Seated (Max)	1.654" (42.00mm)
Package / Case Radial, Can - Snap-In - 3 Lead	Surface Mount Land Size	-
-	Mounting Type	Through Hole
	Package / Case	Radial, Can - Snap-In - 3 Lead
Report errors?		Report errors?

B43501C5277M62 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

B43501C5277M62 Payment Methods





















B43501C5277M62 Shipping Methods













If you have any question about B43501C5277M62, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com