

B43501E0107M007

B43501E0107M007 Information

Heisener.com	 B43501E0107M007 EPCOS (TDK) Capacitors Aluminum Electrolytic Capacitors CAP ALUM 100UF 20% 420V SNAP Radial, Can - Snap-In For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B43501E0107M007 Specifications

Manufacturer EPCOS (TDK) Category Capacitors Aluminum Electrolytic Capacitors Radial, Can - Snap-In Package Radial, Can - Snap-In Series B43501 Capacitance 100µF Tolerance ±20% Voltage - Rated 420V ESR (Equivalent Series Resistance) 1.33 Ohm @ 100Hz Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Impedance 1.6 Ohms Lead Spacing 0.394" (10.00mm) Size / Dimension 0.984" Dia (25.00mm) Height - Seated (Max) 1.063" (27.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Kadial, Can - Snap-In	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43501Capacitance100µFTolerance±20%Voltage - Rated420VESR (Equivalent Series Resistance)1.33 Ohm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeRipple Current - Low Frequency800mA @ 100HzRipple Current - High Frequency-Impedance1.6 OhmsLied Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Manufacturer Part Number	B43501E0107M007
Aluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43501Capacitance100µFTolerance±20%Voltage - Rated420VESR (Equivalent Series Resistance)1.33 Ohm @ 100HzLifetime @ Temp.00000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationGeneral PurposeRipple Current - Low Frequency800mA @ 100HzRipple Current - High Frequency-Ingedance0.394" (10.0mm)Siz / Dimension0.984" Dia (25.00mm)Siz / Dimension0.984" Dia (25.00mm)Sirface Mount Land Size-Mounting Type-Package / CaseKadial, Can - Snap-In	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-InSeriesB43501Capacitance100µFTolerance±20%Voltage - Rated420VESR (Equivalent Series Resistance)1.33 Ohm @ 100HzLifetime @ Temp.00000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency800mA @ 100HzLifetime @ Temp.0.334" (10.00mm)Size / Dimension0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Size / Dimension-Surface Mount Land Size-Package / CaseThrough HolePackage / CaseRadial, Can - Snap-In	Category	Capacitors
SeriesB43501Capacitance100µFTolerance±20%Voltage - Rated420VESR (Equivalent Series Resistance)1.33 Ohm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency800mA @ 100HzLied Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKadial, Can - Snap-In		Aluminum Electrolytic Capacitors
Capacitance100µFTolerance±20%Voltage - Rated420VESR (Equivalent Series Resistance)1.33 Ohm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency800mA @ 100HzRipple Current - High Frequency-Size / Dimension0.944" (10.00mm)Size / Dimension0.948" Dia (25.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Package	Radial, Can - Snap-In
Tolerance±20%Voltage - Rated420VESR (Equivalent Series Resistance)1.33 Ohm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency800mA @ 100HzImpedance1.6 OhmsLead Spacing0.984" Dia (25.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Package / CaseRadial, Can - Snap-In	Series	B43501
Voltage - Rated420VESR (Equivalent Series Resistance)1.33 Ohm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency800mA @ 100HzImpedance1.6 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeRadial, Can - Snap-In	Capacitance	100µF
Composition1.33 Ohm @ 100HzESR (Equivalent Series Resistance)1.0000 Hrs @ 85°CLifetime @ Temp40°C ~ 85°COperating TemperaturePolarPolarizationGeneral PurposeApplications60mA @ 100HzRipple Current - Low Frequency800mA @ 100HzImpedance1.6 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Tolerance	±20%
Lifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency800mA @ 100HzRipple Current - High Frequency-Impedance1.6 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeFhrough HolePackage / CaseRadial, Can - Snap-In	Voltage - Rated	420V
Operating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency800mA @ 100HzRipple Current - High Frequency-Impedance1.6 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeFriough HolePackage / CaseRadial, Can - Snap-In	ESR (Equivalent Series Resistance)	1.33 Ohm @ 100Hz
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency800mA @ 100HzRipple Current - High Frequency-Impedance1.6 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lifetime @ Temp.	10000 Hrs @ 85°C
ApplicationsGeneral PurposeRipple Current - Low Frequency800mA @ 100HzRipple Current - High Frequency-Impedance1.6 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Operating Temperature	$-40^{\circ}\mathrm{C} \sim 85^{\circ}\mathrm{C}$
Ripple Current - Low Frequency800mA @ 100HzRipple Current - High Frequency-Impedance1.6 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Polarization	Polar
In a randomRipple Current - High Frequency-Impedance1.6 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Applications	General Purpose
Impedance1.6 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - Low Frequency	800mA @ 100Hz
Lead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - High Frequency	-
Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Impedance	1.6 Ohms
Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Size / Dimension	0.984" Dia (25.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Height - Seated (Max)	1.063" (27.00mm)
Package / Case Radial, Can - Snap-In	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can - Snap-In
		Report errors?

B43501E0107M007 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE ELARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B43501E0107M007 Payment Methods





If you have any question about B43501E0107M007, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com