

# B43501E2108M87

#### B43501E2108M87 Information

Heisener.com	 B43501E2108M87 EPCOS (TDK) Capacitors Aluminum Electrolytic Capacitors CAP ALUM 1000UF 20% 200V SNAP Radial, Can - Snap-In For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



### B43501E2108M87 Specifications

Manufacturer Part NumberB43501E2108M87ManufacturerEPCOS (TDK)CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43501Capacitance1000µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)100 mOhm @ 100HzLifetime @ Temp.40°C ~ 85°COperating Temperature-40°C ~ 85°CPolarizationSonal PurposeApplicationsGeneral PurposeRipple Current - High Frequency-Impedance130 mOhmsLead Spacing0.394" (10.00mm)
CategoryCapacitorsCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43501Capacitance1000µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)100 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency3.08A @ 100HzImpedance130 mOhms
Auminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43501Capacitance1000µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)100 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency3.08A @ 100HzImpedance130 mOhms
PackageRadial, Can - Snap-InSeriesB43501Capacitance1000µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)100 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - High Frequency3.08A @ 100HzImpedance130 mOhms
SeriesB43501Capacitance1000µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)100 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.08A @ 100HzRipple Current - High Frequency130 mOhms
Capacitance1000μFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)100 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.08A @ 100HzRipple Current - High Frequency-Impedance130 mOhms
Tolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)100 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.08A @ 100HzRipple Current - High Frequency-Impedance130 mOhms
Voltage - Rated200VESR (Equivalent Series Resistance)100 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency3.08A @ 100HzImpedance130 mOhms
ESR (Equivalent Series Resistance)100 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.08A @ 100HzRipple Current - High Frequency-Impedance130 mOhms
Lifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.08A @ 100HzRipple Current - High Frequency-Impedance130 mOhms
Operating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.08A @ 100HzRipple Current - High Frequency-Impedance130 mOhms
PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.08A @ 100HzRipple Current - High Frequency-Impedance130 mOhms
ApplicationsGeneral PurposeRipple Current - Low Frequency3.08A @ 100HzRipple Current - High Frequency-Impedance130 mOhms
Ripple Current - Low Frequency3.08A @ 100HzRipple Current - High Frequency-Impedance130 mOhms
Ripple Current - High Frequency -   Impedance 130 mOhms
Impedance 130 mOhms
Lead Spacing 0.394" (10.00mm)
Size / Dimension 0.984" Dia (25.00mm)
Height - Seated (Max) 2.047" (52.00mm)
Surface Mount Land Size -
Mounting Type Through Hole
Package / Case Radial, Can - Snap-In
Report error

#### B43501E2108M87 Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE BUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### B43501E2108M87 Payment Methods



If you have any question about B43501E2108M87, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com