



B43504A2188M7 Information

Ma Ca Heisener.com

Part Number B43504A2188M7
Manufacturer EPCOS (TDK)
Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 1800UF 20% 250V SNAP

Package Radial, Can - Snap-In

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









B43504A2188M7 Specifications

Manufacturer Part Number B43504A2188M7 Manufacturer EPCOS (TDK) Category Capacitors Package Radial, Can - Snap-In Series B43504 Capacitance 1800µF Tolerance ±20% Voltage - Rated 250V ESR (Equivalent Series Resistance) 80 mOhm @ 100Hz Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 4.16A @ 100Hz Ripple Current - High Frequency - Impedance 100 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 2.244" (57.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In		
Category Capacitors Package Radial, Can - Snap-In Series B43504 Capacitance 1800µF Tolerance ±20% Voltage - Rated 250V ESR (Equivalent Series Resistance) 80 mOhm @ 100Hz Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 4.16A @ 100Hz Ripple Current - High Frequency - Impedance 100 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 2.244" (57.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Manufacturer Part Number	B43504A2188M7
Package Radial, Can - Snap-In Series B43504 Capacitance 1800μF Tolerance ±20% Voltage - Rated 250V ESR (Equivalent Series Resistance) 80 mOhm @ 100Hz Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 4.16A @ 100Hz Ripple Current - High Frequency - Impedance 100 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 2.244" (57.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Manufacturer	EPCOS (TDK)
Package Radial, Can - Snap-In Series B43504 Capacitance 1800µF Tolerance ±20% Voltage - Rated 250V ESR (Equivalent Series Resistance) 80 mOhm @ 100Hz Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 4.16A @ 100Hz Ripple Current - High Frequency - Impedance 100 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 2.244" (57.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Category	Capacitors
Series B43504 Capacitance 1800μF Tolerance ±20% Voltage - Rated 250V ESR (Equivalent Series Resistance) 80 mOhm @ 100Hz Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 4.16A @ 100Hz Ripple Current - High Frequency - Impedance 100 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 2.244" (57.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In		Aluminum Electrolytic Capacitors
Capacitance 1800μF Tolerance ±20% Voltage - Rated 250V ESR (Equivalent Series Resistance) 80 mOhm @ 100Hz Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 4.16A @ 100Hz Ripple Current - High Frequency - Impedance 100 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 2.244" (57.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Package	Radial, Can - Snap-In
Tolerance ±20% Voltage - Rated 250V ESR (Equivalent Series Resistance) 80 mOhm @ 100Hz Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 4.16A @ 100Hz Ripple Current - High Frequency - Impedance 100 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Bight - Seated (Max) 2.244" (57.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Series	B43504
Voltage - Rated250VESR (Equivalent Series Resistance)80 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency4.16A @ 100HzRipple Current - High Frequency-Impedance100 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.244" (57.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Capacitance	1800μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. Operating Temperature -40°C ~ 105°C Polarization Applications General Purpose Ripple Current - Low Frequency A16A @ 100Hz Ripple Current - High Frequency Impedance Lead Spacing 100 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 2.244" (57.00mm) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Tolerance	±20%
Lifetime @ Temp. Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 4.16A @ 100Hz Ripple Current - High Frequency - Impedance 100 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 2.244" (57.00mm) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Voltage - Rated	250V
Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 4.16A @ 100Hz Ripple Current - High Frequency - Impedance 100 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 2.244" (57.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	ESR (Equivalent Series Resistance)	80 mOhm @ 100Hz
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 4.16A @ 100Hz Ripple Current - High Frequency - Impedance 100 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 2.244" (57.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Lifetime @ Temp.	3000 Hrs @ 105°C
Applications General Purpose Ripple Current - Low Frequency 4.16A @ 100Hz Ripple Current - High Frequency - Impedance 100 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 2.244" (57.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Operating Temperature	-40°C ~ 105°C
Ripple Current - Low Frequency 4.16A @ 100Hz Ripple Current - High Frequency - Impedance 100 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 2.244" (57.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Polarization	Polar
Ripple Current - High Frequency Impedance Inpedance Inpe	Applications	General Purpose
Impedance100 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.244" (57.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - Low Frequency	4.16A @ 100Hz
Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 2.244" (57.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Ripple Current - High Frequency	-
Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 2.244" (57.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Impedance	100 mOhms
Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Size / Dimension	1.378" Dia (35.00mm)
Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Height - Seated (Max)	2.244" (57.00mm)
Package / Case Radial, Can - Snap-In	Surface Mount Land Size	-
	Mounting Type	Through Hole
	Package / Case	Radial, Can - Snap-In
Report errors?		Report errors?

B43504A2188M7 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

B43504A2188M7 Payment Methods





















B43504A2188M7 Shipping Methods













If you have any question about B43504A2188M7, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com