



B43504A2277M82 Information

Manufacturer EPCOS (TDK) Category Heisener.com

Aluminum Electrolytic Capacitors Description CAP ALUM 270UF 20% 250V SNAP

Radial, Can - Snap-In - 3 Lead **Package**

Capacitors

For the pricing/inventory/lead time, please contact

Part Number B43504A2277M82

Website: https://www.heisener.com For Reference Only E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









B43504A2277M82 Specifications

Manufacturer Part NumberB43504A2277M82ManufacturerEPCOS (TDK)CategoryCapacitorsPackageRadial, Can - Snap-In - 3 LeadSeriesB43504Capacitance270μFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)480 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.1A @ 100HzRipple Current - High Frequency-
CategoryCapacitorsPackageRadial, Can - Snap-In - 3 LeadSeriesB43504Capacitance $270\mu F$ Tolerance $\pm 20\%$ Voltage - Rated $250V$ ESR (Equivalent Series Resistance) $480 \text{ mOhm } @ 100\text{Hz}$ Lifetime @ Temp. $3000 \text{ Hrs } @ 105^{\circ}\text{C}$ Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$ PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency $1.14 @ 100\text{Hz}$
Aluminum Electrolytic Capacitors Package Radial, Can - Snap-In - 3 Lead Series B43504 Capacitance 270μF Tolerance ±20% Voltage - Rated 250V ESR (Equivalent Series Resistance) 480 mOhm @ 100Hz Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Applications Ripple Current - Low Frequency 1.1A @ 100Hz
PackageRadial, Can - Snap-In - 3 LeadSeriesB43504Capacitance270μFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)480 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.1A @ 100Hz
SeriesB43504Capacitance $270\mu F$ Tolerance $\pm 20\%$ Voltage - Rated $250V$ ESR (Equivalent Series Resistance) $480 \text{ mOhm } @ 100\text{Hz}$ Lifetime @ Temp. $3000 \text{ Hrs } @ 105^{\circ}\text{C}$ Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$ PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency $1.1A @ 100\text{Hz}$
Capacitance $270\mu F$ Tolerance $\pm 20\%$ Voltage - Rated $250V$ ESR (Equivalent Series Resistance) $480 \text{ mOhm } @ 100\text{Hz}$ Lifetime @ Temp. $3000 \text{ Hrs } @ 105^{\circ}\text{C}$ Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$ PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency $1.1\text{A} @ 100\text{Hz}$
Tolerance ±20% Voltage - Rated 250V ESR (Equivalent Series Resistance) 480 mOhm @ 100Hz Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.1A @ 100Hz
Voltage - Rated250VESR (Equivalent Series Resistance)480 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.1A @ 100Hz
ESR (Equivalent Series Resistance) Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.1A @ 100Hz
Lifetime @ Temp. $3000 \text{ Hrs } @ 105^{\circ}\text{C}$ Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$ Polarization Polar Applications General Purpose Ripple Current - Low Frequency $1.1\text{A} @ 100\text{Hz}$
Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.1A @ 100Hz
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.1A @ 100Hz
Applications General Purpose Ripple Current - Low Frequency 1.1A @ 100Hz
Ripple Current - Low Frequency 1.1A @ 100Hz
Ripple Current - High Frequency -
Impedance -
Lead Spacing 0.394" (10.00mm)
Size / Dimension 0.866" Dia (22.00mm)
Height - Seated (Max) 1.465" (37.20mm)
Surface Mount Land Size -
Mounting Type Through Hole
Package / Case Radial, Can - Snap-In - 3 Lead
Report errors?

B43504A2277M82 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

B43504A2277M82 Payment Methods





















B43504A2277M82 Shipping Methods













If you have any question about B43504A2277M82, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com