

## B43504A337M60

#### B43504A337M60 Information

Heisener.com	 B43504A337M60 EPCOS (TDK) Capacitors Aluminum Electrolytic Capacitors CAP ALUM 330UF 20% 420V SNAP Radial, Can - Snap-In For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote



Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



### B43504A337M60 Specifications

Manufacturer EPCOS (TDK)   Category Capacitors   Aluminum Electrolytic Capacitors Aluminum Electrolytic Capacitors   Package Radial, Can - Snap-In   Series B43504   Capacitance 330µF   Tolerance ±20%   Voltage - Rated 420V   ESR (Equivalent Series Resistance) 410 mOhm @ 100Hz   Lifetime @ Temp. 3000 Hrs @ 105°C   Operating Temperature -40°C ~ 105°C   Polarization Folar   Applications General Purpose   Ripple Current - Low Frequency -   Impedance 490 mOhms   Lead Spacing 0.394" (10.00mm)   Size / Dimension 1.181" Dia (30.00mm)   Height - Seated (Max) 1.850" (47.00mm)   Surface Mount Land Size -   Mounting Type Through Hole   Package / Case Radial, Can - Snap-In	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43504Capacitance330µFTolerance±20%Voltage - Rated420VESR (Equivalent Series Resistance)410 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationGeneral PurposeRipple Current - Low Frequency1.5A @ 100HzRipple Current - High Frequency-Impedance490 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.81" Dia (30.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Manufacturer Part Number	B43504A337M60
Aluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43504Capacitance330µFTolerance-20%Voltage - Rated420VESR (Equivalent Series Resistance)410 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationFolaraApplicationsGeneral PurposeRipple Current - High Frequency-Impedance490 mOhmsLiad Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Size / Dimension1.850" (47.00mm)Surface Mount Land Size-Mounting TypeFolacePackage / CaseKadial, Can - Snap-In	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-InSeriesB43504Capacitance330µFTolerance±20%Voltage - Rated420VESR (Equivalent Series Resistance)410 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationGeneral PurposeRiple Current - Low Frequency-Impedance490 mOhmsLingelace0.394" (10.00mm)Liad Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Size / Dimension1.850" (47.00mm)Surface Mount Land Size-Mounting TypeFancePackage / CaseRadial, Can - Snap-In	Category	Capacitors
SeriesB43504Capacitance330µFTolerance±20%Voltage - Rated420VESR (Equivalent Series Resistance)410 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance490 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKadial, Can - Snap-In		Aluminum Electrolytic Capacitors
Capacitance330µFTolerance±20%Voltage - Rated420VESR (Equivalent Series Resistance)410 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance490 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Package	Radial, Can - Snap-In
Tolerance±20%Voltage - Rated420VESR (Equivalent Series Resistance)410 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance490 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can - Snap-In	Series	B43504
Voltage - Rated420VESR (Equivalent Series Resistance)410 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.5A @ 100HzImpedance490 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeFrequencyPackage / CaseRadial, Can - Snap-In	Capacitance	330µF
ESR 410 mOhm @ 100Hz   ESR (Equivalent Series Resistance) 400 mOhm @ 100Hz   Lifetime @ Temp. 3000 Hrs @ 105°C   Operating Temperature -40°C ~ 105°C   Polar Polar   Applications General Purpose   Ripple Current - Low Frequency 1.5A @ 100Hz   Inpedance 490 mOhms   Lead Spacing 0.394" (10.00mm)   Size / Dimension 1.810" Dia (30.00mm)   Height - Seated (Max) 1.850" (47.00mm)   Surface Mount Land Size -   Mounting Type Finough Hole   Package / Case Raial, Can - Snap-In	Tolerance	$\pm 20\%$
Lifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.5A @ 100HzRipple Current - High Frequency-Impedance490 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeFurough HolePackage / CaseRadial, Can - Snap-In	Voltage - Rated	420V
Operating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.5A @ 100HzRipple Current - High Frequency-Impedance490 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	ESR (Equivalent Series Resistance)	410 mOhm @ 100Hz
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.5A @ 100HzRipple Current - High Frequency-Impedance490 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lifetime @ Temp.	3000 Hrs @ 105°C
ApplicationsGeneral PurposeRipple Current - Low Frequency1.5A @ 100HzRipple Current - High Frequency-Impedance490 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Operating Temperature	-40°C ~ 105°C
Ripple Current - Low Frequency1.5A @ 100HzRipple Current - High Frequency-Impedance490 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Polarization	Polar
In PropositionFrequencyRipple Current - High Frequency-Impedance490 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Applications	General Purpose
Impedance490 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - Low Frequency	1.5A @ 100Hz
Lead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - High Frequency	-
Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Impedance	490 mOhms
Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Size / Dimension	1.181" Dia (30.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Height - Seated (Max)	1.850" (47.00mm)
Package / Case Radial, Can - Snap-In	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can - Snap-In
		Report errors?

#### B43504A337M60 Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE EUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### B43504A337M60 Payment Methods





If you have any question about B43504A337M60, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com