

B43504A5227M67

B43504A5227M67 Information

Heisener.com	Part Number Manufacturer Category Description Package	B43504A5227M67 EPCOS (TDK) Capacitors Aluminum Electrolytic Capacitors CAP ALUM 220UF 20% 450V SNAP Radial, Can - Snap-In For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B43504A5227M67 Specifications

Manufacturer Part Number B43504A5227M67 Manufacturer EPCOS (TDK) Category Capacitors Aluminum Electrolytic Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Snap-In Series B43504 Capacitance 220µF Tolerance ±200µF Voltage - Rated 450V ESR (Equivalent Series Resistance) 610 mOhm @ 100Hz Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization General Purpose Applications General Purpose Ripple Current - Low Frequency - Impedance 730 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 0.984" Dia (25.00mm) Height - Seated (Max) 2.047" (52.00mm) Surface Mount Land Size - Mounting Type Fhoregut-Pio	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43504Capacitance220µFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)610 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationGeneral PurposeRipple Current - Low Frequency1.2A @ 100HzRipple Current - High Frequency-Impedance0.394" (10.00mm)Lied Spacing0.984" Dia (25.00mm)Size / Dimension9.044" (52.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Manufacturer Part Number	B43504A5227M67
IdentifyAluminum Electrolytic CapacitonsPackageRadial, Can - Snap-InSeriesB43504Capacitance20µFTolerance420%Voltage - Rated450VESR (Equivalent Series Resistance)610 mOhm @ 100HzDieraing Temperature3000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - High Frequency1.2 A @ 100HzRipple Current - High Frequency300 OhmsLied Spacing0.394" (10.00mm)Siz / Dimension0.984" Dia (25.00mm)Hight - Seated (Max).404" (52.00mm)Surface Mount Land Size-Mounting TypeFirough HolePackage / CaseRadia, Can - Snap-In	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-InSeriesB43504Capacitance220µFTolerance±20%Voltage - Rated610 mOhm @ 100HzESR (Equivalent Series Resistance)610 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency1.2A @ 100HzRipple Current - High Frequency-Impedance0.394" (10.00mm)Size / Dimension0.948" Dia (25.00mm)Size / Dimension2.047" (52.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Category	Capacitors
SeriesB43504Capacitance220µFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)610 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency.Impedance730 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size.Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In		Aluminum Electrolytic Capacitors
Capacitance20μFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)610 mOhm @ 100HzESR (Equivalent Series Resistance)3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency-Impedance730 mOhmsLead Spacing0.984" Dia (25.00mm)Size / Dimension2.047" (52.00mm)Surface Mount Land Size-Mounting TypeFrough HolePackage / CaseRatial, Can - Snap-In	Package	Radial, Can - Snap-In
Tolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)610 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency1.2A @ 100HzImpedance0.394" (10.00mm)Lead Spacing0.984" Dia (25.00mm)Size / Dimension2.047" (52.00mm)Hight - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Pounting TypeRadial, Can - Snap-In	Series	B43504
Voltage - Rated450VESR (Equivalent Series Resistance)610 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.2A @ 100HzRipple Current - High Frequency-Impedance730 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension9.944" Dia (25.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can - Snap-In	Capacitance	220µF
EVE 610 mOhm @ 100Hz ESR (Equivalent Series Resistance) 610 mOhm @ 100Hz Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polar Folarization Applications General Purpose Ripple Current - Low Frequency 1.2A @ 100Hz Ripple Current - High Frequency - Impedance 730 mOhms Size / Dimension 0.394" (10.00mm) Size / Dimension 0.984" Dia (25.00mm) Surface Mount Land Size - Mounting Type - Package / Case Ratial, Can - Snap-In	Tolerance	$\pm 20\%$
Lifetime @ Temp.3000 Hrs @ 105°CDeperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.2A @ 100HzRipple Current - High Frequency-Impedance730 mOhmsLead Spacing0.994" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeFhrough HolePackage / CaseRadial, Can - Snap-In	Voltage - Rated	450V
Operating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.2A @ 100HzRipple Current - High Frequency-Impedance730 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeFrough HolePackage / CaseRadial, Can - Snap-In	ESR (Equivalent Series Resistance)	610 mOhm @ 100Hz
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.2A @ 100HzRipple Current - High Frequency-Impedance730 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lifetime @ Temp.	3000 Hrs @ 105°C
ApplicationsGeneral PurposeRipple Current - Low Frequency1.2A @ 100HzRipple Current - High Frequency-Impedance730 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Operating Temperature	-40°C ~ 105°C
InInRipple Current - Low Frequency1.2A @ 100HzRipple Current - High Frequency-Impedance730 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Polarization	Polar
In a constraint of a constrain	Applications	General Purpose
Impedance730 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - Low Frequency	1.2A @ 100Hz
I card Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - High Frequency	-
Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Impedance	730 mOhms
Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Size / Dimension	0.984" Dia (25.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Height - Seated (Max)	2.047" (52.00mm)
Package / Case Radial, Can - Snap-In	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors	Package / Case	Radial, Can - Snap-In
		Report errors?

B43504A5227M67 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE ELARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B43504A5227M67 Payment Methods





If you have any question about B43504A5227M67, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com