

B43504A826M67 Information



For Reference Only

Part Number B43504A826M67
Manufacturer EPCOS (TDK)
Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 82UF 20% 420V SNAP

Package Radial, Can - Snap-In

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









B43504A826M67 Specifications

Manufacturer Part Number B43504A826M67 Manufacturer EPCOS (TDK) Category Capacitors Package Radial, Can - Snap-In Series B43504 Capacitance 82μF Tolerance ±20% Voltage - Rated 420V ESR (Equivalent Series Resistance) 1.65 Ohm @ 100Hz Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization General Purpose Ripple Current - Low Frequency 550mA @ 100Hz Ripple Current - High Frequency - Lead Spacing 9.394" (10.00mm) Size / Dimension 0.866" Dia (22.00mm) Height - Seated (Max) 1.260" (32.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In		
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Snap-In Series B43504 Capacitance 82µF Tolerance ±20% Voltage - Rated 420V ESR (Equivalent Series Resistance) 1.65 Ohm @ 100Hz Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 550mA @ 100Hz Ripple Current - High Frequency - Impedance 1.95 Ohms Lead Spacing 0.394" (10.00mm) Size / Dimension 0.866" Dia (22.00mm) Height - Seated (Max) 1.260" (32.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Manufacturer Part Number	B43504A826M67
Package Radial, Can - Snap-In Series B43504 Capacitance 82μF Tolerance ±20% Voltage - Rated 420V ESR (Equivalent Series Resistance) 1.65 Ohm @ 100Hz Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 550mA @ 100Hz Ripple Current - High Frequency - Impedance 1.95 Ohms Lead Spacing 0.394" (10.00mm) Size / Dimension 0.866" Dia (22.00mm) Height - Seated (Max) 1.260" (32.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Manufacturer	EPCOS (TDK)
Package Radial, Can - Snap-In Series B43504 Capacitance 82μF Tolerance ±20% Voltage - Rated 420V ESR (Equivalent Series Resistance) 1.65 Ohm @ 100Hz Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 550mA @ 100Hz Ripple Current - High Frequency - Impedance 1.95 Ohms Lead Spacing 0.394" (10.00mm) Size / Dimension 0.866" Dia (22.00mm) Height - Seated (Max) 1.260" (32.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Category	Capacitors
Series B43504 Capacitance 82μF Tolerance ±20% Voltage - Rated 420V ESR (Equivalent Series Resistance) 1.65 Ohm @ 100Hz Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 550mA @ 100Hz Ripple Current - High Frequency - Impedance 1.95 Ohms Lead Spacing 0.394" (10.00mm) Size / Dimension 0.866" Dia (22.00mm) Height - Seated (Max) 1.260" (32.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In		Aluminum Electrolytic Capacitors
Capacitance 82µF Tolerance ±20% Voltage - Rated 420V ESR (Equivalent Series Resistance) 1.65 Ohm @ 100Hz Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 550mA @ 100Hz Ripple Current - High Frequency - Impedance 1.95 Ohms Lead Spacing 0.394" (10.00mm) Size / Dimension 0.866" Dia (22.00mm) Height - Seated (Max) 1.260" (32.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Package	Radial, Can - Snap-In
Tolerance ±20% Voltage - Rated 420V ESR (Equivalent Series Resistance) 1.65 Ohm @ 100Hz Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 550mA @ 100Hz Ripple Current - High Frequency - Impedance 1.95 Ohms Lead Spacing 0.394" (10.00mm) Size / Dimension 0.866" Dia (22.00mm) Height - Seated (Max) 1.260" (32.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Series	B43504
Voltage - Rated ESR (Equivalent Series Resistance) Lifetime @ Temp. Operating Temperature -40°C ~ 105°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing 1.95 Ohms Lead Spacing 0.394" (10.00mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case Ray00 Hrs @ 100Hz -40°C ~ 105°C General Purpose General Purpose 550mA @ 100Hz -50mA @ 100Hz -60m (32.00mm) 1.260" (32.00mm) Through Hole Radial, Can - Snap-In	Capacitance	82μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. Operating Temperature -40°C ~ 105°C Polarization Applications General Purpose Ripple Current - Low Frequency Fipple Current - High Frequency Impedance Lead Spacing 1.95 Ohms Lead Spacing 0.394" (10.00mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Rio00 Hrs @ 100Hz 3000 Hrs @ 105°C -40°C ~ 100Hz -40°C ~ 105°C -40°C ~ 105°C -40°C ~ 105°C -40°C ~ 100Hz -40°C ~	Tolerance	±20%
Lifetime @ Temp. Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency Frequency Fipple Current - High Frequency Impedance 1.95 Ohms Lead Spacing 0.394" (10.00mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case 3000 Hrs @ 105°C -40°C ~ 105°C Folar General Purpose 550mA @ 100Hz 550mA @ 100Hz 1.95 Ohms 1.95 Ohms 1.260" (32.00mm) Through Hole Radial, Can - Snap-In	Voltage - Rated	420V
Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency S50mA @ 100Hz Ripple Current - High Frequency - Impedance 1.95 Ohms Lead Spacing 0.394" (10.00mm) Size / Dimension 0.866" Dia (22.00mm) Height - Seated (Max) 1.260" (32.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	ESR (Equivalent Series Resistance)	1.65 Ohm @ 100Hz
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 550mA @ 100Hz Ripple Current - High Frequency - Impedance 1.95 Ohms Lead Spacing 0.394" (10.00mm) Size / Dimension 0.866" Dia (22.00mm) Height - Seated (Max) 1.260" (32.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Lifetime @ Temp.	3000 Hrs @ 105°C
Applications Ripple Current - Low Frequency S50mA @ 100Hz Ripple Current - High Frequency Impedance 1.95 Ohms Lead Spacing 0.394" (10.00mm) Size / Dimension 0.866" Dia (22.00mm) Height - Seated (Max) 1.260" (32.00mm) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Operating Temperature	-40°C ~ 105°C
Ripple Current - Low Frequency 550mA @ 100Hz Ripple Current - High Frequency - Impedance 1.95 Ohms Lead Spacing 0.394" (10.00mm) Size / Dimension 0.866" Dia (22.00mm) Height - Seated (Max) 1.260" (32.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Polarization	Polar
Ripple Current - High Frequency Impedance 1.95 Ohms Lead Spacing 0.394" (10.00mm) Size / Dimension 0.866" Dia (22.00mm) Height - Seated (Max) 1.260" (32.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Applications	General Purpose
Impedance 1.95 Ohms Lead Spacing 0.394" (10.00mm) Size / Dimension 0.866" Dia (22.00mm) Height - Seated (Max) 1.260" (32.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Ripple Current - Low Frequency	550mA @ 100Hz
Lead Spacing 0.394" (10.00mm) Size / Dimension 0.866" Dia (22.00mm) Height - Seated (Max) 1.260" (32.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Ripple Current - High Frequency	-
Size / Dimension 0.866" Dia (22.00mm) Height - Seated (Max) 1.260" (32.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Impedance	1.95 Ohms
Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Size / Dimension	0.866" Dia (22.00mm)
Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Height - Seated (Max)	1.260" (32.00mm)
Package / Case Radial, Can - Snap-In	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can - Snap-In
		Report errors?

B43504A826M67 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

B43504A826M67 Payment Methods



















B43504A826M67 Shipping Methods













If you have any question about B43504A826M67, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com