

B43504A9127M007

B43504A9127M007 Information

Heisener.com	 B43504A9127M007 EPCOS (TDK) Capacitors Aluminum Electrolytic Capacitors CAP ALUM 120UF 20% 400V SNAP Radial, Can - Snap-In For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B43504A9127M007 Specifications

Manufacturer Part Number B43504A9127M007 Manufacturer EPCOS (TDK) Category Capacitors Aluminum Electrolytic Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Snap-In Series B43504 Capacitance 120µF Tolerance 200µF Voltage - Rated 400V ESR (Equivalent Series Resistance) 730 mOhm @ 100Hz Lifetime @ remp. 3000 Hrs @ 105°C Operating Temperature 40°C ~ 105°C Polarization General Purpose Applications General Purpose Ripple Current - Low Frequency - Impedance 910 mOhms Lead Spacing 0.394° (10.00mm) Size / Dimension 3.666° Dia (22.00mm) Size / Dimension - Mounting Type - Mounting Type -	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43504Capacitance120µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)730 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationGeneral PurposeRipple Current - Low Frequency700mA @ 100HzRipple Current - High Frequency-Impedance910 mOhmsLied Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Manufacturer Part Number	B43504A9127M007
IdentifyAluninum Electrolytic CapacitonsPackageRadial, Can - Snap-InSeriesB43504Capacitance120µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)730 mOhm @ 100HzDieraing Temperature3000 Hrs @ 105°COperating Temperature60eral PurposeApplicationsGeneral PurposeRipple Current - High Frequency70 mOhm @ 100HzRipple Current - High Frequency910 mOhmsLied Spacing0.394" (10.00mm)Size / Dimension3.394" (10.00mm)Size / Dimension1.457" (37.00mm)Sirdare Mount Land Size-Mounting TypeFurough HolePackage / CaseRadia, Can - Snap-In	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-InSeriesB43504Capacitance120μFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)730 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency700mA @ 100HzImpedance910 mOhmsLad Spacing0.394" (10.00mm)Size / Dimension1.457" (37.00mm)Size / Dimension1.457" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can - Snap-In	Category	Capacitors
SeriesB43504Capacitance120µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)730 mOhm @ 100HzESR (Equivalent Series Resistance)3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency700mA @ 100HzIfted Spacing0.394" (10.00mm)Size / Dimension0.366" Dia (22.00mm)Size / Dimension4.45" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can - Snap-In		Aluminum Electrolytic Capacitors
Capacitance120µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)730 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationFolarApplicationsGeneral PurposeRipple Current - High Frequency-00mA @ 100HzInpedance910 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Size / Dimension1.457" (37.00mm)Surface Mount Land Size-Mounting TypeThough HolePackage / CaseRatial, Can - Snap-In	Package	Radial, Can - Snap-In
Tolerance±20%Yoltage - Rated400VESR (Equivalent Series Resistance)730 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency700mA @ 100HzImpedance910 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Hounting TypeFhrough HolePackage / CaseRatial, Can - Snap-In	Series	B43504
Voltage - Rated400VESR (Equivalent Series Resistance)730 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency700mA @ 100HzRipple Current - High Frequency910 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Hounting TypeFrequencyPackage / CaseRatial, Can - Snap-In	Capacitance	120µF
Loc730 mOhm @ 100HzESR (Equivalent Series Resistance)730 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency700mA @ 100HzRipple Current - High Frequency-Impedance910 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866° Dia (22.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeFurogationPackage / CaseRadial, Can - Snap-In	Tolerance	±20%
Lifetime @ Temp.3000 Hrs @ 105°CDperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency700mA @ 100HzRipple Current - High Frequency-Impedance910 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeRadial, Can - Snap-In	Voltage - Rated	400V
Operating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency700mA @ 100HzRipple Current - High Frequency-Impedance910 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeFackage / CaseRakage / CaseRakial, Can - Snap-In	ESR (Equivalent Series Resistance)	730 mOhm @ 100Hz
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency700mA @ 100HzRipple Current - High Frequency-Impedance910 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lifetime @ Temp.	3000 Hrs @ 105°C
ApplicationsGeneral PurposeRipple Current - Low Frequency700mA @ 100HzRipple Current - High Frequency-Impedance910 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Operating Temperature	-40° C ~ 105° C
Ripple Current - Low Frequency700mA @ 100HzRipple Current - High Frequency-Impedance910 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Polarization	Polar
In a constraint of the product of t	Applications	General Purpose
Impedance910 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - Low Frequency	700mA @ 100Hz
Lead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - High Frequency	-
Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Impedance	910 mOhms
Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Size / Dimension	0.866" Dia (22.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Height - Seated (Max)	1.457" (37.00mm)
Package / Case Radial, Can - Snap-In	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors	Package / Case	Radial, Can - Snap-In
		Report errors?

B43504A9127M007 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B43504A9127M007 Payment Methods



B43504A9127M007 Shipping Methods



If you have any question about B43504A9127M007, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com