

# B43504A9227M87

#### B43504A9227M87 Information

Heisener.com	 B43504A9227M87 EPCOS (TDK) Capacitors Aluminum Electrolytic Capacitors CAP ALUM 220UF 20% 400V SNAP Radial, Can - Snap-In For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



### B43504A9227M87 Specifications

Manufacturer EPCOS (TDK)   Category Capacitors   Aluminum Electrolytic Capacitors   Package Radial, Can - Snap-In   Series B43504   Capacitance 220µF   Tolerance ±20%   Voltage - Rated 400 v   ESR (Equivalent Series Resistance) 400 mOhm @ 100Hz   Diferime @ Temp. 3000 Hrs @ 105°C   Operating Temperature -40°C ~ 105°C   Polarization Polar   Applications General Purpose   Ripple Current - Low Frequency -   Impedance 500 mOhms   Lead Spacing 0.394" (10.00mm)   Size / Dimension 0.984" Dia (25.00mm)   Height - Seated (Max) 1.858" (47.20mm)   Surface Mount Land Size -   Mounting Type Through Hole   Package / Case Kadial, Can - Snap-In	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43504Capacitance220µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)400 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance500 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.858" (47.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Manufacturer Part Number	B43504A9227M87
Aluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InStriesB43504Capacitance220µFTolerance420%Voltage - Rated400 VESR (Equivalent Series Resistance)400 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationFolaraceApplicationsGeneral PurposeRipple Current - High Frequency-Impedance500 mOhmsLided Spacing0.394" (10.0mm)Size / Dimension0.984" Dia (25.00mm)Size / Dimension1.858" (47.20mm)Surface Mount Land Size-Mounting TypeFolare Stape.Package / CaseKadial, Can - Snap-In	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-InSeriesB43504Capacitance220µFTolerance±20%Voltage - Rated400 VESR (Equivalent Series Resistance)400 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationGeneral PurposeRiple Current - Low Frequency-Impedance500 mOhmsLifetime @ Temp.0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Size / Dimension1.858" (47.20mm)Surface Mount Land Size-Mounting TypeFancuentPackage / CaseRadial, Can - Snap-In	Category	Capacitors
SeriesB43504Capacitance220µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)400 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency.112A @ 100HzLinedance500 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.858" (47.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKadial, Can - Snap-In		Aluminum Electrolytic Capacitors
Capacitance220µFTolerance±20%Voltage - Rated400 VESR (Equivalent Series Resistance)400 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance500 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Package	Radial, Can - Snap-In
Tolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)400 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency.Impedance500 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.858" (47.20mm)Surface Mount Land Size-Pockage / CaseRadial, Can - Snap-In	Series	B43504
Voltage - Rated400VESR (Equivalent Series Resistance)400 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.12A @ 100HzImpedance500 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.858" (47.20mm)Surface Mount Land Size-Mounting TypeFurous HolePackage / CaseRadial, Can - Snap-In	Capacitance	220µF
Constraint 400 mOhm @ 100Hz   ESR (Equivalent Series Resistance) 400 mOhm @ 100Hz   Lifetime @ Temp. 3000 Hrs @ 105°C   Operating Temperature -40°C ~ 105°C   Polar Polar   Applications General Purpose   Ripple Current - Low Frequency 1.12A @ 100Hz   Inpedance 500 mOhms   Lead Spacing 0.394" (10.00mm)   Size / Dimension 0.984" Dia (25.00mm)   Height - Seated (Max) 1.858" (47.20mm)   Surface Mount Land Size -   Mounting Type Through Hole   Package / Case Raial, Can - Snap-In	Tolerance	±20%
Lifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.12A @ 100HzRipple Current - High Frequency-Impedance500 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.858" (47.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Voltage - Rated	400V
Operating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.12A @ 100HzRipple Current - High Frequency-Impedance500 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.858" (47.20mm)Surface Mount Land Size-Mounting TypeFnough HolePackage / CaseRadial, Can - Snap-In	ESR (Equivalent Series Resistance)	400 mOhm @ 100Hz
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.12A @ 100HzRipple Current - High Frequency-Impedance500 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.858" (47.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lifetime @ Temp.	3000 Hrs @ 105°C
ApplicationsGeneral PurposeRipple Current - Low Frequency1.12A @ 100HzRipple Current - High Frequency-Impedance500 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.858" (47.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Operating Temperature	-40°C ~ 105°C
Ripple Current - Low Frequency1.12A @ 100HzRipple Current - High Frequency-Impedance500 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.858" (47.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Polarization	Polar
In a constraint of the product of t	Applications	General Purpose
Impedance500 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.858" (47.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - Low Frequency	1.12A @ 100Hz
IILead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.858" (47.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - High Frequency	-
Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.858" (47.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Impedance	500 mOhms
Height - Seated (Max)1.858" (47.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Size / Dimension	0.984" Dia (25.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Height - Seated (Max)	1.858" (47.20mm)
Package / Case Radial, Can - Snap-In	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can - Snap-In
		Report errors?

#### B43504A9227M87 Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE BUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### B43504A9227M87 Payment Methods





If you have any question about B43504A9227M87, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com