

# B43504A9476M007

## B43504A9476M007 Information

Heisener.com	 B43504A9476M007 EPCOS (TDK) Capacitors Aluminum Electrolytic Capacitors CAP ALUM 47UF 20% 400V SNAP Radial, Can - Snap-In For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



# B43504A9476M007 Specifications

Manufacturer Part NumberB43504A9476M007ManufacturerEPCOS (TDK)CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43504Capacitance47µFTolerance220%Voltage - RatedMoVESR (Equivalent Series Resistance)1.86 Ohm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationGeneral PurposeRipple Current - Low Frequency300mA @ 100HzRipple Current - High Frequency.Impedance2.31 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.66" Dia (22.00mm)Height - Seated (Max).Mounting TypeInrough HolePort Caree.Mounting TypeRadial, Can - Snap-In	•	
CategoryCapacitorsAluminum Electrolytic CapacitonsPackageRadial, Can - Snap-InSeriesB43504Capacitance47µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)1.86 Ohm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating TemperatureeV0°C ~ 105°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency390mA @ 100HzRipple Current - High Frequency.Impedance2.31 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max).Mounting TypeFrouge HolePackage / CaseKaila, Can - Snap-In	Manufacturer Part Number	B43504A9476M007
Auminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43504Capacitance47µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)1.86 Ohm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature44°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency.Impedance.31 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Size / Dimension1.063" (27.00mm)Surface Mount Land Size.Pokage / CaseRadial, Can - Snap-In	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-InSeriesB43504Capacitance47µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)1.86 Ohm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature440°C ~ 105°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency390mA @ 100HzImpedance2.31 OhmsLad Spacing0.86° Tia (22.00mm)Size / Dimension1.063" (27.00mm)Size / Dimension-Mounting TypeFinoghalePockage / CaseRaid, Can - Snap-In	Category	Capacitors
SeriesB43504Capacitance47µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)1.86 Ohm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency390mA @ 100HzInpedance2.31 OhmsIcad Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKadial, Can - Snap-In		Aluminum Electrolytic Capacitors
Capacitance47μFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)1.86 Ohm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency300m A @ 100HzImpedance2.31 OhmsLad Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can - Snap-In	Package	Radial, Can - Snap-In
Tolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)1.86 Ohm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency390mA @ 100HzInpedance2.31 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeFarcage / CaseRackage / CaseRadial, Can - Snap-In	Series	B43504
Voltage - Rated400VESR (Equivalent Series Resistance)1.86 Ohm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency390mA @ 100HzImpedance2.31 OhmsIcad Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeFrequencyPackage / CaseRatial, Can - Snap-In	Capacitance	47µF
CIseESR (Equivalent Series Resistance)1.86 Ohm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency390mA @ 100HzRipple Current - High Frequency-Impedance2.31 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeFurquencyPackage / CaseRadial, Can - Snap-In	Tolerance	$\pm 20\%$
Lifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency390mA @ 100HzRipple Current - High Frequency-Impedance2.31 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeRadial, Can - Snap-In	Voltage - Rated	400V
Operating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency390mA @ 100HzRipple Current - High Frequency-Impedance2.31 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeFackage / CasePackage / CaseRadial, Can - Snap-In	ESR (Equivalent Series Resistance)	1.86 Ohm @ 100Hz
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency390mA @ 100HzRipple Current - High Frequency-Impedance2.31 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lifetime @ Temp.	3000 Hrs @ 105°C
ApplicationsGeneral PurposeRipple Current - Low Frequency390mA @ 100HzRipple Current - High Frequency-Impedance2.31 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Operating Temperature	-40°C ~ 105°C
Ripple Current - Low Frequency390mA @ 100HzRipple Current - High Frequency-Impedance2.31 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Polarization	Polar
In a randomRipple Current - High Frequency-Impedance2.31 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Applications	General Purpose
Impedance2.31 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - Low Frequency	390mA @ 100Hz
IILead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - High Frequency	-
Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Impedance	2.31 Ohms
Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Size / Dimension	0.866" Dia (22.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Height - Seated (Max)	1.063" (27.00mm)
Package / Case Radial, Can - Snap-In	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors	Package / Case	Radial, Can - Snap-In
1		Report errors?

### B43504A9476M007 Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### B43504A9476M007 Payment Methods





If you have any question about B43504A9476M007, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com