

B43504A9477M60

B43504A9477M60 Information

Heisener (B43504A9477M60 EPCOS (TDK) Capacitors Aluminum Electrolytic Capacitors CAP ALUM 470UF 20% 400V SNAP Radial, Can - Snap-In For the pricing/inventory/lead time, please contact	
For Reference C	Dnly	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B43504A9477M60 Specifications

Manufacturer Part NumberB43504A9477M60ManufacturerEPCOS (TDK)CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43504Capacitance470µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)190 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationGeneral PurposeRipple Current - Low Frequency2A @ 100HzRipple Current - High Frequency-Linde Apacing0.394" (10.00mm)Size / Dinension1.378" Dia (35.00mm)Size / Dinension1.850" (47.00mm)Manufacture TempSize / Dinension1.850" (47.00mm)Size / Dinension1.850" (47.00mm)Size / Dinension-Manufacture TempSize / Dinension-Size / Dinension- <t< th=""><th></th><th></th></t<>		
CategoryCapacitorsAutuninum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43504Capacitance470µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)190 mOnm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency24 @ 100HzRipple Current - High Frequency-Lied Spacing3.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max).Surface Mount Land Size-	Manufacturer Part Number	B43504A9477M60
Auminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43504Capacitance470µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)190 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - High Frequency-40 onthmsLinedance3094" (10.00mm)Liad Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Hight - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-InSeriesB43504Capacitance470μFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)190 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - High Frequency2A @ 100HzLiad Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Hight - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-	Category	Capacitors
SeriesB43504Capacitance470µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)190 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationFolaraApplicationsGeneral PurposeRipple Current - High Frequency24 @ 100HzImpedance240 mOhmsLad Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-		Aluminum Electrolytic Capacitors
Capacitance470µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)100 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency2A @ 100HzImpedance140°C mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Hight - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-	Package	Radial, Can - Snap-In
Tolerance±20%Yoltage - Rated400VESR (Equivalent Series Resistance)190 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency-Impedance240 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Hight - Seated (Max).Surface Mount Land Size-	Series	B43504
Voltage - Rated400VESR (Equivalent Series Resistance)190 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency2A @ 100HzRipple Current - High Frequency-Impedance240 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-	Capacitance	470µF
Lead190 mOhm @ 100HzESR (Equivalent Series Resistance)190 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2A @ 100HzRipple Current - High Frequency-Impedance240 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-	Tolerance	$\pm 20\%$
Lifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2A @ 100HzRipple Current - High Frequency-Impedance240 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-	Voltage - Rated	400V
Applearing Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2A @ 100HzRipple Current - High Frequency-Impedance240 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-	ESR (Equivalent Series Resistance)	190 mOhm @ 100Hz
PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2A @ 100HzRipple Current - High Frequency-Impedance240 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-	Lifetime @ Temp.	3000 Hrs @ 105°C
ApplicationsGeneral PurposeRipple Current - Low Frequency2A @ 100HzRipple Current - High Frequency-Impedance240 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-	Operating Temperature	-40°C ~ 105°C
Ripple Current - Low Frequency2A @ 100HzRipple Current - High Frequency-Impedance240 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-	Polarization	Polar
In a constraint of the second secon	Applications	General Purpose
Impedance240 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-	Ripple Current - Low Frequency	2A @ 100Hz
Lead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-	Ripple Current - High Frequency	-
Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-	Impedance	240 mOhms
Height - Seated (Max) 1.850" (47.00mm) Surface Mount Land Size -	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size -	Size / Dimension	1.378" Dia (35.00mm)
	Height - Seated (Max)	1.850" (47.00mm)
	Surface Mount Land Size	-
Mounting Type Inrough Hole	Mounting Type	Through Hole
Package / Case Radial, Can - Snap-In	Package / Case	Radial, Can - Snap-In
Report errors?		Report errors?

B43504A9477M60 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B43504A9477M60 Payment Methods





If you have any question about B43504A9477M60, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com