

## B43504A9826M80

#### B43504A9826M80 Information

Heisener.com	 B43504A9826M80 EPCOS (TDK) Capacitors Aluminum Electrolytic Capacitors CAP ALUM 82UF 20% 400V SNAP Radial, Can - Snap-In For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



### B43504A9826M80 Specifications

Manufacturer Part Number B43504A9826M80   Manufacturer EPCOS (TDK)   Category Capacitors   Aluminum Electrolytic Capacitors Aluminum Electrolytic Capacitors   Package Radial, Can - Snap-In   Series B43504   Capacitance 82µF   Tolerance ±20%   Voltage - Rated 400V   ESR (Equivalent Series Resistance) 000 V   Lifetime @ Temp. 3000 Hrs @ 105°C   Operating Temperature -40°C ~ 105°C   Polarization General Purpose   Ripple Current - Low Frequency StomA @ 100Hz   Ripple Current - High Frequency -   Stoze / Dimension 0.394" (10.00mm)   Size / Dimension 0.866" Dia (22.00mm)   Height - Seated (Max) 1.268" (32.20mm)   Surface Mount Land Size -   Mounting Type Through Hole   Package / Case Surp - In		
CategoryCapacitorsAuminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43504Capacitance82µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)1.07 Ohm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationFolar Que yongApplicationsGeneral PurposeRipple Current - Low Frequency550mA @ 100HzImpedance.32 OhmsLad Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max).268" (32.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKadia, Can - Snap-In	Manufacturer Part Number	B43504A9826M80
IdentifyAluminum Electrolytic CapacitonsPackageRadial, Can - Snap-InSeriesB43504Capacitance82µFTolerance-20%Voltage - Rated00VESR (Equivalent Series Resistance)010 Phra 200 PhrameOperating Temper000 Hrs @ 100 PhraOperating Temperature-40°C ~ 105°CPolarizationFolar PhrameApplicationsGeneral PurposeRipple Current - Hogh Frequency-Kipple Current - High Frequency-Impedance1.32 OhnsLead Spacing0.394° (10.00mm)Size / Dimension1.268° (32.20mm)Hight - Seated (Max)-Surface Mount Land Size-Houning TypeMountig TypePackage / CaseKadia, Can - Snap-In	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-InSeriesB43504Capacitance82µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)1.07 Ohm @ 100HzDerating Temperature3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationGeneral PurposeRipple Current - Low Frequency550mA @ 100HzRipple Current - High Frequency-Impedance1.32 OhmsLead Spacing0.394" (10.00mm)Size / Dimension8666" Dia (22.00mm)Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Pockage / CaseRadial, Can - Snap-In	Category	Capacitors
SeriesB43504Capacitance82µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)1.07 Ohm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationFolarApplicationsGeneral PurposeRipple Current - High Frequency550mA @ 100HzIded Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Hounting TypeThrough HolePackage / CaseKadial, Can - Snap-In		Aluminum Electrolytic Capacitors
Capacitance82μFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)1.07 Ohm @ 100HzESR (Equivalent Series Resistance)3000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency550mA @ 100HzInpedance1.32 OhmsStard Spacing0.394° (10.00mm)Size / Dimension0.866° Dia (22.00mm)Starface Mount Land Size-Mounting TypeThrough HolePackage / CaseKaila, Can - Snap-In	Package	Radial, Can - Snap-In
Tolerance±0%Voltage - Rated400VESR (Equivalent Series Resistance)1.07 Ohm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency550mA @ 100HzImpedance1.32 OhmsLead Spacing0.394" (10.00mm)Size / Dinension0.866" Dia (22.00mm)Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Mounting TypeFhrough HolePackage / CaseRadial, Can - Snap-In	Series	B43504
Voltage - Rated400VESR (Equivalent Series Resistance)1.07 Ohm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency550mA @ 100HzImpedance.Inpedance0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Mounting TypeFrequencyPackage / CaseRadial, Can - Snap-In	Capacitance	82µF
Component1.07 Ohm @ 100HzESR (Equivalent Series Resistance)1.07 Ohm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency550mA @ 100HzRipple Current - High Frequency-Impedance1.32 OhmsLead Spacing0.394" (10.00mm)Size / Dimension1.268" (32.20mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeFackage / CasePackage / CaseRadial, Can - Snap-In	Tolerance	$\pm 20\%$
Lifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency550mA @ 100HzRipple Current - High Frequency-Impedance1.32 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Voltage - Rated	400V
Operating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency550mA @ 100HzRipple Current - High Frequency-Impedance1.32 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Mounting TypeFhrough HolePackage / CaseRadial, Can - Snap-In	ESR (Equivalent Series Resistance)	1.07 Ohm @ 100Hz
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency550mA @ 100HzRipple Current - High Frequency-Impedance1.32 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lifetime @ Temp.	3000 Hrs @ 105°C
ApplicationsGeneral PurposeRipple Current - Low Frequency550mA @ 100HzRipple Current - High Frequency-Impedance1.32 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Operating Temperature	$-40^{\circ}\mathrm{C} \sim 105^{\circ}\mathrm{C}$
Ripple Current - Low Frequency550mA @ 100HzRipple Current - High Frequency-Impedance1.32 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Polarization	Polar
In a constraint of the product of t	Applications	General Purpose
Impedance1.32 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - Low Frequency	550mA @ 100Hz
Lead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - High Frequency	-
Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Impedance	1.32 Ohms
Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Size / Dimension	0.866" Dia (22.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Height - Seated (Max)	1.268" (32.20mm)
Package / Case Radial, Can - Snap-In	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report error	Package / Case	Radial, Can - Snap-In
Treport on on		Report errors?

#### B43504A9826M80 Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE BUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

## B43504A9826M80 Payment Methods





If you have any question about B43504A9826M80, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com