

B43504B2128M67

B43504B2128M67 Information

Heisener.com	Part Number Manufacturer Category Description Package	B43504B2128M67 EPCOS (TDK) Capacitors Aluminum Electrolytic Capacitors CAP ALUM 1200UF 20% 250V SNAP Radial, Can - Snap-In For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B43504B2128M67 Specifications

Manufacturer Part NumberB43504B2128M67ManufacturerEPCOS (TDK)CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43504Capacitance1200µFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)120 mOhm @ 100HzDerating Temperature40°C ~ 105°COperating Temperature6General PurposeApplicationsSign PurposeRipple Current - Low Frequency3.09A @ 100HzRipple Current - High Frequency50 mOhmsLead Spacing150 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)
CategoryCapacitorsCategoryAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43504Capacitance1200µFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)120 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency3.09A @ 100HzRipple Current - High Frequency150 mOhmsLead Spacing0.394" (10.00mm)
Aluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43504Capacitance1200µFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)120 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - High Frequency3.09A @ 100HzRipple Current - High Frequency150 mOhmsLead Spacing0.394" (10.00mm)
PackageRadial, Can - Snap-InSeriesB43504Capacitance1200μFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)120 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - High Frequency3.09A @ 100HzImpedance150 mOhmsLead Spacing0.394" (10.00mm)
SeriesB43504Series1200µFCapacitance±20%Tolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)120 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency.Impedance150 mOhmsLead Spacing0.394" (10.00mm)
Capacitance1200µFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)120 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.09A @ 100HzRipple Current - High Frequency-Impedance150 mOhmsLead Spacing0.394" (10.00mm)
Tolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)120 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.09A @ 100HzRipple Current - High Frequency-Impedance150 mOhmsLead Spacing0.394" (10.00mm)
Voltage - Rated250VESR (Equivalent Series Resistance)120 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.09A @ 100HzRipple Current - High Frequency-Impedance150 mOhmsLead Spacing0.394" (10.00mm)
ESR (Equivalent Series Resistance)120 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.09A @ 100HzRipple Current - High Frequency-Impedance150 mOhmsLead Spacing0.394" (10.00mm)
Lifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.09A @ 100HzRipple Current - High Frequency-Impedance150 mOhmsLead Spacing0.394" (10.00mm)
Operating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.09A @ 100HzRipple Current - High Frequency-Impedance150 mOhmsLead Spacing0.394" (10.00mm)
PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.09A @ 100HzRipple Current - High Frequency-Impedance150 mOhmsLead Spacing0.394" (10.00mm)
ApplicationsGeneral PurposeRipple Current - Low Frequency3.09A @ 100HzRipple Current - High Frequency-Impedance150 mOhmsLead Spacing0.394" (10.00mm)
Ripple Current - Low Frequency3.09A @ 100HzRipple Current - High Frequency-Impedance150 mOhmsLead Spacing0.394" (10.00mm)
Ripple Current - High Frequency-Impedance150 mOhmsLead Spacing0.394" (10.00mm)
Impedance150 mOhmsLead Spacing0.394" (10.00mm)
Lead Spacing 0.394" (10.00mm)
Size / Dimension 1.181" Dia (30.00mm)
Height - Seated (Max) 2.244" (57.00mm)
Surface Mount Land Size -
Mounting Type Through Hole
Package / Case Radial, Can - Snap-In
Report error

B43504B2128M67 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B43504B2128M67 Payment Methods





If you have any question about B43504B2128M67, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com