

# B43504B2277M87

#### B43504B2277M87 Information

Heisener.com	 B43504B2277M87 EPCOS (TDK) Capacitors Aluminum Electrolytic Capacitors CAP ALUM 270UF 20% 250V SNAP Radial, Can - Snap-In For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



### B43504B2277M87 Specifications

Manufacturer EPCOS (TDK)   Category Capacitors   Aluminum Electrolytic Capacitors Radial, Can - Snap-In   Package Radial, Can - Snap-In   Series B43504   Capacitance 270µF   Tolerance ±20%   Voltage - Rated 250V   ESR (Equivalent Series Resistance) 470 mOhm @ 100Hz   Lifetime @ Temp. 3000 Hrs @ 105°C   Operating Temperature -40°C ~ 105°C   Polarization Polar   Applications General Purpose   Ripple Current - Low Frequency 990mA @ 100Hz   Impedance 570 mOhms   Lead Spacing 0.394" (10.00mm)   Size / Dimension 0.866" Dia (22.00mm)   Height - Seated (Max) 1.268" (32.20mm)   Surface Mount Land Size -   Mounting Type Through Hole   Package / Case Radial, Can - Snap-In	_	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43504Capacitance270μFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)470 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency990mA @ 100HzImpedance570 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Manufacturer Part Number	B43504B2277M87
Aluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43504Capacitance270μFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)470 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency990mA @ 100HzRipple Current - High Frequency-Impedance570 mOhmsLad Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Package / CaseRadial, Can - Snap-In	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-InSeriesB43504Capacitance270µFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)470 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationGeneral PurposeRiple Current - Low Frequency990mA @ 100HzRiple Current - High Frequency-Impedance570 mOhmsLad Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Sirface Mount Land Size-Mounting TypeFhrough HolePackage / CaseRadial, Can - Snap-In	Category	Capacitors
SeriesB43504Capacitance270µFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)470 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency990mA @ 100HzLifedance570 mOhmsImpedance0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Package / CaseRadial, Can - Snap-In		Aluminum Electrolytic Capacitors
Capacitance 270μF   Tolerance ±20%   Voltage - Rated 250V   ESR (Equivalent Series Resistance) 470 mOhm @ 100Hz   Lifetime @ Temp. 3000 Hrs @ 105°C   Operating Temperature -40°C ~ 105°C   Polarization Polar   Applications General Purpose   Ripple Current - Low Frequency 990mA @ 100Hz   Impedance 570 mOhms   Lied Spacing 0.394" (10.00mm)   Size / Dimension 0.866" Dia (22.00mm)   Height - Seated (Max) 1.268" (32.20mm)   Surface Mount Land Size -   Package / Case Radial, Can - Snap-In	Package	Radial, Can - Snap-In
Tolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)470 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency990mA @ 100HzRipple Current - High Frequency-Impedance570 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can - Snap-In	Series	B43504
Voltage - Rated250VESR (Equivalent Series Resistance)470 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency990mA @ 100HzImpedance570 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Package / CaseRadial, Can - Snap-In	Capacitance	270µF
ESR (Equivalent Series Resistance)470 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency990mA @ 100HzBipple Current - High Frequency-Impedance570 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Package / CaseRadial, Can - Snap-In	Tolerance	±20%
Lifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency990mA @ 100HzRipple Current - High Frequency-Impedance570 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Voltage - Rated	250V
Operating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency990mA @ 100HzRipple Current - High Frequency-Impedance570 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	ESR (Equivalent Series Resistance)	470 mOhm @ 100Hz
PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency990mA @ 100HzRipple Current - High Frequency-Impedance570 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lifetime @ Temp.	3000 Hrs @ 105°C
ApplicationsGeneral PurposeRipple Current - Low Frequency990mA @ 100HzRipple Current - High Frequency-Impedance570 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Operating Temperature	$-40^{\circ}$ C ~ $105^{\circ}$ C
Ripple Current - Low Frequency990mA @ 100HzRipple Current - High Frequency-Impedance570 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Polarization	Polar
Ripple Current - High Frequency-Impedance570 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Applications	General Purpose
Impedance570 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - Low Frequency	990mA @ 100Hz
I card Spacing0.394" (10.00mm)Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - High Frequency	-
Size / Dimension0.866" Dia (22.00mm)Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Impedance	570 mOhms
Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Size / Dimension	0.866" Dia (22.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Height - Seated (Max)	1.268" (32.20mm)
Package / Case Radial, Can - Snap-In	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can - Snap-In
		Report errors?

#### B43504B2277M87 Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE EUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### B43504B2277M87 Payment Methods





If you have any question about B43504B2277M87, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com