

B43504B5277M007

equest a Quote

B43504B5277M007 Information

	Dart Number	B43504B5277M007
Heisener.com		EPCOS (TDK)
	Category	Capacitors Aluminum Electrolytic Capacitors
	Description	CAP ALUM 270UF 20% 450V SNAP
	Package	Radial, Can - Snap-In
		For the pricing/inventory/lead time, please contact
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B43504B5277M007 Specifications

Manufacturer Part NumberB43504B5277M007ManufacturerEPCOS (TDK)CategoryCapacitorsCategoryAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InPackageB43504Capacitance270µFTolerance±20%Voltage - Rated500 mOhm @ 100HzESR (Equivalent Series Resistance)500 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature440°C ~ 105°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency1.4A @ 100Hz	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43504Capacitance270µFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)500 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationFolarApplicationsGeneral Purpose	
HereinAluninum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43504Capacitance270μFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)500 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating TemperatureHolarPolarizationFolarApplicationsGeneral Purpose	
PackageRadial, Can - Snap-InSeriesB43504Capacitance270μFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)500 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationFolarApplicationsGeneral Purpose	
SeriesB43504Capacitance270μFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)500 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral Purpose	
Capacitance270μFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)500 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral Purpose	
Tolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)500 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral Purpose	
Voltage - Rated450VESR (Equivalent Series Resistance)500 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral Purpose	
ESR (Equivalent Series Resistance)500 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral Purpose	
Lifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral Purpose	
Operating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral Purpose	
Polarization Polar Applications General Purpose	
Applications General Purpose	
Pinple Current Low Frequency 144 @ 100Hz	
Ripple Current - Low Frequency 1.4A @ 100HZ	
Ripple Current - High Frequency -	
Impedance 590 mOhms	
Lead Spacing 0.394" (10.00mm)	
Size / Dimension 1.378" Dia (35.00mm)	
Height - Seated (Max) 1.457" (37.00mm)	
Surface Mount Land Size -	
Mounting Type Through Hole	
Package / Case Radial, Can - Snap-In	
Report e	errors?

B43504B5277M007 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE ELARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B43504B5277M007 Payment Methods





If you have any question about B43504B5277M007, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com