

B43504B5337M67

Request a Quote

B43504B5337M67 Information

	Part Number	B43504B5337M67	
	Manufacturer	EPCOS (TDK)	
(A Heisener.com	Category	Capacitors Aluminum Electrolytic Capacitors	
A Constantier	Description	CAP ALUM 330UF 20% 450V SNAP	
	Package	Radial, Can - Snap-In	
		For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B43504B5337M67 Specifications

Manufacturer Part NumberB43504B5337M67ManufacturerEPCOS (TDK)CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43504Capacitance330µFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)410 mohm @ 100HzDerating Temperature9000 Hrs @ 105°COperating Temperature60arApplicationsGeneral PurposeRipple Current - Low Frequency1.6A @ 100HzRipple Current - High Frequency900 mohmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)
CategoryCapacitorsCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43504Capacitance330µFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)410 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature440°C ~ 105°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - High Frequency1.6A @ 100HzImpedance490 mOhmsLead Spacing0.394" (10.00mm)
Auminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43504Capacitance330µFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)410 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - High Frequency1.6A @ 100HzRipple Current - High Frequency-Lad Spacing0.394" (10.00mm)
PackageRadial, Can - Snap-InSeriesB43504Capacitance330µFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)410 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - High Frequency-Impedance490 mOhmsLead Spacing0.394" (10.00mm)
SeriesB43504Series330µFCapacitance±20%Tolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)410 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency.Impedance490 mOhmsLead Spacing0.394" (10.00mm)
Capacitance330µFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)410 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.6A @ 100HzRipple Current - High Frequency-Impedance490 mOhmsLead Spacing0.394" (10.00mm)
Tolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)410 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.6A @ 100HzRipple Current - High Frequency-Impedance490 mOhmsLead Spacing0.394" (10.00mm)
Voltage - Rated450VESR (Equivalent Series Resistance)410 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.6A @ 100HzRipple Current - High Frequency-Impedance490 mOhmsLead Spacing0.394" (10.00mm)
ESR (Equivalent Series Resistance)410 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.6A @ 100HzRipple Current - High Frequency-Impedance490 mOhmsLead Spacing0.394" (10.00mm)
Lifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.6A @ 100HzRipple Current - High Frequency-Impedance490 mOhmsLead Spacing0.394" (10.00mm)
Operating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.6A @ 100HzRipple Current - High Frequency-Impedance490 mOhmsLead Spacing0.394" (10.00mm)
PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.6A @ 100HzRipple Current - High Frequency-Impedance490 mOhmsLead Spacing0.394" (10.00mm)
ApplicationsGeneral PurposeRipple Current - Low Frequency1.6A @ 100HzRipple Current - High Frequency-Impedance490 mOhmsLead Spacing0.394" (10.00mm)
Ripple Current - Low Frequency1.6A @ 100HzRipple Current - High Frequency-Impedance490 mOhmsLead Spacing0.394" (10.00mm)
Ripple Current - High Frequency-Impedance490 mOhmsLead Spacing0.394" (10.00mm)
Impedance490 mOhmsLead Spacing0.394" (10.00mm)
Lead Spacing 0.394" (10.00mm)
Size / Dimension 1.378" Dia (35.00mm)
Height - Seated (Max) 1.654" (42.00mm)
Surface Mount Land Size -
Mounting Type Through Hole
Package / Case Radial, Can - Snap-In
Report erro

B43504B5337M67 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE ELARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B43504B5337M67 Payment Methods



If you have any question about B43504B5337M67, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com