



#### B43504B9227M62 Information

Heisener.com

For Reference Only

Part Number B43504B9227M62
Manufacturer EPCOS (TDK)
Category Capacitors

Aluminum Electrolytic Capacitors

DescriptionCAP ALUM 220UF 20% 400V SNAPPackageRadial, Can - Snap-In - 3 Lead

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **B43504B9227M62 Specifications**

Manufacturer Part NumberB43504B9227M62ManufacturerEPCOS (TDK)CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-In - 3 LeadSeriesB43504Capacitance220µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)400 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral Purpose	<b>L</b>	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-In - 3 LeadSeriesB43504Capacitance220μFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)400 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral Purpose	Manufacturer Part Number	B43504B9227M62
$\begin{array}{cccccccccccccccccccccccccccccccccccc$	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-In - 3 LeadSeriesB43504Capacitance $220\mu F$ Tolerance $\pm 20\%$ Voltage - Rated $400V$ ESR (Equivalent Series Resistance) $400 \text{ mOhm } @ 100\text{Hz}$ Lifetime @ Temp. $3000 \text{ Hrs } @ 105 ^{\circ}\text{C}$ Operating Temperature $-40 ^{\circ}\text{C} \sim 105 ^{\circ}\text{C}$ PolarizationPolarApplicationsGeneral Purpose	Category	Capacitors
SeriesB43504Capacitance $220\mu F$ Tolerance $\pm 20\%$ Voltage - Rated $400V$ ESR (Equivalent Series Resistance) $400 \text{ mOhm } @ 100\text{Hz}$ Lifetime @ Temp. $3000 \text{ Hrs } @ 105 ^{\circ}\text{C}$ Operating Temperature $-40 ^{\circ}\text{C} \sim 105 ^{\circ}\text{C}$ PolarizationPolarApplicationsGeneral Purpose		Aluminum Electrolytic Capacitors
Capacitance $220\mu F$ Tolerance $\pm 20\%$ Voltage - Rated $400V$ ESR (Equivalent Series Resistance) $400 \text{ mOhm } @ 100\text{Hz}$ Lifetime @ Temp. $3000 \text{ Hrs } @ 105 ^{\circ}\text{C}$ Operating Temperature $-40 ^{\circ}\text{C} \sim 105 ^{\circ}\text{C}$ PolarizationPolarApplicationsGeneral Purpose	Package	Radial, Can - Snap-In - 3 Lead
Tolerance $\pm 20\%$ Voltage - Rated $400\text{V}$ ESR (Equivalent Series Resistance) $400 \text{ mOhm } @ 100\text{Hz}$ Lifetime @ Temp. $3000 \text{ Hrs } @ 105^{\circ}\text{C}$ Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$ Polarization Polar  Applications General Purpose	Series	B43504
Voltage - Rated $400\text{V}$ ESR (Equivalent Series Resistance) $400 \text{ mOhm } @ 100\text{Hz}$ Lifetime @ Temp. $3000 \text{ Hrs } @ 105^{\circ}\text{C}$ Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$ PolarizationPolarApplicationsGeneral Purpose	Capacitance	220μF
ESR (Equivalent Series Resistance)  Lifetime @ Temp.  3000 Hrs @ 105°C  Operating Temperature  -40°C ~ 105°C  Polarization  Polar  Applications  General Purpose	Tolerance	±20%
Lifetime @ Temp. $3000  \text{Hrs}  @  105^{\circ}\text{C}$ Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$ PolarizationPolarApplicationsGeneral Purpose	Voltage - Rated	400V
Operating Temperature  -40°C ~ 105°C  Polarization  Applications  General Purpose	ESR (Equivalent Series Resistance)	400 mOhm @ 100Hz
Polarization Polar Applications General Purpose	Lifetime @ Temp.	3000 Hrs @ 105°C
Applications General Purpose	Operating Temperature	-40°C ~ 105°C
	Polarization	Polar
	Applications	General Purpose
Ripple Current - Low Frequency 1.11A @ 100Hz	Ripple Current - Low Frequency	1.11A @ 100Hz
Ripple Current - High Frequency -	Ripple Current - High Frequency	-
Impedance 500 mOhms	Impedance	500 mOhms
Lead Spacing 0.394" (10.00mm)	Lead Spacing	0.394" (10.00mm)
Size / Dimension 1.181" Dia (30.00mm)	Size / Dimension	1.181" Dia (30.00mm)
Height - Seated (Max) 1.457" (37.00mm)	Height - Seated (Max)	1.457" (37.00mm)
Surface Mount Land Size -	Surface Mount Land Size	-
Mounting Type Through Hole	Mounting Type	Through Hole
Package / Case Radial, Can - Snap-In - 3 Lead	Package / Case	Radial, Can - Snap-In - 3 Lead
Report errors?		Report errors?

#### **B43504B9227M62 Guarantees**



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### B43504B9227M62 Payment Methods



















# B43504B9227M62 Shipping Methods













If you have any question about B43504B9227M62, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com