

B43504B9277M87

B43504B9277M87 Information

Heisener.com	 B43504B9277M87 EPCOS (TDK) Capacitors Aluminum Electrolytic Capacitors CAP ALUM 270UF 20% 400V SNAP Radial, Can - Snap-In For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B43504B9277M87 Specifications

Manufacturer Part Number B43504B9277M87 Manufacturer EPCOS (TDK) Category Capacitors Aluminum Electrolytic Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Snap-In Series B43504 Capacitance 270µF Tolerance ±20% Voltage - Rated 400V ESR (Equivalent Series Resistance) 320 mOhm @ 100Hz Lifetime @ Temp. 3000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization General Purpose Applications General Purpose Ripple Current - Low Frequency - Ippedance 1.39A @ 100Hz Lead Spacing 0.394" (10.00mm) Size / Dimension 1.81" Dia (30.00mm) Size / Dimension 1.81" Dia (30.00mm) Size / Dimension 6.61" (42.20mm) Height - Seated (Max) 6.61" (42.20mm) Surdae Mount Land Size - Mouning Type Fhough Hole Report emores Report emores		
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43504Capacitance270µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)320 mOhm @ 100HzDigrating Temperature-40°C ~ 105°COperating TemperaturePolarApplicationsGeneral PurposeRipple Current - High Frequency-Impedance1.29A @ 100HzLied Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.661" (42.20mm)Surface Mount Land Size-Mounting TypeFinough HolePackage / CaseRadial, Can - Snap-In	Manufacturer Part Number	B43504B9277M87
Aluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43504Capacitance270µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)320 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationGeneral PurposeRipple Current - Low Frequency1.29A @ 100HzRipple Current - High Frequency-Impedance0.394" (10.0mm)Size / Dimension1.181" Dia (30.00mm)Size / Dimension1.661" (42.20mm)Surface Mount Land Size-Mounting TypeRadial, Can - Snap-In	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-InSeriesB43504Capacitance270µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)320 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency.129A @ 100HzRipple Current - High Frequency0.394" (10.00mm)Lied Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max).661" (42.20mm)Surface Mount Land Size-Mounting TypeFnough HolePackage / CaseRadial, Can - Snap-In	Category	Capacitors
SeriesB43504Capacitance270µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)320 mOhm @ 100HzESR (Equivalent Series Resistance)3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolariFolarizationApplicationsGeneral PurposeRipple Current - Low Frequency-1Impedance1.29A @ 100HzLad Spacing0.394" (10.00mm)Size / Dinension1.181" Dia (30.00mm)Height - Seated (Max)-661" (42.20mm)Surface Mount Land Size-Mounting TypeFnough HolePackage / CaseKadia, Can - Snap-In		Aluminum Electrolytic Capacitors
Capacitance 270μF Capacitance ±20% Tolerance ±20% Voltage - Rated 400V ESR (Equivalent Series Resistance) 320 mOhm @ 100Hz ESR (Equivalent Series Resistance) 3000 Hrs @ 105°C Operating Temperature 40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.29A @ 100Hz Ripple Current - High Frequency - Impedance 410 mOhms Size / Dimension 1.381" Dia (30.00mm) Size / Dimension 1.661" (42.20mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Package	Radial, Can - Snap-In
Tolerance±2%Voltage - Rated400VESR (Equivalent Series Resistance)320 mOhm @ 100HzESR (Equivalent Series Resistance)3000 Hrs @ 105°COperating Temperature-40°C ~ 105°COpariang TemperaturePolarPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - High Frequency-Impedance410 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.661" (42.20mm)Height - Seated (Max)1.661" (42.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can - Snap-In	Series	B43504
Voltage - Rated400VESR (Equivalent Series Resistance)320 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.29A @ 100HzImpedance410 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.661" (42.20mm)Surface Mount Land Size-Mounting TypeFrequencePackage / CaseRatial, Can - Snap-In	Capacitance	270µF
ESR (Equivalent Series Resistance)320 mOhm @ 100HzLifetime @ Temp.3000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.29A @ 100HzImpedance410 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.661" (42.20mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Tolerance	±20%
Lifetime @ Temp.3000 Hrs @ 105°CDeperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.29A @ 100HzRipple Current - High Frequency-Impedance410 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.661" (42.20mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeRadia, Can - Snap-In	Voltage - Rated	400V
Operating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.29A @ 100HzRipple Current - High Frequency-Impedance410 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.681" Dia (30.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeForugationPackage / CaseRadial, Can - Snap-In	ESR (Equivalent Series Resistance)	320 mOhm @ 100Hz
PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.29A @ 100HzRipple Current - High Frequency-Impedance410 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.661" (42.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lifetime @ Temp.	3000 Hrs @ 105°C
ApplicationsGeneral PurposeRipple Current - Low Frequency1.29A @ 100HzRipple Current - High Frequency-Impedance410 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.661" (42.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Operating Temperature	-40°C ~ 105°C
Ripple Current - Low Frequency1.29A @ 100HzRipple Current - High Frequency-Impedance410 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.81" Dia (30.00mm)Height - Seated (Max)1.661" (42.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadia, Can - Snap-In	Polarization	Polar
Higher High Frequency-Impedance410 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.661" (42.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Applications	General Purpose
Impedance410 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.661" (42.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - Low Frequency	1.29A @ 100Hz
I cad Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.661" (42.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - High Frequency	-
Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.661" (42.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Impedance	410 mOhms
Height - Seated (Max)1.661" (42.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Size / Dimension	1.181" Dia (30.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Height - Seated (Max)	1.661" (42.20mm)
Package / Case Radial, Can - Snap-In	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can - Snap-In
1		Report errors?

B43504B9277M87 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B43504B9277M87 Payment Methods



If you have any question about B43504B9277M87, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com